AGENDA



EXTRAORDINARY LOCAL TRAFFIC COMMITTEE MEETING

MONDAY 3 JUNE 2024

11:00 AM



Function of the Local Traffic Committee

Background

Roads and Maritime Services (RMS) is legislated as the Authority responsible for the control of traffic on all NSW Roads. The RMS has delegated certain aspects of the control of traffic on local roads to councils. To exercise this delegation, councils must establish a local traffic committee and obtain the advice of the RMS and Police. The Inner West Council Local Traffic Committee has been constituted by Council as a result of the delegation granted by the RMS pursuant to Section 50 of the Transport Administration Act 1988.

Role of the Committee

The Local Traffic Committee is primarily a technical review and advisory committee which considers the technical merits of proposals and ensures that current technical guidelines are considered. It provides recommendations to Council on traffic and parking control matters and on the provision of traffic control facilities and prescribed traffic control devices for which Council has delegated authority. These matters are dealt with under **Part A** of the agenda and require Council to consider exercising its delegation.

In addition to its formal role as the Local Traffic Committee, the Committee may also be requested to provide informal traffic engineering advice on traffic matters not requiring Council to exercise its delegated function at that point in time, for example, advice to Council's Development Assessment Section on traffic generating developments. These matters are dealt with under **Part C** of the agenda and are for information or advice only and do not require Council to exercise its delegation.

Committee Delegations

The Local Traffic Committee has no decision-making powers. The Council must refer all traffic related matters to the Local Traffic Committee prior to exercising its delegated functions. Matters related to State Roads or functions that have not been delegated to Council must be referred directly to the RMS or relevant organisation.

The Committee provides recommendations to Council. Should Council wish to act contrary to the advice of the Committee or if that advice is not supported unanimously by the Committee members, then the Police or RMS have an opportunity to appeal to the Regional Traffic Committee.

Committee Membership & Voting

Formal voting membership comprises the following:

- one representative of Council as nominated by Council;
- one representative of the NSW Police from each Local Area Command (LAC) within the LGA, being Newtown, Marrickville, Leichhardt and Ashfield LAC's.
- one representative from the RMS; and
- State Members of Parliament (MP) for the electorates of Summer Hill, Newtown, Heffron, Canterbury, Strathfield and Balmain or their nominees.

Where the Council area is represented by more than one MP or covered by more than one Police LAC, representatives are only permitted to vote on matters which effect their electorate or LAC.

Informal (non-voting) advisors from within Council or external authorities may also attend Committee meetings to provide expert advice.

Committee Chair

Council's representative will chair the meetings.

Public Participation

Members of the public or other stakeholders may address the Committee on agenda items to be considered by the Committee. The format and number of presentations is at the discretion of the Chairperson and is generally limited to 3 minutes per speaker. Committee debate on agenda items is not open to the public.

AGENDA

- 2 **Disclosures of Interest**
- 3 Matters Arising from Council's Resolution of Minutes
- Part A Items Where Council May Exercise Its Delegated Functions 4

Traffic Matters

ITEM		Page
LTC0624(2) Item 1	Interim East-West Pedestrian and Cycle Link (EWPCL) Proposal from Sydenham Station to Marrickville Station (Midjuburi - Marrickville Ward/Summer Hill Electorate/ Inner West PAC)	4
LTC0624(2) Item 2	Burrows Avenue and Railway Road, Sydenham - Proposed Bus layover and parking changes (Midjuburi – Marrickville Ward/Hefron Electorate / Inner West PAC)	34
LTC0624(2) Item 3	Railway Road, Sydenham - Proposed changes to parking and traffic arrangements as a result of construction works (Midjuburi-Marrickville Ward / Hefron Electorate / Inner West PAC)	143
LTC0624(2) Item 4	Proposed new kerb extension facilities at intersection of Victoria Street and Clissold Street, Ashfield (Djarrawawunang- Ashfield Ward/Summer Hill Electorate/Burwood PAC)	145

Parking Matters

Nil at the time of printing.

Late Items

Nil at time of printing.

5 Part B - Items for Information Only

Nil at the time of printing.

Part C - Items for General Advice 6

Nil at the time of printing.

7 **General Business**

8 **Close of Meeting**



Item No: LTC0624(2) Item 1

Subject: INTERIM EAST-WEST PEDESTRIAN AND CYCLE LINK (EWPCL) PROPOSAL FROM SYDENHAM STATION TO MARRICKVILLE SATION (MIDJUBURI - MARRICKVILLE WARD/SUMMER HILL ELECTORATE/ INNER WEST PAC)

Prepared By: George Tsaprounis - Coordinator Traffic Engineering Services (south)

Authorised By: Manod Wickramasinghe - Traffic and Transport Planning Manager

RECOMMENDATION

That the following design plans for the proposed interim EWPCL (East West Pedestrian and Cycleway Link) between Sydenham and Marrickville stations submitted by Sydney Metro (Group GSA, EWPCL INTERIM CYCLEWAY DESIGN, drawings A241703 L-2101 to 2104 issue H, A241703 L-2105 to 2110 Issue I and ACOR Consultants, EWPCL INTERIM CYCLEWAY DESIGN SYDENHAM STATION TO MARRICKVILLE STATION, drawings C05-0001 to C05-0004 Issue F and C05-1000 Issue F) be approved, subject to the following conditions:

- a) Sydney Metro undertaking all maintenance and management activities (including community liaison) for the duration of the interim EWPCL;
- b) any amendments and or changes to the interim EWPCL be undertaken by Sydney Metro;
- c) all proposed treatments are to be constructed, installed or marked as per Council standards and/or specifications and to the satisfaction of Council; and
- d) Sydney Metro undertake all necessary work to implement a 40 km/h zone for the following streets/lanes (Meeks Road, Gerald Street, Sydney Lane, Maude Lane and Meeks Lane) prior to completion of the works, subject TfNSW approval.

STRATEGIC OBJECTIVE

This report supports the following strategic directions contained within Council's Community Strategic Plan:

2: Liveable, connected neighbourhoods and transport

EXECUTIVE SUMMARY

This report outlines proposed interim EWPCL (East West Pedestrian and Cycleway Link) between Sydenham and Marrickville and seeking approval for its implementation. This cycleway link will play an important role during the upcoming track possession of Southwest Rail Line between Sydenham and Bankstown by providing alternate options for the commuters and local community. Part of this interim EWPCL is consistent with Council's future bike strategy.

It is recommended that the proposed attached design submitted by Sydney Metro be approved subject to conditions.

BACKGROUND

Sydney Metro proposes to deliver an interim cycle link between Marrickville Station and Sydenham Station for the community to use during the final Metro conversion shutdown of the T3 Bankstown Line. It is planned for the interim cycle link to be opened before the final conversion shutdown of up to 12 months. Works along the route are proposed at Lower

Railway Parade, Marrickville Road, Meeks Road, Victoria Road up to Station Street. (refer to figure 1 below).

HR WIZST

These works form part of Southwest Link– a fully integrated transport plan for Southwest Sydney giving passengers choices between dedicated and existing local bus services, rail services, light rail, active transport and turn up and go Metro services to and from Sydenham station.




Figure 1 – Proposed route

DISCUSSION

The EWPCL is a Sydney Metro project which seeks to improve east- west pedestrian and cyclist facilities between Sydenham and Bankstown along the T3 line. Components of the end-state EWPCL design are being led by Council and procurement for undertaking the detailed design is currently in progress. Sydney Metro will then undertake the delivery component. Sydney Metro will also be undertaking community engagement for the end-state EWPCL later this year.

Sydney Metro has engaged with both Council and TfNSW staff to ensure that comments and requirements have been considered and incorporated into the design as agreed upon by the stakeholders. The attached design plans are the final product of these stakeholder meetings.

It should be noted that there is potential alignment with some of the interim EWPCL and Marrickville Road East routes that form part of Council's capital works program. Marrickville Road East provides a separated cycleway along Marrickville Road from Meeks Road to Railway Parade/Gleeson Avenue and is currently undergoing detailed design. The final treatments for Marrickville Road will differ from those included as part of the TTP which is expected to provide shared paths rather than a separated cycleway. In this respect, Council may be able to retain constructed infrastructure where it provides synergies with the proposed Marrickville Road East route and where it provides a benefit to the public.

Design components of the proposed works include:

• Shared path along Lower Railway Parade – This will involve the installation of relevant signage, line marking and symbols, various repair works along the footpath, tree trimming and tree planting (refer to attached drawings A241703 L-2101 and 2102 issue H)

- Shared path along Marrickville Road (northern side from Lower Railway Parade to Sydney Street and southern side from Sydney Street to Meeks Road) – This will involve hazard driveway markings, installation of relevant signage, line marking and symbols, painted road treatment on Marrickville Road, new kerb blisters (either side of Buckley Street), various works along the footpath, stamped on-road threshold treatment at Barclay Street, Sydney Street and Gerald Street and hold rails to existing refuge island on Marrickville Road at Sydney Street (refer to attached drawings A241703 L-2103 and 2104 issue H and 2105 Issue I, C05-0003 Issue F and C05-0002 Issue F)
- Bi-directional on-road bicycle lane along Meeks Road between Sydney Lane and Maude Lane (eastern side) and on-road mixed traffic treatment for the remainder of Meeks Road to Victoria Road This will involve on road stamped threshold treatment on Meeks Road, either side of Marrickville Road, Sydney Lane, Marrickville Lane and Maude Lane, painted road treatment across driveways, separation treatment between bicycle lane and parking lanes, , installation of relevant signage, line marking and symbols, painted bicycle refuge and transition zone and on-road threshold treatment at the bend in Meeks Road (refer to attached drawings A241703 L-2106, 2107 and 2108 Issue I and C05-0004 Issue F)
- Use of existing council bi-directional lane along Victoria Road from Meeks Road to Myrtle Street and connection to off road shared path connecting Marrickville Station to Victoria Road – This will involve installation of relevant signage, line marking and symbols, installation of speed cushions and refuge island (refer to attached drawings A241703 L-2109 and 2110 Issue I, C05-0001 and C05-1000 Issue F)

It should be noted that a Pre-Construction Concept Design Road Safety Audit was undertaken to support the proposal.

Council Officers did raise concerns in relation to cyclists crossing at the intersection of Buckley Street and Marrickville Road as the intersection does carry large volume of traffic and the geometric features of the intersection are not ideal for a pedestrian crossing. Although the cyclist will be asked to dismount at this location, this will provide motorists with additional stopping time to give way to crossing cyclists.

The 'pros and cons' of installing a mixed traffic treatment versus a bi-directional cycle lane in Meeks Road was discussed prior to the final proposal for a bi-directional cycle lane to be provided on the eastern side of the roadway. This is envisaged to provide a safe and separated cycleway facility and aligns with the end state EWPCL design.

Following a discussion on lowering the speed limit on Meeks Road, Council Officers asked that Sydney Metro pursue lowering the speed limit along Meek Roads (and adjacent Street(s)/laneways to 40km/h.

Sydney Metro will be requested to construct, install and line mark all proposed treatments as per Council standards or specifications and to the satisfaction of Council.

COMMUNITY ENGAGEMENT

Sydney Metro undertook doorknocks with adjacent businesses to the proposed cycle link alignment (as well as on Buckley Street) on Wednesday 15 May and Thursday 16 May. 27 businesses were spoken to directly about the interim path (and provided with a copy of the factsheet), while the cycle link fact sheet was letterbox dropped at other businesses (where possible) and adjacent residential properties. Areas where doorknocks were undertaken are marked in yellow in the below map.



Business feedback was generally positive. A summary of issues/concerns is detailed below (further consultation will be conducted with these businesses prior to the start of construction).

Sydney Metro have indicated that they will conduct further engagement following approval of this proposal by the Traffic Committee, including:

- Distributing the fact sheet to a wider footprint of properties in Marrickville
- Emailing the fact sheet to Sydney Metro's Marrickville Station distribution list
- Distributing the fact sheet as a handout to train users at Marrickville and Sydenham Stations ahead of construction of the interim link commencing.

Issue raised	Sydney Metro response
Safety issues re heavy vehicle/car driveway access in and out and potential conflict with cyclists using path	 Several measures, including the marking of chevrons on business driveways along the link, are within the design to increase awareness of potential for heavy vehicles in the area Sydney Metro will continue to consult with businesses with these concerns around potential for additional signage (non-regulatory signage)
Loss of parking on Lower Railway Parade throughout shutdowns Driver behaviour issues during previous shutdowns	 These are unrelated to the interim cycle path Parking changes relate to previous shutdowns where Lower Railway Parade was used as a laydown area for replacement buses It is likely that there will be less parking loss during final shutdown, alternative layover spaces are currently being progressed (TBC) Drivers will be briefed and reminded about
	appropriate behaviours.
Potential parking loss on Meeks Road	 The design minimises impacts to local parking, resulting in the loss of only two spots on Meeks Road

CONCLUSION

It is recommended that Council conditionally approve the following attached design drawings for the interim EWPCL (East West Pedestrian and Cycleway Link) between Sydenham and Marrickville. These conditions to pertain to responsibilities for management and maintenance as well as responsibilities pre, post and during construction of the route.



FINANCIAL IMPLICATIONS

There are no financial implications associated with the implementation of the proposed recommendations outlined in the report.

ATTACHMENTS

1. <u></u> ↓	EWPCL	INTERIM	CYCLEWAY	DESIGN

2.0 SYDENHAM STATION TO MARRICKVILLE STATION - CIVIL WORKS EWPCL INTERIM CYCLEWAY DESIGN SYDENHAM STATION TO MARRICKVILLE STATION - LAYOUT, LINEMARKING AND SIGNAGE

EWPCL INTERIM CYCLEWAY DESIGN SYDENHAM STATION TO MARRICKVILLE STATION CIVIL WORKS



DRAWING NUMBER	DRAWING TITLE
C01-0001	COVER SHEET, LOCALITY PLAN AND DRAWING SCHEDULE
C01-0101	CONSTRUCTION NOTES
C05-0001	GENERAL ARRANGEMENT PLAN - SHEET 1
C05-0002	GENERAL ARRANGEMENT PLAN - SHEET 2
C05-0003	GENERAL ARRANGEMENT PLAN - SHEET 3
C05-0004	GENERAL ARRANGEMENT PLAN - SHEET 4
C05-1000	TURNING PATH PLAN
C07-0001	NOTES AND DETAILS

f and a second

an at the second se	ISSUED FOR APPROVAL 22 05.24 MDM VK	Noth	Scala	SYDNEY METRO	Archited GROUP GSA PTY LTD	Ac		Project EWPCL INTERIM CYCLEWAY DESIGN SYDENHAM STATION TO MARRICKVILLE STATION	Drawing Title CIVIL COVER SHEE	ET, LOCALITY F	PLAN AND DR	RAWING SCHEI	JULE
Ē	ISSUED FOR APPROVAL 11.05.24 MDM JK ISSUED FOR APPROVAL 14.05.24 MDM JK ISSUED FOR APPROVAL 03.05.24 MDM JK			LEVEL 43, 680 GEORGE ST	LEVEL 7, 80 WILLIAM ST	OR	Charlestown NSW 2290 T +61 2 4926 4811		Drawn MDM	Designed JK	Q.A. Check JPR	03.05.24	ale@A1 ↓.T.S.
	NOT ISSUED NOT ISSUED Descrition Date Date: Account	-	PRINT IN COLOUR 🔘	SYDNEY, NSW, 2000	SYDNEY, NSW, 2011 T: +612 9361 4144	CONSULTANTS	<u>@@@</u>	NOT FOR CONSTRUCTION	Project No. NA240270	Drawing No. C01-0001			issue F

Attachment

GENERAL NOTES

- 1. THE DRAWING DIMENSIONS SHALL NOT BE OBTAINED BY SCALING.
- THESE DRAWINGS SHALL BE READ IN CONJUNCTION WITH THE SPECIFICATION AND WRITTEN INSTRUCTIONS. ANY DISCREPANCY OR VARIATION SHALL BE REFERRED TO THE SUPERINTENDENT BEFORE PROCEEDING WITH THE WORK.
- ALL WORK TO BE IN ACCORDANCE WITH INNER WEST COUNCIL ENGINEERING REQUIREMENTS FOR DEVELOPMENT AND INNER WEST COUNCIL STANDARD DRAWINGS AND SPECIFICATIONS.
- NO ADDITIONAL OR P.C. WORKS SHALL BE UNDERTAKEN WITHOUT THE SUPERINTENDENTS APPROVAL. CONFIRM COUNCIL INSTRUCTIONS WITH SUPERINTENDENT
- 5. THE CONTRACTOR MUST ENSURE SUPERINTENDENT AND/OR COUNCIL APPROVAL OF MATERIALS, PRIOR TO DELIVERY TO SITE.
- 6. DIVERSION OF WATER AND THE PROTECTION OF WORKS IS THE CONTRACTORS RESPONSIBILITY.
- THE CONTRACTOR HAS SOLE RESPONSIBILITY TO EXERCISE CARE AND TAKE PRECAUTIONS TO ENSURE CONSTRUCTION ACTIVITES DO NOT AFFECT ADJACENT PROPERTIES, ACCESS OR STRUCTURES, MAINTAIN EMARKMENTS AND STRUCTURES IN STABLE CONDITION DURING CONSTRUCTION ENSURING NO PART IS OVERSTRESSED. TEMPORARY STRUCTURES, FORMWORK, TEMPORARY BRACING, SHORING AND HE LIKE SHALL BE THE SOLE REPROVISILITY OF THE CONTRACTOR.
- THE CONTRACTOR WILL BE RESPONSIBLE FOR THE FULL OA DOCUMENTATION OF THE PROJECT TO ENSURE WORKS MEET THE RELEVANIT SECTIONS OF AUSPEC FOR ROADS, DRAINAGE, WATER AND SEWEE A COMPLETE ITP PLAN SHALL BE SUBMITTED TO THE SUPERINTENDENT FOR APPROVAL PRIOR TO WORKS COMMENCING ON SITE
- CONTRACTOR IS TO VERIFY THE LOCATION OF ALL SERVICES WITH EACH RELEVANT AUTHORITY. ANY DAMAGE TO SERVICES SHALL BE REPAIRED BY THE CONTRACTOR OR THE RELEVANT AUTHORITY AT THE CONTRACTOR'S EXPENSE. SERVICES SHOWN ON THESE PLANS ARE ONLY THOSE EVIDENT AT THE TIME OF SURVEY.
- 10. UNDERTAKE WORKS TO PRINCIPLES OF AS 9001. SUBMIT WORK METHOD STATEMENT TO SUPERINTENDENT.
- HOLD POINTS SHALL APPLY TC: APPROVAL OF WORK METHOD STATEMENT APPROVAL OF TRAFFIC CONTROL PLAN LOCATION OF INGROUND SERVICES SETUDI OF EACH AREA OF WORKS CERTIFICATION OF SUBGRADE STORMWATER PIPEWORK PRIOR TO BACKFILL WORK AS EXECUTED SURVEY GEOTECHNICAL CERTIFICATION
- 11. ALL WORKS ARE TO BE SETOUT BY A REGISTERED SURVEYOR.
- 12. ALL LEVELS SHALL BE OBTAINED FROM ESTABLISHED BENCH MARKS ONLY. STANDARD DATUM FOR ALL DRAWINGS IS AUSTRALIAN HEIGHT DATUM (A.H.D.).
- 13. A TRAFFIC CONTROL PLAN TO AS 1742.3 IS TO BE SUBMITTED TO COUNCIL FOR APPROVAL PRIOR TO WORKS COMMENCING.
- 14. SERVICE CONDUITS SHALL BE PLACED AS DIRECTED BY AUSGRID, NBN, JEMENA AND AS REQUIRED BY COUNCIL.
- 15. PROPOSED SERVICES CROSSING EXISTING ROADS SHALL BE THRUST BORED UNDER THE ROAD SO AS NOT TO DAMAGE EXISTING SURFACES.
- ALL NEW WORKS ARE TO MAKE SMOOTH JUNCTIONS WITH ALL EXISTING CONDITIONS. AC JOINTS TO BE SAW CUT AT CONNECTION TO EXISTING PAVEMENT. THE CONTRACTOR IS TO MAKE ALL DUE ALLOWANCES FOR WORKS DURING CONSTRUCTION.

PAVEMENT MARKING AND SIGNAGE NOTES

- THE WORK SHALL INCLUDE ALL PAVEMENT MARKING TO ROADS, HARDSTANDS, PATHS, CARPARKS AND THE TRAFFICABLE AREAS.
- PAVEMENT MARKING AND PAINT SHALL BE IN ACCORDANCE WITH AS 1742.2 AND THE RELEVANT LOCAL AND STATE AUTHORITY GUIDELINES AND SPECIFICATIONS.
- PAVEMENT MARKING SHALL BE SPOTTED OUT AND APPROVED PRIOR TO SPRAYING.

2.

3

4

6.

q

2.

- PAINT SHALL BE APPLIED AT A WET THICKNESS OF BETWEEN 0.35mm TO 0.40mm.
- EXISTING PAVEMENT MARKING IN CONFLICT WITH NEW WORKS SHALL BE REMOVED IN ACCORDANCE WITH As 1742. REDUNDANT PAVEMENT PARKING MUST BE REMOVED BY GRINDING, BLASTING OR RESURFACING, PAINTING OVER WITH BLACK BITUMINOUS PAINT IS NOT ACCEPTABLE.
- RAISED PAVEMENT MARKERS ARE TO BE INSTALLED IN ACCORDANCE WITH AS 1742.2 AND AS DIRECTED BY SUPERINTENDENT.
- SIGNAGE SHALL BE IN ACCORDANCE WITH AS 1742.1, AS 1742.2, AS 2890.1 AND THE RELEVANT LOCAL AND STATE AUTHORITY GUIDELINES AND SPECIFICATIONS.
- EXISTING SIGNAGE IN CONFLICT WITH NEW WORKS SHALL BE REMOVED OR RELOCATED AS DIRECTED BY THE SUPERINTENDENT.
- PAVEMENT MARKING NOTATION IS AS FOLLOWS;
- DOUBLE TWO-WAY EDGE LINE ELI NO STOPPING LINE PEDESTRIAN CROSSING (ZEBRA) BICYCLE CROSSING LINE TBC

SAFETY IN DESIGN

- THE DESIGN SAFETY ASSESSMENT HAS BEEN CARRIED OUT WITH REFERENCE TO CURRENT WHS REGULATIONS FOR DESIGN TO BE SAFE SO FAR AS REASONABLY PRACTICABLE. HAZARD AND RISK IDENTIFICATION IS BASED ON INFORMATION AVAILABLE TO THE DESIGNER AT THE TIME OF THE DESIGN.
- IDENTIFIED HAZARDS ARE THOSE WHICH ARE AFFECTED BY THE DESIGN, AND ARE WITHIN THE CONTROL OF THE DESIGNER.
- HAZARDS AND RISK RELATING TO CONSTRUCTION, OPERATION, MAINTENANCE AND DEMOLITOR MUST BE CONSIDERED BY THE OWNER, MANAGER, BUILDER, USER, MAINTAINER AND DEMOLSIHER. ALL SUCH ENTITIES ARE ASSUMED TO BE QUALIFIED, COMPETENT AND EXPERIENCED.
- SEEK ADVICE WHERE ACTIVITIES ARE OUTSIDE THE FIELD OF EXPERIENCE OF THE OPERATOR/BUILDER/MAINTAINER, INCLUDING BUT NOT LIMITED TO QUALIFIED STRUCTURAL AND GEOTECHNICAL ENGINEERS.
- ATYPICAL HAZARDS HAVE BEEN IDENTIFIED IN THE DESIGN PROCESS.
- ATYPICAL HAZARDS IDENTIFIED ARE; • CLOSE PROXIMITY TO MOVING VEHICLES
- WHERE STATE OR TERRITORY LEGISLATION EXISTS, OR OTHERWISE AS MAY BE REQUIRED, A DESIGN VERIFICATION STATEMENT WILL BE PROVIDED BY THE CONSULTING ENGINEER.

EXISTING SERVICES AND FEATURES

- THE CONTRACTOR SHALL ALLOW FOR THE CAPPING OFF, EXCAVATION, REMOVAL AND DISPOSAL IF REQUIRED OF ALL EXISTING SERVICES IN AREAS AFFECTED BY WORKS WITHIN THE CONTRACT AREA AS DIRECTED OTHERWISE BY THE SUPERINTENDENT.
- 2. THE CONTRACTOR SHALL ENSURE THAT AT ALL TIMES SERVICES TO ALL BUILDINGS NOT AFFECTED BY THE WORKS ARE NOT DISRUPTED.
- 3. EXISTING BUILDINGS, EXTERNAL STRUCTURES, AND TREES SHOWN ON THESE DRAWINGS ARE FEATURES EXISTING PRIOR TO ANY DEMOLITION WORKS.
- 4. CONTRACTOR SHALL CONSTRUCT TEMPORARY SERVICES TO MAINTAIN EXISTING SUPPLY TO BUILDINGS REMAINING IN OPERATION DURING WORKS TO THE SATISFACTION AND APPROVAL OF THE SUPERINTENDENT. ONCE DIVERSION IS COMPLETE AND COMMISSIONED THE CONTRACTOR SHALL REMOVE ALL SUCH TEMPORARY SERVICES AND MAKE GOOD TO THE SATISFACTION OF THE SUPERINTENDENT.
- INTERRUPTION TO SUPPLY OF EXISTING SERVICES SHALL BE DONE SO AS NOT TO CAUSE ANY INCONVENIENCE TO THE PRINCIPAL. CONTRACTOR TO GAIN APPROVAL OF SUPPENITENDENT FOR TIME OF INTERRUPTION.

INNER WEST COUNCIL STANDARD DRAWINGS

THE FOLLOWING STANDARD DRAWINGS ARE TO BE ADOPTED UNLESS NOTED OTHERWISE

- C1 STANDARD CYCLEWAY DETAILS
- E1 SEDIMENT & EROSION CONTROL PLAN F2 - 100mm THICK REINFORCED CONCRETE FOOTPATH
- F3 150mm THICK REINFORCED CONCRETE FOOTPATH
- F3 ISUMINI THICK REINFORCED CONCRETE FOC
 F4 KERB RAMPS
 F9 ASPHALTIC CONCRETE PAVED FOOTPATH
- R1 STANDARD KERB PROFILES
- R2 CONCRETE ROAD SLAB REPLACEMENT WORK
- R5 STANDARD FLEXIBLE ROAD PAVEMENTS RECONSTRUCTION WITH ASPHALTIC CONCRETE OVER DGB
 R6 - STANDARD FLEXIBLE ROAD PAVEMENTS - FULL DEPTH ASPHALTIC CONCRETE
- ROAD PAVEMENTS
 R7 ASPHALTIC CONCRETE ROAD HEAVY PATCHING
- T2 WATTS PROFILE SPEED HUMPS & ASPHALTIC SPEED CUSHIONS (WHERE PERMANENT FIXTURES ARE PROPOSED)
- DRIVEWAY LINE MARKING DRAWING

ALL STANDARD DETAILS AND PAVEMENT WORKS ARE TO BE CONFIRMED ON SITE WITH COUNCILS WORKS SUPERVISOR AND MATCH TO ADJACENT SURROUNDING CONDITIONS

EROSION AND SEDIMENT CONTROL NOTES


- PROVIDE EROSION AND SEDIMENT CONTROL MEASURES DURING CONSTRUCTION TO COUNCIL STANDARDS AND CONFORMING TO LANDCOM SOILS & CONSTRUCTION Vol 1, 4th EDITION, MARCH 2004.
- PREPARE EROSION AND SEDIMENT CONTROL PLAN AND OBTAIN COUNCIL APPROVAL PRIOR TO WORKS.
- ALL PERIMETER CONTROL DEVICES ARE TO BE INSTALLED PRIOR TO WORK COMMENCING AND BE MAINTAINED DURING CONSTRUCTION. LOCATE SEDIMENT FENCE WITHIN WORKS BOUNDARY.
- CONTRACTOR TO DEFINE ACCESS, STOCKPILE AND OTHER AREAS PRIOR TO WORK COMMENCING.
- . PROVIDE A SINGLE POINT OF ACCESS TO THE SITE.
- MINIMISE SITE DISTURBANCE AND REDUCE STOCKPILING TO A LEVEL NECESSARY TO CONSTRUCT THE WORKS. STOCKPILE AREAS, CONSTRUCTION ACCESSES AND NO GO AREAS TO BE DEFINED AND CONFIRMED PRIOR TO COMMENCEMENT OF WORK, FENCE NO GO AREAS.
- PROVIDE MEASURES AT STOCKPILES TO DIVERT CLEAN WATER AND COLLECT SEDIMENT DOWNSTREAM, LOCATE STOCKPILES AWAY FROM STORMWATER FLOWS.
- PROVIDE AND MAINTAIN PERMANENT GRASSING AS SOON AS POSSIBLE AFTER CONSTRUCTION. STAGE WORKS AS INCESSARY GRASS SPECIES SHALL BE TO COUNCIL REQUIREMENTS, GRASS TURF TABLEDRAINS AND SWALES. MULCH (IF AVAILABLE FROM STEC LEARNING) AND SEED ALL OTHER DISTURBED AREAS INCLUDING TREIN-TIES, WHICH HAVE NOT BEEN TURFED. ON COMPLETION OF WORKS PROVIDE STRIP TURFING, SEE CENTRAL NOTES.
- 9. CONTROL DUST BY WINDBREAKS, WATERING ETC.
- 10. EROSION AND SILT PROTECTION MEASURES ARE TO BE MAINTAINED AT ALL TIMES. ADJUST TO SUIT STAGING AND PROGRESS.
- 11. HIGH EROSION AREAS, INCLUDING BATTERS TO BE STABILISED WITHIN 7 DAYS OF COMPLETING OF WORKS AND EARLIER IF DIRECTED BY SUPERINTENDENT.
- 12. ALL STABILISED WORKS ARE TO BE MAINTAINED UNTIL COMPLETION OF WORKS.
- REMOVE TEMPORARY MEASURES AFTER COMPLETION OF CONSTRUCTION AND STABILISATION OF WORKS.




		North	Scale	SYDNEY METRO	Architect GROUP GSA PTY LTD		ACOR Consultants Pty Ltd	EWPCL INTERIM CYCLEWAY DESIGN	Drawing Title CIV/II				
5				STUNET METRO	GROUP GSA PTY LTD		The Forum, Level 1		CONSTRUCT	TION NOTES			
1	F ISSUED FOR APPROVAL 22.0	35.24 MDM JK				AC	Suite 1 240-244 Pacific Highway	SYDENHAM STATION TO MARRICKVILLE STATION	00110111001	1011110120			
	E ISSUED FOR APPROVAL 17.0	05.24 MDM JK					Charlestown NSW 2290		Drawn	Designed	0.4 Cherk	Date	Scale (B A1
	D ISSUED FOR APPROVAL 14.0	05.24 MDM JK					T +61 2 4926 4811		MDM	IK	IPR	03.05.24	NTS
	C ISSUED FOR APPROVAL 03.0	05.24 MDM JK		LEVEL 43, 680 GEORGE ST	LEVEL 7, 80 WILLIAM ST	\sim \times			morm	UIC	UTIX	00.00.24	11.1.2.
	B NOT ISSUED			SYDNEY, NSW, 2000	SYDNEY, NSW, 2011	- - -			Project No.	Drawing No.			Issue
	A NOT ISSUED		PRINT IN COLOUR C		T: +612 9361 4144	CONVENTION OF	- -	NOT FOR CONSTRUCTION	NA240270	C01-0101			F
-	Issue. Description Da	ate Drawn Approved			1. 1012 0001 4144	and another state							
	A COMPOSIT JAN AND STATES AND A	AL 40.070 000 040	and a second	dealer from 1000 Occurrence Dealer									

f this design and plan is the propenty of ACOR Consultants Pty Ltd, ACN 679 306 246 ABN 40.079 306 246, all rights reserved. It must not be used, modified, reproduced or copied wholly or in part without written permission from ACOR Consultants Pty Ltd.


Item 1






~

Item 1




IER WEST

Attachment




Attachment

`



issue F





Attachment

EWPCL INTERIM CYCLEWAY DESIGN SYDENHAM STATION TO MARRICKVILLE STATION







17

T ON SIGNAGE DISTANCE NEWTOWN SHOW x M OR XK KENHAM STATION SHOW x M OR XK REKVILE STATION SHOW x M OR XK KENHAM STATION SHOW x M OR XK KENAM STATION SHOW x M OR XK	KM
ENHAM STATION SHOW X M OR XK NCKVLLE STATION SHOW X M OR XK ENHAM STATION SHOW X M OR XK ENHAM STATION SHOW X M OR XK CKVLLE STATION SHOW X M OR XK SERVAM STATION SHOW X M OR XK SERVAM STATION SHOW X M OR XK SERVAM STATION SHOW X M OR XK SHOW X M OR XK SHOW X M OR XK SHOW X M OR XK SHOW X M OR XK SHOW X M OR XK SHOW X M OR XK SHOW X M OR XK SHOW X M OR XK SHOW X M OR XK SHOW X M OR XK SHOW X M OR XK SHOW X M OR XK SHOW X M OR XK SHOW X M OR XK SCKVLLE STATION SHOW X M OR XK SHOW X M OR XK SHOW X M OR XK	KM
ENHAM STATION SHOW X M OR XK NCKVLLE STATION SHOW X M OR XK ENHAM STATION SHOW X M OR XK ENHAM STATION SHOW X M OR XK CKVLLE STATION SHOW X M OR XK SERVAM STATION SHOW X M OR XK SERVAM STATION SHOW X M OR XK SERVAM STATION SHOW X M OR XK SHOW X M OR XK SHOW X M OR XK SHOW X M OR XK SHOW X M OR XK SHOW X M OR XK SHOW X M OR XK SHOW X M OR XK SHOW X M OR XK SHOW X M OR XK SHOW X M OR XK SHOW X M OR XK SHOW X M OR XK SHOW X M OR XK SHOW X M OR XK SCKVLLE STATION SHOW X M OR XK SHOW X M OR XK SHOW X M OR XK	KM
RCKVLLE STATION SHOW x M OR X K SHOW x M OR X K SHOW x M OR X K SCKVLLE STATION SHOW x M OR X K VENHAM STATION SHOW x M OR X K ROKVLLE STATION SHOW x M OR X K	KA NEW KA NEW KA NEW KA NEW KA NEW KA NEW
ENHAND STATION SHOW X M OR X K OCKVLLE STATION SHOW X M OR X K SHOW X M OR X K SHOW X M OR X K SHOW X M OR X K SHOW X M OR X K SCRULLE STATION SHOW X M OR X K STATION SHOW X M OR X K SCRULLE STATION SHOW X M OR X K	KM
CKVLLE STATION - SHOW x M OR X K SHOW x M OR X K SHOW x M OR X K NDKVLLE STATION SHOW x M OR X K SHOW x M OR X K SHOW x M OR X K SHOW x M OR X K SHOW x M OR X K SHOW x M OR X K SHOW x M OR X K SHOW x M OR X K SHOW x M OR X K SHOW x M OR X K SHOW x M OR X K SERVICE STATION SHOW x M OR X K	KM NEW KM CAN NEW KM CAN NEW KM CAN NEW KM CAN NEW
ENHAM STATION SHOW X M OR X K ACKVLLE STATION SHOW X M OR X K MISTATION SHOW X M OR X K MISTATION SHOW X M OR X K ACKVLLE STATION SHOW X M OR X K EXHAM STATION SHOW X M OR X K EXHAM STATION SHOW X M OR X K EXHAM STATION SHOW X M OR X K RCKVLLE STATION SHOW X M OR X K RCKVLLE STATION SHOW X M OR X K RCKVLLE STATION SHOW X M OR X K	KM M KM NEW KM NEW KM NEW KM NEW
RCKVLLE STATION SHOW x M OR X K SHOW x M OR X K SHOW x M OR X K SHOW x M OR X K SHOW x M OR X K VCKVLLE STATION SHOW x M OR X K NCKVLLE STATION SHOW x M OR X K NCKVLLE STATION SHOW x M OR X K	KM NEW KM NEW KM NEW KM NEW
SHOW X M OR X K SHOW X M OR X K NCKVILE STATION SHOW X M OR X K NEWHAM STATION SHOW X M OR X K NCKVILE STATION SHOW X M OR X K	KM NEW KM NEW KM NEW
NCKVLLE STATION SHOW x M OR X K VENHAM STATION SHOW x M OR X K NCKVLLE STATION SHOW x M OR X K VENHAM STATION SHOW x M OR X K NCKVLLE STATION SHOW x M OR X K NCKVLLE STATION SHOW x M OR X K	KM NEW KM
EENAAM STATION SHOW X M OR X K XICKVILLE STATION SHOW X M OR X K EENAAM STATION SHOW X M OR X K XICKVILLE STATION SHOW X M OR X K	KM NEW
RICKVILLE STATION SHOW X M OR X K VENHAM STATION SHOW X M OR X K RICKVILLE STATION SHOW X M OR X K	
NENHAM STATION SHOW X M OR X K	км
RICKVILLE STATION SHOW X M OR X K	
	M NEW
	км
DENHAM STATION SHOW X M OR X K	<mark>км</mark> NEW
RICKVILLE STATION SHOW X M OR X K	км
RICKVILLE STATION	
BUSES BUS SYMBOL AND ARR	łow
BUSES BUS SYMBOL AND ARR	NOW
SYDENHAM PEDESTRIAN SYMBOL A a Marrickville Road ARROW	AND
BUSES BUS SYMBOL AND ARR	ROW NEW
SYDENHAM PEDESTRIAN SYMBOL A a Marrickville Road ARROW	AND
SYDENHAM a Marrickville Road SHOW X M OR X K	км
	STODIANM Maricakie Raad PECESTRIM STANDUC MARICAKIE Raad UIS SYMBOL AND ARR STODIANM Maricakie Raad STODIANM S




Item 1







ER WEST








Item 1



—

ltem



面

Extraordinary Local Traffic Committee Meeting



1

129

-


1


傪

G9-57


6.

LEGEND











Item 1













Item 1





Attachment 2




Amendments		Client		Architect	Project Title			
Devotes A CLEENTIBLE B ISSUE FOR RSA C FIRAL OCUMENTATION D FIRAL ISSUE	De EXECUTOR	Sydowy Metro Lavar 43, 800 George Streat, Sydney XSW 2000 Sydney XSW 2000 Consultant Col Construction A Col Construction C	Consultant Traffic Conjeer / Final na na francjeer / Final na Althouse (Final Strategy) Althouse (Final Strategy) Althouse (Final Strategy) Info@(Final Strategy) Info@(Final Strategy) (Final St	COURSESSON	EWPCL Interim Cycleway Design	Drawing Cruatel (data) Crawing Cruatel (data) Unified Agrossid East Priget Na Databage Age 24 17 003 Location This deates in the schedule commencement of any ways, waiting data Compared to the schedule commencement of any ways, waiting data Compared to the schedule commencement of any ways, waiting data Compared to the schedule commencement of any ways, waiting data Compared to the schedule commencement of any ways, waiting data Compared to the schedule commencement of any ways, waiting data Compared to the schedule commencement of any ways, waiting data Compared to the schedule commencement of any ways, waiting data Compared to the schedule commencement of any ways, waiting data Commencement of any ways, waiting data Commencement Comme	A Pty Ltd and may not be altered y any means in part or in whole SA Pty Ltd. of and verified on site prior to the or drawing or labrication of	•


- LIMIT OF THICKENED PAVEMENT SLAB UNDER SHOWN DASHED NOTE: SETBACK DISTANCE FROM KERB TO BE THE SAME IN AC PAVING FACE OF KERB OI SIGNAGE POST PLAN -WHITE LINEMARKING 400mm WIDE, 400mm LINE, 400mm GAP REFER COUNCIL STANDARD DETAILS FOR OFFSET REQUIREMENTS REFER TO PLANS FOR KERB SEPARATOR 400 a 400 y (· · · · · · · · ·) 75mm GALVANSED POST IRON PIPE GREEN PAINTED ASPHALT (XB) Ŷ 300mm DIA 15MPa CONCRETE FOOTING TO ALL NEW AND RELOCATED SIGNAGE POSTS 60 20 - WHITE LINEMARKING 100mm WIDE, 400mm LINE, 400mm GAP 12mm DIA STEEL SPIKES THROUGH GALVANISED POST 1500 1500 DRIVEWAY 300 TYPICAL SIGNAGE POST DRIVEWAY - MARKINGS SECTION PLAN REFER TO GA PLAN FOR LAYOUT AND DRIVEWAY OFFSETS. φ 3 x ORCA 300 SERIES ISLANDS FIXED TO EXISTING ASPHALT SURFACE AS PER MANUFACTURER SPECIFICATIONS. (1 x 500600 INTERMEDIATE ISLAND AND 2 x 500601 ISLAND WITH ENDS) •E7 LINE 100MM WIDE SOLID LINE ON BOTH SIDES OF CYCLEWAY 50mm DIA HOT DIPPED GALVANISED HOLDING RAIL WITH A YELLOW POWDER COATED FINISH AND CLASS 2 REDIWHITE REFLECTIVE BANDS. REFER TO MATERIALS SCHEDULE. E7 LINE 100MM WIDE SOLID LINE AT THE INTERFACE OF ROAD & 400MM CYCLEWAY SEPARATION EXISTING PAVEMENT - SURFACE MOUNT AS PER MANUFACTURER'S SPECIFICATIONS HOLE 300mm MIN, CORE DRILLED INTO EXISTING SURFACE 自己についた。 出行をつい 2100 100 2400 2100 2900 2900 拍 Bi-DIRECTIONAL CYCLEWAY AND PARKING ARRANGEMENT AT MEEKS ROAD BIKE HOLDING RAIL PLAN

Amendments		Client		Architect	Project Title			
Description A CLIENT ISSUE B ISSUE FOR RSA C FINAL DOCUMENTATION D FINAL ISSUE	Das Biologizza 44552024 10642024 22/652024	Sydney Metro Level 43, 680 George Street, Sydney NSW 2000 sydneymetro,info			EWPCL Interim Cycleway Design Demin 76 DETAILS	Drawing Created (date) Drawing Created (by) Verified Approved Scale	05/04/2024 MC MS SH A1	
		Consultant Civil Engineer ACCR Consultants Pty Ltd Level 1: 64 Union Street, 2000 info@gacco.com.su T + 612 4926 4811 M 0419 194 408	Consultant Traffic Engineer Tee Transport Presning Patheres (TTPP) Abures (TTPP) Abures (TTPP) Suite 402, 22 Atchison 81, ST LEONARDS NSW 2005 info@ttpp.net.aw (02) 8437 7800	T +612 9361 4144 F +612 9322 3488 architecture interper dasign urban dasiga bundasya nem architect Liszkharer Corrept. 9859 7566		Project No. A241703 This drawing is the copyright of neproduced or transmitted in any without the within permission on All lowla and dimensions are to commencement of any work, me components. Do not soale data	Group GSA Pty Ltd and may not form or by any means in part or (Group GSA Pty Ltd. be checked and verified on site aking of shop drawings or fabrica	or in whole e prior to the cation of

Attachment



Attachment 2





Item No: LTC0624(2) Item 2

Subject: BURROWS AVENUE AND RAILWAY ROAD, SYDENHAM - PROPOSED BUS LAYOVER AND PARKING CHANGES (MIDJUBURI -MARRICKVILLE WARD / HEFRON ELECTORATE / INNER WEST PAC)

Prepared By: George Tsaprounis - Coordinator Traffic Engineering Services (south)

Authorised By: Manod Wickramasinghe - Traffic and Transport Planning Manager

RECOMMENDATION

That the detail design drawing for the on-road changes associated with the proposed construction of a bus layover area in Burrows Avenue, west of Gleeson Avenue, Sydenham (as per attached drawing "Sydenham Station Bus Layover Burrows Avenue and Railway Road Signs and line marking plan" by Aurecon, dated 13/2/24, drawing no. 520212-AURC-038-RW-DRG-002001, sheet 10 of 41) be approved, subject to the following conditions:

- a) TfNSW provide assurances to Council with regards to buses servicing Sydenham Station will be a quieter bus fleet with a reduced footprint in relation to exhaust fumes; and
- b) TfNSW monitor the interaction between buses and vehicles along Railway Road (one way) and Burrows Road over the next 12 months and implement further traffic control measures should they be required.

STRATEGIC OBJECTIVE

This report supports the following strategic directions contained within Council's Community Strategic Plan:

2: Liveable, connected neighbourhoods and transport

EXECUTIVE SUMMARY

Transport for New South Wales (TfNSW) has approached Council with regards to a proposal for the construction of a bus layover area in Burrows Avenue, west of Gleeson Avenue, Sydenham. The designated bus layover area is required at Sydenham Station to cater for the growing number of bus services in this area. Prior to picking up passengers, buses currently park along Burrows Avenue which creates congestion and safety issues for pedestrians and drivers. The bus layover area will store up to 6 buses. The existing unrestricted parking spaces (approximately 11 spaces) on the south side of Burrows Avenue (adjacent to the vacant property) and six (6) 90-degree angle parking spaces on the north side of Burrows Avenue will be lost as a result of the proposal. In response to this loss of parking it is proposed to convert the parallel parking on the east side of Railway Road to 45-degree rear to kerb parking to lessen the impact from the loss of parking because of this proposal.

Community engagement was undertaken and it began on Friday 24 November and ended on Friday 8 December 2023. Community notifications, letterbox dropped and nearby properties door knocked on Railway Road, Burrows Avenue and Wright Street were part of the consultation process.

It is recommended that Council approve the signs and line marking plan (drawing no. 520212-AURC-038-RW-DRG-002001 sheet 10 of 41).

BACKGROUND

Sydenham Station is an important junction with the Bankstown Railway Line (T3), Illawarra and Eastern Suburbs line (T4) and Airport and South line (T8) and interchange with east-west bus routes. It continues to be a logical bus terminus for passengers interchanging with rail services from Sydney's Inner East and Inner West. This interchange function is expected to intensify in coming years with:

- The opening of the City & Southwest Metro between Chatswood and Bankstown. Increased Illawarra Line services
- Increased bus service levels and patronage to and from Sydenham Station. Population growth in surrounding precincts
- Sydenham being identified as the terminus for future new bus routes under the *Greater Sydney Bus Network Strategy.*

Given the importance of Sydenham Station as a multimodal transport interchange, buses servicing this major hub don't have enough room to terminate and layover between services. This creates congestion on Railway Road, Burrows Avenue and Gleeson Avenue (a freight corridor to the Airport and Port Botany). The limited bus layover options in the area results in buses idling in these streets, causing obstruction to pedestrians and cars, in active bus zones and surrounding streets. Transport for NSW representatives have advised of safety issues, delays to passengers and bus services which are currently being experienced as a result. To resolve this issue, Transport for NSW is proposing to construct a bus layover facility at the corner of Railway Road and Burrows Avenue in Sydenham (refer to figure 1 below)



Figure 1 – Locality Plan

DISCUSSION

Transport for New South Wales (TfNSW) is proposing a new bus layover facility at the corner of Railway Road and Burrows Avenue as part of the Bus Priority Infrastructure Program (BPIP) to improve the reliability and efficiency of bus services. Prior to picking up passengers, buses currently park along Burrows Avenue which creates congestion and safety issues for pedestrians and drivers.

TRR HFSG Extraordi

The proposed bus layover would give bus drivers a place to park safely between services and improve bus travel times and service frequencies, increasing reliability for passengers. Sydenham requires a bus layover area to cater to the growing number of bus services in this area. At present, prior to picking up passengers, buses park along Burrows Avenue and Railway Road creating congestion and impacting bus operations.

The proposed bus layover facility at the corner of Railway Road and Burrows Avenue in Sydenham will include the following changes (refer to figure 2):

- Six 16m-long angle bus parking spaces on the southern side of Burrows Avenue with manoeuvring space at the northern end of Railway Parade for egress, replacing a total of 11 parallel parking spaces.
- A dedicated drivers amenity block with a lunchroom and toilets.
- The 8 parallel parking spaces along the eastern side of Railway Road converted into 13 45-degree angle car parking spaces.
- A reduction in 90 degree angle car parking spaces along the northern side of Burrows Avenue from 12 to 6.
- Create a path for pedestrians, passengers and the community to safely walk to and from Railway Road to Gleeson Avenue.
- Build a noise wall to separate the nearby homes from the new bus layover facility and minimise noise impacts from the bus layover facility.
- Install driveways for buses to enter from Railway Road and leave through Burrows Avenue.

Extraordinary Local Traffic Committee Meeting 3 June 2024




Figure 2 – Bus layover proposal

|--|--|

The above changes result in a net loss of 17 unrestricted parking spaces across the two streets. The impacts of the proposed changes to the current parking arrangements along Burrows Avenue and Railway Road are provided in table 1 below.

Road Name	Parking Restrictions	Parking supply	Impact	Justification
Burrows Avenue – East *	Unrestricted	11	- 11	Required for the buses to exit from the new layover into Burrows Avenue
Burrows Avenue – West	Unrestricted	12	- 6	Required for buses to safe turning movements
Railway Rd -East	2 P	10	+5	Changing to angle parking
Railway Rd -West	1P, 2P	23	zero	No change

Table 1 – Proposed changes to parking

Given the loss of parking Council requested that parking data be collected by TfNSW to determine the impact of the proposed loss. The objective of the parking investigation was to provide TfNSW and Council with data, its analysis including assessment and recommendations on parking restriction changes and identify the parking impacts of the proposed layover area at the corner of Railway Road and Burrows Avenue ('Proposal Footprint') and on alternative parking areas within a 400m radius of the proposal area ('Side Streets). Refer to attached Parking Data Report for further details.

A site inspection was undertaken on Tuesday, 5 September 2023 between 12:30pm and 1:30pm to gain an understanding of the current parking conditions and constraints. Some of the key conclusions are listed below.

- Surplus parking in addition to the parking supply was observed in Buckley Street, Railway Parade, Railway Road (one-way), Hogan Avenue and George Street.
- The occupancy results show that there was some surplus parking in Burrows Avenue, Buckley Street and Hogan Avenue.
- The duration of stay results showed that on the peak weekdays and weekend days:
 - Most vehicles stayed for one hour and only four to six vehicles parked during the whole 13-hour surveys.
 - The average vehicle stays were six hours in Burrows Avenue and 3 to 3.5 hours in Railway Road (one-way).
- A total of 131 properties in Railway Road, George Street, Swain Street, Gleeson Avenue, Park Road and Yelverton Street were identified as not having onsite parking capacity. Of the 21 properties within the proposal footprint (all in Railway Road and none in Burrows Avenue), only seven had onsite parking.
- Under TfNSW's proposal, there is mostly insufficient parking across Burrows Avenue and Railway Road between Monday and Friday. The occupancy across all streets ranges between 55% and 80% and therefore there is still sufficient parking in surrounding streets.

In order to address the shortfall in parking, TfNSW have proposed that the current parking spaces along the eastern side of Railway Road be converted from 2P parallel parking spaces to 2P 45-degree, (rear to kerb) parking spaces. It has been calculated that this will result in a net gain of 5 timed parking spaces. It should be noted that the majority of the spaces lost as a result of the proposed works will be unrestricted spaces and adjacent to railway land. From the data analysis, it does seem that spare capacity does exist within a 400m radius to cope with the transfer of these spaces. It should also be noted that the majority of residential streets within close proximity to Sydenham Station have been treated with 2P resident parking restrictions.

COMMUNITY ENGAGEMENT

再返 金玉辺

Community engagement began on Friday 24 November and ended on Friday 8 December 2023, with community notifications letterbox dropped and nearby properties doorknocked on Railway Road, Burrows Avenue and Wright Street. Feedback was invited in person, on the phone, via email and through the Sydenham bus layover project web page, the Transport Your Say website, and the NSW Government Have Your Say portal. (Refer to the attached Community Engagement Report). A summary of the channels of engagement and description is provided in table 2 below.

At the end of the engagement period, feedback was received from 18 individuals. The local community supported the proposed bus layover in principle but had concerns around parking and the proposed location.

Transport used an 'inform' and 'consult' engagement approach for this project:

- 'Inform' the community, businesses and other stakeholders on the proposal.
- 'Consult' on changes to parking on Railway Road and Burrows Avenue.

Table 2 – Summary of channels of engagement

Channel	Description
Have your say community notification	 170 print notifications were letterbox dropped to residents and businesses across the proposal area Email notifications to emergency services and local schools Notifications and engagement with disability peak bodies through the Accessible Transport Advisory Committee
Transport project web page	www.transport.nsw.gov.au/projects/current- projects/sydenham-bus-layover 122 unique visitors accessed the project page
Your say Transport website	yoursay.transport.nsw.gov.au/sydenham-bus-layover 132 unique visitors accessed the Your say page
NSW Government Have Your Say portal	www.nsw.gov.au/have-your-say/sydenham-bus-layover
Inner West Community Forum	The Sydenham Bus Layover proposal was featured in the Inne West December livestream on Wednesday 6 December, reminding community members to have their say
Doorknocks	 On Thursday 23 and Friday 24 November, 24 properties were doorknocked along Railway Road and Wright Street. Direct face to face engagement was carried out with 15 residents at their residential properties. Two businesses were informed and engaged along Railway Road.
Key stakeholder briefings	 Inner West Council briefed 7 June and 24 November 2023 Rail, Tram and Bus Union, and Transport Workers' Union of NSW briefed 19 October 2023

The main issues raised in relation to traffic and parking from the engagement that was undertaken by TfNSW are summarised below as follows.

n

IER WEST

	Issue Raised	Response from TfNSW
Traffic	The layover will create more traffic on Railway Road and Burrows Avenue, creating congestion and noise	Transport expects the project to benefit the community and wider bus network. The proposed bus layover facility is expected to improve local traffic flows, road safety, and bus timetable reliability by reducing congestion, delays, and reducing instances of buses 'double parking' on Railway Road and Burrows Avenue. To manage noise to adjacent properties, the proposal includes the construction of a noise wall. The noise wall will run along the eastern boundary of the bus layover and will provide significant noise shielding.
	Will the configuration of lanes at the Intersection of Gleeson Avenue and Burrows Avenue change as part of this proposal?	The configuration of lanes at the Gleeson Avenue and Burrows Avenue intersection will not change as part of this project.
Parking	Railway Road is used for parking buses for rail replacement services, would a permanent layover replace this practice?	The proposed bus layover is a permanent facility and will be used by regular bus services as well as by rail replacement services. The layover is expected to improve local traffic flows, road safety, and on-time running by reducing congestion, delays, and instances of buses 'double parking' on Railway Road and Burrows Avenue. We do not expect to exceed six buses at the layover at any given time.
	There is not enough parking in the street and angled parking does not provide enough spaces to offset the loss of spaces, negatively impacting residents and businesses.	Transport has undertaken a parking assessment and has worked to optimise the parking spaces in Railway Road and Burrows Avenue. The introduction of angled parking provides an additional five spaces to the existing eight spaces in the section along Railway Road between Nos.105 and 117 Railway Road.
		Transport has also carried out a review of the Sydenham residential parking permit scheme and available parking spaces post- project delivery. There are sufficient available parking spaces within the project scope area (including Wright Street) to accommodate the permit allocation available for properties along Railway Road.
	Angled parking looks the wrong way Angled parking would narrow the road and increase the risk of crashes	The proposed angled parking is in accordance with Australian Standard 2890 Parking Facilities. The introduction of angled parking has historically been shown to reduce vehicle speeds which creates a safer road environment. Angled parking will also not adversely affect traffic flows along Railway Road.
	Will parking on the southern side of Railway Road be modified or removed?	Parking spaces on the southern side of Railway Road will not be modified or removed as part of this project scope. The parking changes are on the northern side of Railway Road and on Burrows Avenue.
	Why is angled parking on the right side of Railway	The angled parking is proposed for the northern side of Railway Road to accommodate bus turning

Traffic Committee Meeting

3 June 2024

Extraordinary Local

Road and not the left?	maneuvers into the layover.
 What is the net change	The parking changes to accommodate the bus
in parking spaces?	layover will result in a net reduction of 12 parking
in parking spaces:	spaces.
	spaces.
	For Railway Road on the southern side, there is no change to the existing 23 parking spaces. On the northern side there are currently eight parking spaces which will increase to 13 parking spaces with the introduction of angled parking.
	On the western side of Burrows Avenue, 12 parking spaces will be reduced to six. The 11 informal parking opportunities in the right turn pocket on the eastern side of Burrows Avenue will be removed as that area forms the layover exit for the buses.
	Transport has undertaken a parking assessment to optimise parking spaces. Transport has also carried out an assessment of the Sydenham residential parking permit scheme and available parking spaces post project delivery. The results of the assessments indicate that there are sufficient available parking spaces within the project scope area (including Wright Street) to accommodate the permit allocation available for properties along Railway Road.

CONCLUSION

The new bus layover facility project will benefit Sydenham Station as a multimodal transport interchange and support public transport infrastructure within the Inner West area. However, this will come at a cost to the adjoining residents with possible noise and exhaust impacts from the additional buses laying over and loss of overall parking. The creation of 45 degree angle parking will help ease the burden for resident as the additional spaces will be posted as 2P RPS area. It would also seem like the loss in unrestricted parking spaces can be accommodated in the adjacent street network. Issues of additional buses along Railway Road and their impacts are not properly addressed. Council should seek assurances from TfNSW as to servicing this node point with a quieter bus fleet with a reduced footprint in relation to exhaust fumes. Furthermore, given the increase in buses, the interaction of buses and vehicles should be monitored over a period of time and that TfNSW be responsible implementing further traffic control measures should they be required in future.

FINANCIAL IMPLICATIONS

There are no financial implications associated with the implementation of the proposed recommendations outlined in the report.

ATTACHMENTS

- 1. Sydenham Bus Layover Parking Data report
- 2. J Sydenham Bus Layover Community Engagement Report
- **3.** Sydenham Bus Layover Detailed Design



Sydenham Bus Layover Parking Data Report



Transport for NSW 12 March 2024





Gold Coast

Suite 26, 58 Riverwalk Avenue Robina QLD 4226 P: (07) 5562 5377

W: www.bitziosconsulting.com.au

Brisbane Level 2, 428 Upper Edward Street Spring Hill QLD 4000 P: (07) 3831 4442 Sydney Studio 203, 3 Gladstone Street

Newtown NSW 2042 P: (02) 9557 6202

E: admin@bitziosconsulting.com.au

Copyright in the information and data in this document is the property of Bitzios Consulting. This document and its information and data is for the use of the authorised recipient and this document may not be used, copied or reproduced in whole or in part for any purpose other than for which it was supplied by Bitzios Consulting. Bitzios Consulting makes no representation, undertakes no duty and accepts no responsibility to any third party who may use or rely upon this document or its information and data.

Document Issue History

Report File Name	Prepared	Reviewed	Issued	Date	Issued to
P6209.001R Sydenham Bus Layover Parking Data Report	S. Daizli / R. Jain	A. Grey	A. Grey	21/09/2023	Vishnu Anne <u>vishnu@matrix888.com</u>
P6209.002R Sydenham Bus Layover Parking Data Report	S. Daizli	A. Grey	A. Grey	2/02/2024	Vishnu Anne <u>vishnu@matrix888.com</u>
P6209.003R Sydenham Bus Layover Parking Data Report	S. Daizli	A. Grey	A. Grey	1/03/2024	Vishnu Anne <u>vishnu@matrix888.com</u>
P6209.004R Sydenham Bus Layover Parking Data Report	S. Daizli	A. Grey	S. Daizli	12/03/2024	Vishnu Anne <u>vishnu@matrix888.com</u>







CONTENTS

		Page
1.	INTRODUCTION	1
1.1	Overview	1
1.2	Background	1
1.3	Project Objective and Study Area	2
1.4	Scope of Works	4
2.	OVERVIEW OF PARKING AREAS	5
2.1	Parking Inventory	5
2.2	Road Network	6
2.3	Land Uses	8
3.	SITE INSPECTION	9
3.1	Overview	9
3.2	Bitzios vs. Matrix Parking Supply	9
3.3	Surplus Parking	10
3.4	Conflicting Signage	11
3.5	Temporary Parking Changes	13
4.	PARKING SURVEYS	14
4.1	Overview	14
4.2	Limitations	14
4.3	Occupancy Survey Results	14
4.3.1	D1. Burrows Avenue (within proposal footprint)	14
4.3.2	D2. Railway Road (one-way) (within proposal footprint)	15
4.3.3	O1. Buckley Street	15
4.3.4	O2-1. Railway Parade	16
4.3.5	O2-2. Railway Parade (one-way)	16
4.3.6	O3. Hogan Avenue	17
4.3.7	O4. George Street	17
4.3.8	O5. Swain Street	18
4.3.9	O6. Gleeson Avenue	18
4.3.10) O7. Park Road	19
4.3.11	l O8. Railway Road	19
4.3.12	2 O9. Rowe Lane	20
	3 O10. Reilly Lane	20
	4 O11. Yelverton Street	21
4.4	Duration of Stay Survey Results	21
4.4.1	Burrows Avenue (within proposal footprint)	21
	Railway Road (one-way) (within proposal footprint)	21
5.	PROPERTIES WITHOUT ONSITE PARKING	24
6.	ALTERNATIVE PARKING ASSESSMENT	26
6.1	Burrows Avenue / Railway Road Only	26
6.2	All Streets	27
6.3	Parking Directional Signage	28
7.	CONCLUSIONS	29





Tables

- Table 1.1: Study Area
- Table 2.1:
 Existing Parking Inventory
- Table 2.2:
 Existing Road Characteristics
- Table 3.1: Bitzios vs. Matrix Parking Supply
- Table 3.2: Surplus Parking Areas
- Table 3.3: Conflicting Parking Signage
- Table 4.1: Peak Duration of Stay D1. Burrows Avenue
- Table 4.2: Peak Duration of Stay D2. Railway Road (one-way)
- Table 5.1: Properties Without Onsite Parking

Figures

- Figure 1.1: Proposed Bus Layover
- Figure 1.2: Study Area
- Figure 2.1: Existing Parking Restrictions and Supply
- Figure 2.2: Road Classifications
- Figure 2.3: Land Zoning Map
- Figure 3.1: Surplus Parking Locations
- Figure 3.2: Conflicting Parking Signage Locations
- Figure 3.3: Temporary parking changes for rail replacement bus use
- Figure 4.1: Parking Occupancy D1. Burrows Avenue
- Figure 4.2: Parking Occupancy D2. Railway Road (one-way)
- Figure 4.3: Parking Occupancy O1. Buckley Street
- Figure 4.4: Parking Occupancy O2-1. Railway Parade
- Figure 4.5: Parking Occupancy O2-2. Railway Parade (one-way)
- Figure 4.6: Parking Occupancy O3. Hogan Avenue
- Figure 4.7: Parking Occupancy O4. George Street
- Figure 4.8: Parking Occupancy O5. Swain Street
- Figure 4.9: Parking Occupancy O6. Gleeson Avenue
- Figure 4.10: Parking Occupancy O7. Park Road
- Figure 4.11: Parking Occupancy O8. Railway Road
- Figure 4.12: Parking Occupancy O9. Rowe Lane
- Figure 4.13: Parking Occupancy O10. Reilly Lane
- Figure 4.14: Parking Occupancy O11. Yelverton Street
- Figure 5.1: Properties Without Onsite Parking
- Figure 6.1: Cumulative Parking Occupancy in Burrows Avenue / Railway Road With Proposal
- Figure 6.2: Cumulative Parking Occupancy Percentages in Burrows Avenue / Railway Road With Proposal
- Figure 6.3: Cumulative Parking Occupancy in All Streets With Proposal
- Figure 6.4: Cumulative Parking Occupancy Percentages in All Streets With Proposal
- Figure 6.5: Proposed VMS Locations

Appendices

Appendix A: Parking Inventory



Sydenham Bus Layover Parking Data Report Project: P6209 Version: 004



1. INTRODUCTION

1.1 Overview

Sydenham Station on the north-south Illawarra Railway Line is an important junction with the Bankstown Railway Line and interchange with east-west bus routes. It continues to be a logical bus terminus for passengers interchanging with rail services from Sydney's Inner East and Inner West. This interchange function is expected to intensify in coming years with:

- The opening of the City & South West Metro between Chatswood and Bankstown
- Increased Illawarra Line services
- Increased bus service levels and patronage to and from Sydenham Station
- Population growth in surrounding precincts
- Sydenham being identified as the terminus for future new bus routes under the *Greater Sydney Bus Network Strategy*.

1.2 Background

A designated bus layover area is required at Sydenham Station to cater to the growing number of bus services in this area. Prior to picking up passengers, buses currently park along Burrows Avenue which creates congestion and safety issues for pedestrians and drivers.

Transport for NSW (TfNSW) is proposing a bus layover area at the corner of Railway Road and Burrows Avenue. This will provide drivers a safe place to park between services, improve bus travel times and service frequencies, and increase reliability for passengers.

The proposal includes:

- Six 16m-long angle bus parking spaces on the southern side of Burrows Avenue with manoeuvring space at the northern end of Railway Parade for egress, replacing a total of 11 parallel parking spaces
- A dedicated drivers amenity block with a lunchroom and toilets
- The 14 parallel parking spaces along the northern side of Railway Parade converted into 13 45° angle car parking spaces
- A reduction in 90° angle car parking spaces along the northern side of Burrows Avenue from 11 to six.

The above changes result in a net loss of 17 parking spaces across the two streets. TfNSW's proposal is shown in Figure 1.1. It is assumed that current parking and time restrictions will remain.







Source: Transport for NSW Sydenham Bus Layover project webpage

Figure 1.1: Proposed Bus Layover

FR

1.3 Project Objective and Study Area

The objective of the parking investigation is to provide TfNSW with data, its analysis including assessment and recommendations on parking restriction changes, and identify the parking impacts of the proposed additional layover area at the corner of Railway Road and Burrows Avenue ('Proposal Footprint') on alternative parking areas within a 400m radius of the proposal area ('Side Streets').

The study area is summarised in Table 1.1 and shown in Figure 1.2.





Table 1.1: Study Area

ST

F

ID	Road Name	Section	Side/s Included			
Proposal Footprint						
D1	Burrows Avenue	Railway Road to Gleeson Avenue	Both			
D2	Railway Road (one-way)	Gleeson Avenue to Burrows Avenue	Both			
Side S	treets					
01	Buckley Street	Marrickville Road to No. 21-25 and 26-28	Both			
O2-1	Railway Parade	All	Both			
02-2	Railway Parade (one-way)	All	South			
O3	Hogan Avenue	All	Both			
04	George Street	Burrows Avenue to Henry Street	Both			
O5	Swain Street	All	Both			
O6	Gleeson Avenue	All	East			
07	Park Road	Unwins Bridge Road to Henry Street	Both			
08	Railway Road	Unwins Bridge Road to Henry Street	Both			
O9	Rowe Lane	Railway Road to Reilly Lane	South			
O10	Reilly Lane	Unwins Bridge Road to Henry Street	West			
011	Yelverton Street	Unwins Bridge Road to Henry Street	Both			



Adapted from Google Maps

Figure 1.2: Study Area



Sydenham Bus Layover Parking Data Report

Project: P6209 Version: 004

3

1.4 Scope of Works

TfNSW engaged Matrix Traffic and Transport Data (Matrix) to undertake the parking investigation, surveys and reporting for this project. Matrix has since engaged Bitzios Consulting (Bitzios) to prepare the parking data report (this report) in accordance with TfNSW's *Requirements for a Parking Study for an REF (REF Requirements, 2016)*, which included the following tasks:

- Summarise the parking surveys undertaken in terms of days, time and type
- Summarise the occupancy and duration of stay for each section on weekdays and weekends
- Prepare maps displaying the parking inventory, restrictions and type (retail, commuter, staff or residential)
- Review the study area, including extents, corridor length, existing lane restrictions, lane configuration, speed limits, business centre locations, and key locations of legal and illegal parking
- Undertake a parking assessment on the parking impacts from the proposed bus junction infrastructure in terms of parking supply and demand, including parking impacts along Burrows Avenue and Railway Road (between Gleeson Avenue and Burrows Avenue) and the suitability of nearby side streets by measuring the former's parking demand against alternative parking demand by:
 - Mapping how the areas have been divided and nearby side streets included in the analysis
 - Dividing the results into sections, days (weekday and weekend) and by direction
 - Provide comments on any events or unusual events
 - Describing the adjacent land use where the parking is permitted
 - Plotting graphs of road demand against nearby parking vacancies for each area on each day
 - Summarising the parking in terms of deficit or surplus for each area and the time of any parking deficits at the area occurred
 - Identifying the length of parking to be removed and the number of parking spaces impacted to be in accordance with AS2890.5:On-street parking
 - The need for parking directional signage for directing residents and other road users to side street parking and the potential locations for these signs.
- Prepare one map for locations and information of any parking, legal or illegal, not displayed in Figure 1.2
- Identify any business or residents that do not have onsite parking capacity
- Identify any business loading areas occurring on the section of road.



49



2. OVERVIEW OF PARKING AREAS

2.1 Parking Inventory

The existing parking inventory in each road section as at Tuesday, 5 September 2023 is summarised in Table 2.1. There are no lane restrictions (i.e. clearways, transit lanes or bus lanes) or loading, taxi or mail zones in these areas.

Table 2.1: Existing Parking Inventory

ID	Road Name	Name Parking Type/s Parking Restrictions		Parking Supply		
Proposal Footprint						
D1	Burrows Avenue	Commuter / residential	Bus Zone, No Stopping, Unrestricted	22		
D2	Railway Road (one-way)	Residential	1P, 2P, No Parking, No Stopping, Unrestricted	33		
Side	Streets					
01	Buckley Street	Residential	No Stopping, Unrestricted	12		
O2-1	Railway Parade	Commuter / residential	2P, 4P, Bicycle Parking, No Parking, Car Share, No Stopping, Unrestricted	95		
02-2	Railway Parade (one-way)	Commuter	Bus Zone, No Stopping, Unrestricted	3		
O3	Hogan Avenue	Residential	2P, No Parking, No Stopping, Unrestricted	14		
04	George Street	Residential	2P, Disabled Only, No Stopping, Unrestricted	59		
05	Swain Street	Residential	2P, Disabled Only, No Stopping	28		
06	Gleeson Avenue	Retail	Bus Zone, No Parking, No Stopping, 1P	7		
07	Park Road	Retail / residential	2P, No Stopping, Unrestricted	47		
08	Railway Road	Retail / residential	Bus Zone, No Parking, No Stopping, 1P	29		
09	Rowe Lane	Residential	4P, No Parking, No Stopping	25		
010	Reilly Lane	Residential	No Parking, No Stopping, Unrestricted	3		
011	Yelverton Street	Residential	2P, No Stopping	52		
			Total	429		

The locations of each parking restriction and their supply are shown in Figure 2.1. The parking and time restrictions of each segment are provided in **Appendix A**.








Figure 2.1: Existing Parking Restrictions and Supply

2.2 Road Network

Key characteristics of each road section and adjoining land uses are summarised in Table 2.2.

Road Name	Road Classification	No. of Travel Lanes	Speed Limit	Corridor Length	Adjoining Land Uses*		
Proposal Footprint							
Burrows Avenue	Local Road	1 (one-way)	50km/h	85m	 R2 Low Density Residential 		
Railway Road (one-way)	Local Road	1 (one-way)	50km/h	114m	E1 Local CentreR2 Low Density Residential		
Side Streets							
Buckley Street	State Road	2 (one-way)	60km/h	153m	 E4 General Industrial 		
Railway Parade	Local Road	2 (two-way)	50km/h	278m	 E4 General Industrial 		
Railway Parade (one-way)	State Road	2 (one-way)	60km/h	275m	 Sydenham Station 		
Hogan Avenue	Local Road	2 (two-way)	50km/h	106m	E4 General IndustrialR2 Low Density Residential		
George Street	Local Road	2 (two-way)	50km/h	301m	R2 Low Density ResidentialSydenham Green Park		
Swain Street	Local Road	1 (one-way)	50km/h	108m	E1 Local CentreR2 Low Density Residential		

Table 2.2: Existing Road Characteristics



Sydenham Bus Layover Parking Data Report

Project: P6209 Version: 004



Road Name	Road Classification	No. of Travel Lanes	Speed Limit	Corridor Length	Adjoining Land Uses*
Gleeson Avenue	State Road	4 (two-way)	60km/h	119m	 E1 Local Centre / Sydenham Town Centre
					 Memory Reserve
Park Road	Local Road	2 (two-way)	50km/h	172m	 E1 Local Centre / Sydenham Town Centre R2 Low Density Residential
Railway Road	State Road	4 (two-way)	60km/h	164m	 E1 Local Centre / Sydenham Town Centre R2 Low Density Residential Sydenham Green Park
Rowe Lane	Local Road	1 (two-way)	50km/h	116m	E1 Local CentreR2 Low Density ResidentialSydenham Green Park
Reilly Lane	Local Road	1 (two-way)	50km/h	119m	R2 Low Density ResidentialSydenham Green Park
Yelverton Street	Local Road	2 (two-way)	50km/h	175m	 R2 Low Density Residential

*Source: Inner West Local Environmental Plan 2022

The classification of each road section is shown in Figure 2.2.





Figure 2.2: Road Classifications





2.3 Land Uses

The land use definitions under the Inner West Local Environmental Plan 2022 are shown in Figure 2.3.



Source: NSW Planning Portal Spatial Viewer

Figure 2.3: Land Zoning Map



Sydenham Bus Layover Parking Data Report Project: P6209 Version: 004



3. SITE INSPECTION

3.1 Overview

A site inspection was undertaken on Tuesday, 5 September 2023 between 12:30pm and 1:30pm to gain an understanding of the current parking conditions and constraints, as well as verify the inventory survey undertaken by Matrix.

Buses taking up vehicle parking spaces along Burrows Avenue and Railway Road (one-way) was not observed during the parking surveys or site inspection.

3.2 Bitzios vs. Matrix Parking Supply

The parking supply in each area verified Bitzios and surveyed by Matrix are compared in Table 3.1. The greatest difference was only five vehicles. A permanent No Stopping zone was recently implemented on the western corner of Burrows Avenue. The remaining differences are based on AS2890.5 (where practical), as well as first-principles (i.e. locations of driveways and road infrastructure, road geometry, types of vehicles and land uses). The parking supply in the occupancy survey results throughout this report is based on Bitzios' survey.

Road Name	Bitzios Parking Supply	Matrix Parking Supply	Difference
Burrows Avenue	22	26	-4
Railway Road (one-way)	33	36	-3
Buckley Street	12	9	+3
Railway Parade	95	95	0
Railway Parade (one-way)	3	3	0
Hogan Avenue	14	13	0
George Street	59	59	0
Swain Street	28	28	0
Gleeson Avenue	7	7	0
Park Road	47	49	-2
Railway Road	29	29	0
Rowe Lane	25	25	0
Reilly Lane	3	3	0
Yelverton Street	52	47	+5
Total	429	429	0

Table 3.1: Bitzios vs. Matrix Parking Supply





3.3 Surplus Parking

Surplus parking in addition to the above supply not identified by Bitzios or Matrix, including both legal/practical and illegal/unsafe parking, was observed in some areas as summarised in Table 3.2. Their locations are shown in Figure 3.1.


Table 3.2: Surplus Parking Areas

ID	Location	Description / Comments	Illustration*
1		4 illegally parked vehicles observed across driveways (maybe associated with nearby businesses).	
2		2 parked vehicles observed at the north- eastern end (appears safe, practical and common according to Nearmap).	
3	(one-way)	6 additional parked vehicles observed at the south-western end (the first 5 from left deemed safe enough; common according to Nearmap).	
4		1 additional parked vehicle observed.	

*Yellow circle = legal/practical parking and red circle = illegal/unsafe parking.







*Matrix: No Board = no space to park. / Basemap: Community Map

Figure 3.1: Surplus Parking Locations

3.4 Conflicting Signage

ER WEST

Table 3.3 summarises conflicting parking signage observed during the site inspection. Their locations are shown in Figure 3.2.

Table 3.3:	Conflicting	Parking	Signage
------------	-------------	---------	---------

ID	Location	Issue	Illustration
1	-	Missing double arrow No Stopping sign. There is currently an end No Stopping sign.	




Sydenham Bus Layover Parking Data Report Project: P6209 Version: 004



ID	Location	Issue	Illustration
2	Railway Parade	Missing end No Parking and start 2P signs.	
3	Gleeson Avenue	Missing start Bus Zone sign. There is currently a double arrow No Stopping sign.	
4	Railway Road	Missing start No Stopping sign.	







*Matrix: No Board = no space to park. / Basemap: Community Map

Figure 3.2: Conflicting Parking Signage Locations

3.5 Temporary Parking Changes

Posters hung along Burrows Avenue, Railway Road (one-way), Gleeson Avenue and Railway Parade show that some parking spaces in these areas are used by rail replacement buses, particularly during major weekday rail shutdowns. A poster outlining upcoming changes during the Term 3 school holidays is shown in Figure 3.3.



Figure 3.3: Temporary parking changes for rail replacement bus use



ER WEST

Sydenham Bus Layover Parking Data Report Project: P6209 Version: 004 Attachment 1

Item 2

58

4. PARKING SURVEYS

4.1 Overview

ΗR

Matrix undertook parking inventory and occupancy surveys along each road section between Wednesday, 26 July and Tuesday, 1 August 2023 between 6:00am and 7:00pm daily. A duration of stay survey was also undertaken along Burrows Avenue and Railway Road (one-way) over the same period. The occupancy and duration of stay were recorded every hour.

4.2 Limitations

It was observed in the survey data that:

- Occupancy (if any) was not recorded in the following zones where it is illegal to park:
 - No Stopping (including part-time)
 - No Parking (including part-time)
- Bus Zone.
- Areas used by trucks for business loading were not identified, particularly given the lack of loading or mail zones.


It is therefore difficult to identify and/or verify any common areas or times of surplus parking, illegal parking or business loading.

4.3 Occupancy Survey Results

4.3.1 D1. Burrows Avenue (within proposal footprint)

The parking occupancy results for Burrows Avenue are presented in Figure 4.1. Key observations include that:

- Surplus parking (up to three vehicles) occurred on Thursday, Saturday, Monday and Tuesday between 10:00am and 1:00pm, most likely used by commuters. It is noted that a supply of 26 spaces was allowed at the time of the survey, now 22 due to the permanent No Stopping zone (see Section 3.2)
- Friday and Sunday only had up to 17 parked vehicles per hour.





Sydenham Bus Layover Parking Data Report Project: P6209 Version: 004



4.3.2 D2. Railway Road (one-way) (within proposal footprint)

The parking occupancy results for Railway Road (one-way) are presented in Figure 4.2. Parking was highest on Wednesday, Thursday and Sunday after 1:00pm. Parking was lowest on Friday and Sunday before 1:00pm.





Figure 4.2: Parking Occupancy – D2. Railway Road (one-way)

4.3.3 O1. Buckley Street

The parking occupancy results for Buckley Street are presented in Figure 4.3. Surplus parking (up to six vehicles) occurred on Wednesday after 9:00am, as well as on Friday, Monday and Tuesday between 9:00am and 2:00pm. This is most likely associated with nearby businesses.



15

Item 2



4.3.4 O2-1. Railway Parade

The parking occupancy results for Railway Parade are presented in Figure 4.4. Weekday and weekend parking patterns were generally consistent. Weekday parking peaked at 92 vehicles on Wednesday at 1:00pm, compared with just 29 vehicles on Saturday at 11:00am. It is likely that most parking is used by commuters.





Figure 4.4: Parking Occupancy – O2-1. Railway Parade

4.3.5 O2-2. Railway Parade (one-way)

The parking occupancy results for Railway Parade (one-way) are presented in Figure 4.5. Parking was mostly at capacity, however, it is likely that more vehicles were parked at the south-western end.



Item 2

16

4.3.6 O3. Hogan Avenue

The parking occupancy results for Hogan Avenue are presented in Figure 4.6. Surplus parking (up to three vehicles) occurred during five hours on Thursday, and two hours each on Wednesday and Friday afternoon and Tuesday morning. This may be due to the nearby smash repairers.





Figure 4.6: Parking Occupancy – O3. Hogan Avenue

4.3.7 O4. George Street


The parking occupancy results for George Street are presented in Figure 4.7. Spaces were mostly at least 90% occupied, except on Thursday which had just 49%. It is not clear why.






4.3.8 O5. Swain Street

The parking occupancy results for Swain Street are presented in Figure 4.8. Parking generally increased throughout the day on all days and was higher on weekdays.



4.3.9 O6. Gleeson Avenue

The parking occupancy results for Gleeson Avenue are presented in Figure 4.9. Parking is only allowed on the eastern (southbound) side. Weekend parking was higher as it is unrestricted and six spaces were occupied most of the week.





18

Item 2




4.3.10 O7. Park Road





4.3.11 O8. Railway Road

The parking occupancy results for Railway Road are presented in Figure 4.11. Spaces on weekends were up to 45% occupied, compared with just 28% on weekdays. Eastern (southbound) spaces (12) between Rowe Lane and Henry Street were predominantly unoccupied.



Attachment 1

19



4.3.12 O9. Rowe Lane

The parking occupancy results for Rowe Lane are presented in Figure 4.12. Parking patterns were generally consistent each day: increasing till 12:00pm, then decreasing till 3:00pm and increasing again. Non-permit holders can only park for four hours between 8:30am-6:00pm Monday to Friday.





Figure 4.12: Parking Occupancy – O9. Rowe Lane

4.3.13 O10. Reilly Lane

The parking occupancy results for Reilly Lane are presented in Figure 4.13. Parking was mostly at capacity.



20

4.3.14 O11. Yelverton Street

The parking occupancy results for Yelverton Street are presented in Figure 4.14. Key observations include that:

- Parking patterns were generally consistent each day, decreasing till 12:00pm, then increasing
- Weekend parking was higher as it is unrestricted
- Weekday parking was lower possibly due to residents commuting.




Figure 4.14: Parking Occupancy – O11. Yelverton Street

4.4 Duration of Stay Survey Results

4.4.1 Burrows Avenue (within proposal footprint)

The duration of stay during the peak weekday (Thursday) and weekend day (Saturday) for Burrows Avenue are summarised in Table 4.1. Key observations include that:

- Most vehicles stayed for one hour on both days: Thursday 12 (26%) and Saturday nine (19%)
- Four vehicles were parked during the whole Thursday survey (9%) and six vehicles were parked during the Saturday (13%) survey
- The average vehicle stays were 6 hrs 6 mins on Thursday and 5 hrs 56 mins on Saturday.

4.4.2 Railway Road (one-way) (within proposal footprint)

The duration of stay during the peak weekday (Tuesday) and weekend day (Saturday) for Railway Road (one-way) are summarised in Table 4.2. Key observations include that:

- Most vehicles stayed for one hour on both days: Tuesday 44 (44%) and Saturday 28 (33%)
- Four vehicles were parked during the whole Tuesday survey (4%) and five vehicles were parked during the Saturday survey (6%)
- The average vehicle stays were 2 hrs 57 mins on Tuesday and 3 hrs 24 mins on Saturday.



Sydenham Bus Layover Parking Data Report Project: P6209 Version: 004



	Duration of Stay (hours)												
Hour	1	2	3	4	5	6	7	8	9	10	11	12	13
Thursday													
6:00	-	1	1	1	-	-	1	1	2	1	3	1	4
7:00	-	-	-	-	-	-	-	1	-	-	-	-	-
8:00	-	1	-	-	-	-	-	-	1	-	3	-	-
9:00	-	-	-	-	-	-	-	-	-	1	-	-	-
10:00	-	-	-	-	-	-	1	2	1	-	-	-	-
11:00	-	-	-	-	-	-	-	-	-	-	-	-	-
12:00	-	-	-	-	1	1	-	-	-	-	-	-	-
13:00	-	-	-	-	-	1	-	-	-	-	-	-	-
14:00	-	-	-	-	-	-	-	-	-	-	-	-	-
15:00	1	-	-	2	-	-	-	-	-	-	-	-	-
16:00	2	-	1	-	-	-	-	-	-	-	-	-	-
17:00	3	2	-	-	-	-	-	-	-	-	-	-	-
18:00	6	-	-	-	-	-	-	-	-	-	-	-	-
Total	12	4	2	3	1	2	2	4	4	2	6	1	4
			-		-	S	aturday	/	-	-	-	-	-
6:00	1	-	-	1	-	-	-	3	3	2	1	2	6
7:00	-	-	-	-	1	-	1	-	-	-	-	-	-
8:00	-	-	-	1	-	-	-	-	-	-	1	-	-
9:00	1	-	-	-	1	-	-	-	-	-	-	-	-
10:00	-	-	-	-	-	-	-	-	1	-	-	-	-
11:00	-	-	-	1	-	-	-	-	-	-	-	-	-
12:00	-	-	-	1	-	-	-	-	-	-	-	-	-
13:00	-	-	-	-	-	-	-	-	-	-	-	-	-
14:00	-	2	-	-	-	-	-	-	-	-	-	-	-
15:00	-	-	1	4	-	-	-	-	-	-	-	-	-
16:00	-	1	4	-	-	-	-	-	-	-	-	-	-
17:00	1	1	-	-	-	-	-	-	-	-	-	-	-
18:00	6	-	-	-	-	-	-	-	-	-	-	-	-
Total	9	4	5	8	2	-	1	3	4	2	2	2	6

Table 4.1: Peak Duration of Stay – D1. Burrows Avenue

ST



 $\mathbb{R}\mathbb{R}$

Sydenham Bus Layover Parking Data Report
Project: P6209 Version: 004



Have	Duration of Stay (hours)												
Hour	1	2	3	4	5	6	7	8	9	10	11	12	13
Tuesday													
6:00	-	5	4	1	-	1	2	-	-	-	-	-	4
7:00	1	2	-	-	2	-	-	1	-	-	-	-	-
8:00	2	-	1	-	-	-	-	-	2	-	-	-	-
9:00	2	1	3	-	-	-	1	-	-	2	-	-	-
10:00	1	-	-	-	-	-	-	-	-	-	-	-	-
11:00	3	1	-	1	-	-	-	1	-	-	-	-	-
12:00	4	6	1	-	-	-	1	-	-	-	-	-	-
13:00	4	-	-	-	-	-	-	-	-	-	-	-	-
14:00	2	1	-	-	2	-	-	-	-	-	-	-	-
15:00	4	-	-	1	-	-	-	-	-	-	-	-	-
16:00	7	3	3	-	-	-	-	-	-	-	-	-	-
17:00	9	3	-	-	-	-	-	-	-	-	-	-	-
18:00	5	-	-	-	-	-	-	-	-	-	-	-	-
Total	44	22	12	3	4	1	4	2	2	2	-	-	4
Saturday													
						S	aturday	1					
6:00	1	2	4	1	-	- S	<mark>aturday</mark> -	2	2	1	-	1	5
6:00 7:00	1 -	2 1	4	1	-		-		2 -	1	-	1	5
						-	-	2					
7:00	-	1	1	-	-	-	-	2 1	-	-	-	-	-
7:00 8:00	- 2	1	1	-	-		-	2 1 -	-	-	-	-	-
7:00 8:00 9:00	- 2 2	1 1 -	1 1 -	-		- - -	-	2 1 -	-	- - 1	-		
7:00 8:00 9:00 10:00	- 2 2 4	1 1 - 1	1 1 - 2	- - - 2		- - - -		2 1 - -	- - - 1	- - 1 -			
7:00 8:00 9:00 10:00 11:00	- 2 2 4 -	1 1 - 1 4	1 1 - 2 -	- - 2 2	- - - -	- - - - -		2 1 - - -	- - - 1 -	- - 1 -		- - - -	
7:00 8:00 9:00 10:00 11:00 12:00	- 2 2 4 - 1	1 - 1 4 1	1 - 2 - -	- - 2 2 -	- - - - -	- - - - - -		2 1 - - - - -	- - - 1 - -	- - 1 - -	- - - - -	- - - - -	- - - - -
7:00 8:00 9:00 10:00 11:00 12:00 13:00	- 2 2 4 - 1 7	1 - 1 4 1 -	1 - - - -	- - 2 2 -	- - - - - - -	- - - - - - -		2 1 - - - - - -	- - 1 - -	- - 1 - - -	- - - - - - -	- - - - - -	- - - - - -
7:00 8:00 9:00 10:00 11:00 12:00 13:00 14:00	- 2 2 4 - 1 7 1	1 - 1 4 1 - 6	1 - - - - - -	- - 2 2 - - 1	- - - - - - 1	- - - - - - - - - - -		2 1 - - - - - - -	- - - 1 - - - -	- - 1 - - -	- - - - - - - - - -	- - - - - - - - - -	- - - - - - - - - -
7:00 8:00 9:00 10:00 11:00 12:00 13:00 14:00 15:00	- 2 2 4 - 1 7 1 -	1 1 - 1 4 1 - 6 -	1 - - - - - 2	- - 2 2 - - 1 1	- - - - - - - 1 -	- - - - - - - - - - - -		2 1 - - - - - - - - -	- - - - - - - - - -	- - - - - - - -	- - - - - - - - -	- - - - - - - - - - - -	- - - - - - - - - -
7:00 8:00 9:00 10:00 11:00 12:00 13:00 14:00 15:00 16:00	- 2 2 4 - 1 7 1 - 1	1 - 1 4 1 - 6 - 4	1 1 - - - - - 2 2	- - 2 2 - - 1 1 -	- - - - - - - 1 - - - -	- - - - - - - - - - - - -		2 1 - - - - - - - -	- - - - - - - - -	- - - - - - - - - -	- - - - - - - - - - -	- - - - - - - - - - - -	- - - - - - - - - - - -

Table 4.2: Peak Duration of Stay – D2. Railway Road (one-way)

ST

囹



 $\mathbb{F}\mathbb{D}$

Sydenham Bus Layover Parking Data Report

Project: P6209 Version: 004



5. PROPERTIES WITHOUT ONSITE PARKING

A total of 131 properties (all in Sydenham) have been identified as not having onsite parking capacity. These are listed in Table 5.1 and shown in Figure 5.1.

Table 5.1: Properties Without Onsite Parking

л П

ΗÐ


Within Proposal Footprin		1	
84 Railway Road	93 Railway Road	58A Park Road	 54 Yelverton Street
86 Railway Road	 47 George Street 	59 Park Road	 55 Yelverton Street
88 Railway Road	 49 George Street 	60 Park Road	 56 Yelverton Street
92 Railway Road	 53 George Street 	61A Park Road	 57 Yelverton Street
94 Railway Road	 57 George Street 	61B Park Road	 58 Yelverton Street
 96 Railway Road 	 59 George Street 	62 Park Road	 59 Yelverton Street
100 Railway Road	 61 George Street 	64 Park Road	 61 Yelverton Street
105 Railway Road	 63 George Street 	66 Park Road	 63 Yelverton Street
106 Railway Road	 65 George Street 	67 Park Road	 64 Yelverton Street
107 Railway Road	 69 George Street 	68 Park Road	 65 Yelverton Street
109 Railway Road	 71 George Street 	69 Park Road	 66 Yelverton Street
111 Railway Road	 73 George Street 	70 Park Road	 67 Yelverton Street
 113 Railway Road 	 75 George Street 	71 Park Road	 68 Yelverton Street
115 Railway Road	 77 George Street 	72 Park Road	 69 Yelverton Street
	 86 George Street 	73 Park Road	 70 Yelverton Street
	 116A George Street 	75 Park Road	 71 Yelverton Street
	 116B George Street 	76 Park Road	 72 Yelverton Street
	 120 George Street 	77 Park Road	 78 Yelverton Street
	 122 George Street 	78 Park Road	 79 Yelverton Street
	 124 George Street 	79 Park Road	 80 Yelverton Street
	 126 George Street 	80 Park Road	 81 Yelverton Street
	 128 George Street 	81 Park Road	 82 Yelverton Street
	 130 George Street 	82 Park Road	 83 Yelverton Street
	 132 George Street 	83 Park Road	 84 Yelverton Street
	 4 Swain Street 	84 Park Road	 85 Yelverton Street
	 5 Swain Street 	85 Park Road	 86 Yelverton Street
	 6 Swain Street 	86 Park Road	 87 Yelverton Street
	 7 Swain Street 	87 Park Road	 88 Yelverton Street
	 8 Swain Street 	88 Park Road	 89 Yelverton Street
	 9 Swain Street 	90 Park Road	 90 Yelverton Street
	 10 Swain Street 	92 Park Road	 91 Yelverton Street
	 11 Swain Street 	93 Park Road	 92 Yelverton Street
	 5 Gleeson Avenue 	94 Park Road	 93 Yelverton Street
	 7 Gleeson Avenue 	95 Park Road	 94 Yelverton Street
	 9-9A Gleeson Avenue 	96 Park Road	 95 Yelverton Street
	 11-13 Gleeson Avenue 	97 Park Road	 96 Yelverton Street
	56 Park Road	98 Park Road	 97 Yelverton Street
	57 Park Road	99 Park Road	 98 Yelverton Street
	58 Park Road	100 Park Road	 99 Yelverton Street



Sydenham Bus Layover Parking Data Report

Project: P6209 Version: 004





*Matrix: No Board = no space to park. Properties source: NSW Land Parcel and Property Theme cadastre Basemap: Community Map

Figure 5.1: Properties Without Onsite Parking




Sydenham Bus Layover Parking Data Report Project: P6209 Version: 004



6. ALTERNATIVE PARKING ASSESSMENT

6.1 Burrows Avenue / Railway Road Only

The cumulative parking occupancy vs. parking supply across Burrows Avenue and Railway Road was analysed to determine whether there is sufficient parking under the proposal. The results are presented in Figure 6.1 and Figure 6.2. There is mostly insufficient parking in Burrows Avenue and Railway Road between Monday and Friday.





Sydenham Bus Layover Parking Data Report Project: P6209 Version: 004 26

6.2 All Streets

The cumulative parking occupancy vs. parking supply across all streets was analysed to determine whether there is sufficient parking under the proposal. The results are presented in Figure 6.3 and Figure 6.4. The highest occupancy is 80% and the lowest occupancy is 55%.




Figure 6.3: Cumulative Parking Occupancy in All Streets – With Proposal




Figure 6.4: Cumulative Parking Occupancy Percentages in All Streets – With Proposal





6.3 Parking Directional Signage

The *REF Requirements (2016)* require parking directional signage for side street parking, however, providing such signage is not commonplace for on-street parking. Also, given the extent of the study area, this is considered complex for drivers who can otherwise drive around to look for nearby parking as they would normally do. As such, it is suggested that variable message signs (VMS) be installed on major entry points to the study area as shown in Figure 6.5 to warn drivers of the parking changes and to seek alternative parking.



Adapted from Google Maps

Figure 6.5: Proposed VMS Locations

It is noted that there are limited opportunities for installing VMS within the study area due to narrow roadside space, particularly along Unwins Bridge Road (from St Peters) and Marrickville Road. Alternative signs may be required at these locations. The use of traffic signs should be used in conjunction with Live Traffic and other communication channels.



Sydenham Bus Layover Parking Data Report Project: P6209 Version: 004



7. CONCLUSIONS

The key findings from the Sydenham Station bus layover parking investigation to assess the parking impacts of the proposed bus layover area at the corner of Railway Road and Burrows Avenue are summarised as follows:

- TfNSW's proposal includes:
 - Six 16m-long angle bus parking spaces on the southern side of Burrows Avenue with manoeuvring space at the northern end of Railway Parade for egress, replacing a total of 11 parallel parking spaces
 - A dedicated drivers amenity block with a lunchroom and toilets
 - The 14 parallel parking spaces along the northern side of Railway Parade converted into 13 45° angle car parking spaces
 - A reduction in 90° angle car parking spaces along the northern side of Burrows Avenue from 11 to six.
- Bitzios' parking inventory identified minor differences in supply from Matrix in Burrows Avenue, Railway Road, Buckley Street, Park Road and Yelverton Street
- There are no lane restrictions or loading, taxi or mail zones in the study area
- Surplus parking in addition to the parking supply was observed in Buckley Street, Railway Parade, Railway Parade (one-way), Hogan Avenue and George Street
- Conflicting parking signage was observed in Buckley Street, Railway Parade, Gleeson Avenue and Railway Road
- Some parking spaces along Burrows Avenue, Railway Road (one-way), Gleeson Avenue and Railway Parade are already used by rail replacement buses during major weekday rail shutdowns
- The occupancy results show that there was some surplus parking in Burrows Avenue, Buckley Street and Hogan Avenue
- The duration of stay results show that on the peak weekdays and weekend days:
- Most vehicles stayed for one hour and only four to six vehicles parked during the whole 13-hour surveys
 The average vehicle stays were six hours in Burrows Avenue and 3 to 3.5 hours in Railway Road (one-way).
- A total of 131 properties in Railway Road, George Street, Swain Street, Gleeson Avenue, Park Road and Yelverton Street have been identified as not having onsite parking capacity. Of the 21 properties within the proposal footprint (all in Railway Road and none in Burrows Avenue), only seven have onsite parking
- Under TfNSW's proposal, there is mostly insufficient parking across Burrows Avenue and Railway Road between Monday and Friday. The occupancy across all streets ranges between 55% and 80% and therefore there is still sufficient parking in surrounding streets
- It is suggested that VMS be installed on major entry points to the study area along Railway Road, Unwins Bridge Road (from Tempe) and Sydenham Road instead of parking directional signage due to not being commonplace for on-street parking and complexity for drivers. Unwins Bridge Road (from St Peters) and Marrickville Road may require alternative signs due to narrow roadside space. The use of traffic signs should be used in conjunction with Live Traffic and other communication channels.



Sydenham Bus Layover Parking Data Report Project: P6209 Version: 004



Attachment 1






Appendix A: Parking Inventory




Item 2

Item 2




Item 2




77

Item 2



	Section		Road Name	Side	Suburb	Segment Length_m	Parking Restrictions	Time/Other Restrictions	Matrix Supply	Bitzios Supply	Notes
0	D1 D1 D1	1 2	Burrows Avenue Burrows Avenue	North	Sydenham Sydenham	5.155 44.04	No Stopping Unrestricted	90' Angle Parking Rear to kerb Vehicles under 6m only	- 15	0	Used by rail replacement buses Used by rail replacement buses
2	D1 D1	3	Burrows Avenue Burrows Avenue	North	Sydenham Sydenham	53.908 5.679	Bus Zone No Stopping		0	0	
4	D1	5		South	Sydenham	7.32	No Stopping	-	0	0	I forf hy rail rankrement histor
6	D2 D2		Railway Road (one-way)	North	Sydenham	90.064	2P No Parking	8am-10pm Permit holders excepted Area M4	14		Used by rail replacement buses
8	D2	3	Railway Road (one-way) Railway Road (one-way)	North	Sydenham Sydenham	3.143	No Stopping	-	Ő	Ő	
9	D2 D2	4	Railway Road (one-way) Railway Road (one-way)	South	Sydenham Sydenham	6.18 7.451 25.154	Unrestricted No Parking	90' Angle Parking Rear to kerb Vehicles under 6m only -	2	2	
11	D2 D2	6	Railway Road (one-way) Railway Road (one-way)	South South	Sydenham Sydenham	25.154 121.724	19 29	8:30am-6pm Mon-Fri, 8:30am-12:30pm Sat 8am-10pm Permit holders excepted Area M4	3	3	
13	01	1 2	Buckley Street Buckley Street	West	Marrickville Marrickville	39.046 140.532	No Stopping		0	0	Missing double arrow No Stopping sign. There is currently an end No Stopping sign S additional parked vehicles observed across driveways (maybe associated with nearby businesses)
19	01 01 01	3	Buckley Street Buckley Street Buckley Street	East East	Marrickville Marrickville Marrickville	105.429 26.615	Unrestricted Unrestricted No Stopping		4 5 0	6	
17	01	5	Buckley Street	East	Marrickville	38.238	No Stopping		0	0	
18	02-1	1 2	Railway Parade Railway Parade Railway Parade		Marrickville Marrickville	18.025	No Stopping No Parking	-	0	0	
20	02-1 02-1	3 4	Railway Parade Railway Parade	North North	Marrickville Marrickville	23.382 143.836	No Stopping 29	- 7am-Spm Mon-Fri	0		
22	02-1 02-1	5	Railway Parade Railway Parade	North			No Parking 29	7am-Spm Mon-Fri	0	0	Missing and sign Missing start sign
24	02-1	7	Railway Parade	North	Marrickville	14.355	No Parking	90' Angle Parking Vehicles under 6m only	Û	0	
28	02-1 02-1	9 10	Railway Parade Railway Parade Railway Parade	South		16.138 77.919	No Parking Authorised car share vehicles excepted 49	90' Angle Parking Vehicles under 6m only & 30am-6pm Mon-Fri	1 5 0		
22	02-1	11	Railway Parade	South South	Sydenham Sydenham	147.434	No Stopping Unrestricted	- 90' Angle Parking Vehicles under 6m only	37	0 37	2 additional parked vehicles observed at the north-eastern end
30	02-1 02-1	13	Railway Parade Railway Parade	South South	Sydenham Sydenham	2.872 45.376	No Stopping Unrestricted	- 90' Angle Parking Vehicles under 6m only	0	0	Used by rail replacement buses
	02-1	14 15	Railway Parade Railway Parade	South South	Sydenham	2.872 45.415	No Stopping Unrestricted	90' Angle Parking Vehicles under 6m only	0	0	Used by rail replacement buses
33	02-1	16	Railway Parade		Sydenham	2.872	No Stopping	90' Angle Parking Vehicles under 6m only & 30am 6pm Mon-Fri	0	0	
35	02-1	18	Railway Parade Railway Parade	South	Sydenham Sydenham	3.871	Bicycle Parking	av reige raiking venices under om driv clauer opti Mon-tri	11 2	2	Used by rail replacement buses
36	02-2	1	Railway Parade (one-way) Railway Parade (one-way)	North South	Sydenham	332.183 66.95	No Stopping No Stopping		0	0	
	02-2		Railway Parade (one-way) Railway Parade (one-way)	South	Sydenham Sydenham	110.644 35.27	Bus Zone No Stopping		0	0	
40	02-2	5	Railway Parade (one-way)	South	Sydenham Sydenham	7.092 49.865	No Stopping Bus Zone	-	0	0	
43	02-2	7	Railway Parade (one-way) Railway Parade (one-way)	South	Sydenham	72.73	Unrestricted	-	3	3	6 additional parked vehicles observed at the south-western end (5 deemed safe enough)
43	03	1 2	Hogan Avenue Hogan Avenue	East East	Sydenham Sydenham	17.332 13.332	No Stopping No Parking	-	0	0	
45	03	3 4	Hogan Avenue Hogan Avenue	East East	Sydenham	72.284 14.469	Unrestricted No Stopping		4	4	
47	03	5		West	Sydenham Sydenham	22.569	No Stopping 29	8am-10pm Permit holders excepted Area M4	0 9	0	
45		7	Hogan Avenue	West	Sydenham Sydenham	30.551	No Stopping No Stopping		0	0	
51		2	George Street	East	Sydenham	98.677	29	8am-10pm Permit holders excepted Area M4	2	2	1 additional parked vehicle observed
53	04	4	George Street George Street	East East	Sydenham Sydenham	15.806 17.825	No Stopping No Stopping		0	0	
54	04 04 04	5	George Street George Street	East	Sydenham	118.998	29	8:30am-6pm Mon-Fri Permit holders excepted Area M4	0 14 1	0 14	
56	04	7	George Street George Street		Sydenham Sydenham Sydenham	5.493 54.269 8.085	Disabled Only 29 No Stopping	8:30am-6pm Mon-Fri Permit holders excepted Area M4	6	6	
58	04	9	George Street	West	Sydenham	12.763	No Stopping		0	0	
60	04	10 11	George Street George Street		Sydenham Sydenham	178.533 15.012	Unrestricted No Stopping	-	25 0	0	
61	04	12 13	George Street George Street	West	Sydenham	18.591 94.631	No Stopping 29	8am-10pm Permit holders excepted Area M4	0	0	
63		14	George Street Swain Street		Sydenham Sydenham	13.764 7.879	No Stopping No Stopping	-	0	0	
	05	2	Swain Street Swain Street	East	Sydenham Sydenham	104.917 4.266	29 Disabled Only	8am-10pm Permit holders excepted Area M4	12	12	
67			Swain Street	East	Sydenham Sydenham	4.752	No Stopping No Stopping		0	0	
65	05	6	Swain Street	West	Sydenham	24.237	29	8am-10pm Permit holders excepted Area M4	4	0	
70	05 05	7	Swain Street Swain Street		Sydenham Sydenham	9.12 75.54	Disabled Only 29	8am-10pm Permit holders excepted Area M4	1 10	1	
73		9	Swain Street Gleeson Avenue	West East	Sydenham Sydenham	5.714 10.262	No Stopping No Stopping	-	0	0	
7:	06	2	Gleeson Avenue Gleeson Avenue	East Fast	Sydenham Sydenham	24.932 62.636	Bus Zone No Parking / 1P	NP 6-9am, 3:30-6:30pm Mon-Fri / 1P 9am-3:30pm Mon-Fri	0 7	0	Missing start Bus Zone sign. There is currently a double arrow No Stopping sign liked by call renlarament histor
76	06 06 06	4	Gleeson Avenue	East	Sydenham Sydenham	43.226	No Stopping No Stopping		0	0	Used by rail replacement buses
72	06	6	Gleeson Avenue	West	Sydenham	37.388	No Stopping	-	0	0	
75	07 07 07	2	Park Road	East	Sydenham Sydenham	14.197 13.11 5.246	No Stopping Unrestricted	-	0 2 0	0 2 0	
83	07	4	Park Road	East	Sydenham Sydenham	137.229	No Stopping 29	8:30am-6pm Mon-Fri Permit holders excepted Area M4	22	20	
83	07	6	Park Road Park Road	East West	Sydenham Sydenham	8.314 8.4	No Stopping No Stopping	-	0	0	
85	07		Park Road Park Road	West	Sydenham Sydenham	136.58 8.182	2P No Stopping	8:30am-6pm Mon-Fri Permit holders excepted Area M4	23	23	
87	07	9 10	Park Road Park Road	West	Sydenham	13.976 13.433	Unrestricted No Stopping		2	2	
85	08	10	Railway Road	East		10.213	No Stopping	-	0	0	
90	08	2		East	Sydenham Sydenham		No Parking / 1P No Stopping	NP 6-9am, 3:30-6:30pm Mon-Fri / 1P 9am-3:30pm Mon-Fri -	3	3	
90 93	08 08	4	Railway Road Railway Road	East East	Sydenham Sydenham	12.224 85.625	No Stopping No Stopping	- 6-9am Mon-Fri	0	0	
94 95	08	6	Railway Road Railway Road	East East	Sydenham	22.616 28.591	Bus Zone No Stopping		0	0	Missing start sign
96			Railway Road	West	Sydenham Sydenham	11.802 22.073	No Stopping Bus Zone	-	0		
99	08	10	Railway Road		Sydenham	108.098	No Stopping	3:30-6:30pm Mon-Fri		0 14 0	
95	08	12	Railway Road	West	Sydenham	8.278 39.113	No Stopping No Stopping	-	0	0	
10	09		Rowe Lane		Sydenham	11.741 113.539	No Stopping No Parking		0	0	
10	09	3	Rowe Lane	North		11.123 36.254	No Stopping	- 90' Angle Parking Vehicles under 6m only 8:30am-6pm Mon-Fri Permit	0	0	
10		_			.,	_		holders excepted Area M4 90' Angle Parking Vehicles under 6m only 8:30am-6pm Mon-Fri Parmit		10	
10	09	5	Rowe Lane	South	Sydenham	33.729 34.552	4	holders excepted Area M4	10	10	
10	010	6		East	Sydenham Sydenham	42.86	No Board	8:30am-6pm Mon-Fri Permit holders excepted Area M4	5	5	Matrix: No space to park
10	010	3	Reilly Lane Reilly Lane	East West	Sydenham Sydenham	91.323	No Parking No Parking		0	0	No Entry Authorised vehicles only Gate to be kept closed at all times No Entry Authorised vehicles only Gate to be kept closed at all times
11	010	4	Reilly Lane	West	Sydenham	91.137 6.56 26.57	No Stopping Unrestricted	-	0	0	
11	010	6	Reilly Lane	West	Sydenham	9.676	No Parking	-	0	0	
11	011	1		East	Sydenham Sydenham	6.283 194.079	No Stopping 29	- 8:30am-6pm Mon-Fri Permit holders excepted Area M4	0 22		
11	011	3	Yelverton Street Yelverton Street	East West		9.396 9.329	No Stopping No Stopping	-	0	0	
11	011 011	5	Yelverton Street Yelverton Street	West	Sydenham Sydenham	194.5 7.256	29 No Stopping	8:30am-6pm Mon-Fri Permit holders excepted Area M4	25 0	25 0	







transport.nsw.gov.au

OFFICIAL

Acknowledgement of Country

Transport for NSW (Transport or TfNSW) acknowledges the Gadigal people of the Eora Nation, the traditional custodians of the land in which this project is located, and all peoples and nations.

We pay our respects to Elders past and present and celebrate the diversity of Aboriginal people and their ongoing cultures and connections to the lands and waters of NSW.

Many of the transport routes we use today – from rail lines, to roads, to water crossings – follow the traditional song lines, trade routes and ceremonial paths in Country that our nation's First Peoples followed for tens of thousands of years.

Transport for NSW is committed to honouring Aboriginal peoples' cultural and spiritual connections to the land, waters and seas and their rich contribution to society.





Table of Contents


1.	Executive Summary
2.	Purpose of this report6
2.1	Background6
3.	Project overview7
4.	Engagement approach9
4.1	Engagement objectives
4.2	How engagement was done9
5.	Consultation summary/what we heard10
5.1	Overview
5.1 5.2	Overview
5.2	Engagement outcomes
5.2 5.3	Engagement outcomes
5.2 5.3 6.	Engagement outcomes
5.2 5.3 6. 6.1	Engagement outcomes





Document control

Authors	Transport for NSW
Document owner	Community and Place
Approved by	Director, Inner West Place
Document number	ISBN-978-1-922875-93-8
Branch	Community and Place
Division	Greater Sydney



1. Executive Summary

This report outlines the engagement that Transport for NSW (Transport) conducted with residents, businesses and key stakeholders on the proposed construction of Sydenham Bus Layover (bus layover, or the layover) at the corner of Railway Road and Burrows Avenue in Sydenham.

Transport is proposing a new bus layover facility as part of the Bus Priority Infrastructure Program (BPIP) to improve the reliability and efficiency of bus services while easing congestion for all road users.

The proposed bus layover would give bus drivers a place to park safely between services and improve bus travel times and service frequencies, increasing reliability for passengers. Sydenham requires a bus layover area to cater to the growing number of bus services in this area. At present, prior to picking up passengers, buses park along Burrows Avenue and Railway Road creating congestion and impacting bus operations.

The proposed bus layover facility at the corner of Railway Road and Burrows Avenue in Sydenham would:

- provide six bus parking spaces, a meal room and toilets for bus drivers
- create a path for pedestrians, passengers and the community to safely walk to and from Railway Road to Gleeson Avenue
- build a noise wall to separate the nearby homes from the new bus layover facility and minimise noise impacts from the bus layover facility
- install driveways for buses to enter from Railway Road and leave through Burrows Avenue
- remove parking spaces from Burrows Avenue to create enough space for buses to safely exit the layover area
- convert parallel car parking spaces on the northern side of Railway Road to angled parking, subject to approval from Inner West Council.

Community engagement began on Friday 24 November and ended on Friday 8 December 2023, with community notifications letterbox dropped and nearby properties doorknocked on Railway Road, Burrows Avenue and Wright Street. Feedback was invited in person, on the phone, via email and through the Sydenham bus layover project web page, the Transport Your Say website, and the NSW Government Have Your Say portal.

At the end of the engagement period, feedback was received from 18 individuals. The local community supported the proposed bus layover in principle but had concerns around parking and the proposed location.

Transport has considered all feedback received from the local community and has decided to progress development of the proposal with the following amendment:

 relocation of the pedestrian walkway between the noise wall and the bus layover, providing residential properties with more privacy. The noise wall will be set back half a metre from residential property boundaries to allow access for maintenance purposes.

Pending approval, construction is planned to start in early 2024. We will continue to inform the community and stakeholders as the project progresses.

OFFICIAL

Attachment 2

2. Purpose of this report

2.1 Background


This report is regarding Transport's proposal for the Sydenham Bus Layover, community engagement and feedback to the proposal, as well as the next steps following the release of this report.

Sydenham Station is an important multimodal transport interchange. Buses servicing this major hub currently have insufficient space to terminate and layover between services. Delivery of the Sydney Metro project resulted in adjustments to the Bus Zone around Sydenham Station. Consequently, this has created increased bus congestion and is impacting bus operation, passengers and the safe movement of pedestrians and other road users.

Analyses of bus timetables show there are 306 bus arrivals at Sydenham Station per week that require some waiting time prior to scheduled departure times. The proposed bus layover facility will alleviate congestion, delays and reduce instances of buses 'double parking' on Railway Road and Burrows Avenue. This will assist in improving the on-time running of buses and local traffic flows on Railway Road and Burrows Avenue. Availability of this proposed bus layover will allow bus operators the opportunity to schedule more efficient bus movements and reduce dead (empty) running between Sydenham and Tempe on the Princes Highway, or other depots through inner-city streets.

The proposed bus layover facility will also provide a valuable operational asset to support assured delivery and increase efficiency of future bus services at this intermodal node between the Sydney Trains, Metro, Inner-West and Inner-East bus networks in alignment with Future Transport, the Greater Sydney Integrated Network Plan and the Greater Sydney Bus Network Strategy.

This report highlights the features of the proposed bus layover facility and details the community engagement conducted, and the project team's responses to feedback from local residents, businesses and other stakeholders.



3. Project overview


ER WEST

Sydenham Station is an important multimodal transport interchange. Buses servicing this major hub don't have enough room to terminate and layover between services. This creates congestion on Railway Road, Burrows Avenue and Gleeson Avenue (a freight corridor to the Airport and Port Botany).

The limited bus layover options in the area result in buses idling in these streets, causing obstruction to pedestrians and cars, in active bus zones and surrounding streets. Safety issues, delays to passengers and bus services are currently being experienced as a result.

To resolve this issue, Transport for NSW proposes a bus layover facility at the corner of Railway Road and Burrows Avenue in Sydenham.

3.1 Proposed bus layover location




3.2 Original design proposal









4. Engagement approach

4.1 Engagement objectives

- To raise awareness of the Sydenham Bus Layover proposal
- Build preparedness and strategic readiness for changes in traffic and parking arrangements to the local area and seek comment, feedback, ideas, and suggestions on the proposal.
- Build a database of interested community members with whom we can continue to engage during the proposal's development and delivery.
- Engage with relevant councils, businesses and other community groups.
- Inform the community, businesses and other stakeholders on the proposal.

4.2 How engagement was done

Transport used an 'inform' and 'consult' engagement approach for this project:

- 'Inform' the community, businesses and other stakeholders on the proposal
- 'Consult' on changes to parking on Railway Road and Burrows Avenue.

Community engagement occurred from Friday 24 November to Friday 8 December 2023.

Community members were invited to provide their feedback through the Transport project website, Your Say Transport website, the NSW Government Have Your Say portal, as well as via face-to-face conversations, email correspondence, doorknocks, and phone conversations via the project info line.

Community engagement activities

Channel	Description
Have your say community notification	 170 print notifications were letterbox dropped to residents and businesses across the proposal area Email notifications to emergency services and local schools Notifications and engagement with disability peak bodies through the Accessible Transport Advisory Committee
Transport project web page	 www.transport.nsw.gov.au/projects/current- projects/sydenham-bus-layover 122 unique visitors accessed the project page
Your say Transport website	 yoursay.transport.nsw.gov.au/sydenham-bus-layover 132 unique visitors accessed the Your say page
NSW Government Have Your Say portal	www.nsw.gov.au/have-your-say/sydenham-bus-layover
Inner West Community Forum	The Sydenham Bus Layover proposal was featured in the Inner West December livestream on Wednesday 6 December, reminding community members to have their say
Doorknocks	 On Thursday 23 and Friday 24 November, 24 properties were doorknocked along Railway Road and Wright Street. Direct face to face engagement was carried out with 15 residents at their residential properties. Two businesses were informed and engaged along Railway Road.
Key stakeholder briefings	 Inner West Council briefed 7 June and 24 November 2023 Rail, Tram and Bus Union, and Transport Workers' Union of NSW briefed 19 October 2023

OFFICIAL

Item

5. Consultation summary/what we heard

5.1 Overview

 \blacksquare

Transport received feedback from 18 residents and local businesses regarding our proposed bus layover facility at the corner of Railway Road and Burrows Avenue.

Feedback provided that is not related to this proposal has been passed on to the relevant agency for their consideration. Comments in relation to public transport improvements and bus services have been passed on to the relevant team within Transport.

lssue Category	Issue Raised	Response
Access	Access to the rail corridor from Burrows Avenue must be maintained	Sydney Trains requires access to their assets at all times for maintenance. Transport has reviewed the design to maintain access to the rail corridor from Burrows Avenue. A 'No Parking' sign will be installed in front of the railway gate on Burrows Avenue/Railway Road and a chevroned area will be marked at the access gate.
Alternative layover location	Transport should consider alternative layover locations, including Railway Parade, as well as the lower part of Railway Parade between Marrickville Road and Sydenham Road, which was the preferred option in 2018 as part of the Metro upgrade for Sydenham	Transport appreciates the community's feedback on alternative locations for a bus layover facility. We have evaluated suggestions for other bus layover locations raised by the community. The alternative location on the lower part of Railway Parade between Marrickville Road and Sydenham Road, noted in the 2018 Planning Approval Consistency Assessment Form, relates to traffic changes as part of Sydney Metro's proposed projects. As this project is being delivered under the Bus Priority Infrastructure Program, the project objectives are separate to Sydney Metro. Consequently, the 2018 Planning Approval Consistency Assessment Form does not apply to this project. A bus layover requires adequate space to accommodate bus parking as well as entry and exit manoeuvres. There is insufficient space to locate a bus layover on upper Railway Parade. The proposed bus layover will provide a valuable operational asset to support assured delivery and increase efficiency of existing and future bus services at this intermodal node between the Sydney Trains, Metro, Inner-West and Inner-East bus networks. This project along with other layover projects align with the Future Transport, the Greater Sydney Integrated Network Plan and the Greater Sydney Bus Network Strategy.

		Overall, Transport expects the project to benefit the community and wider bus network. The proposed bus layover is expected to improve local traffic flows, road safety, and on-time running by reducing congestion, delays, and reduce instances of buses double parking on Railway Road and Burrows Avenue.
Amenity	The proposed layover and noise wall will be an eyesore that will attract graffiti and reduce property value	Transport will carry out a visual impact assessment to evaluate the landscape character and visual impact of the bus layover facility, including the building and noise wall and assess how it fits into the surrounding environment. The visual impact assessment will be included in the Review of Environmental Factors and mitigations will be provided where required. Transport will publish the Review of Environmental Factors report on the project website once completed.
		The final design will look at solutions for the surface of the noise wall as part of graffiti prevention. The project team will work with Transport's maintenance teams to ensure appropriate maintenance for the bus layover, including the noise wall.
	Will there be street lighting for the new footpath	Yes, lighting will be provided within the bus layover which will light the footpath. The lighting assessment for the bus layover has been performed in accordance with the Australian Standards, Lighting for Roads and Public Spaces (AS/NZS 1158.3.1.)
	Lighting for the new footpath needs to be directed away from residential properties	Transport understands residents' concerns regarding potential light spillage from the construction of the proposed bus layover. This consideration has been included in the lighting assessment of the bus layover. Properties on the eastern boundary of the bus layover will be shielded from light spillage by the noise wall.
Bus Services	What hours will the buses use the layover?	Hours that buses will use the bus layover facility will be according to bus timetabling, dependent on public transport needs and bus services Transport needs to provide the community.
	Bus drivers need to turn off their engines when at the layover	Transit Systems will be the entity managing the buses and layover operation. Transport does not expect bus drivers to continue running their engines when parked and stationary.
	Noise from the layover	To manage operational noise from the bus layover, Transport has taken a proactive approach and incorporated a noise wall in the design. The noise wall will be located between the layover and the adjacent properties to provide noise shielding from the layover.
		As part of the Review of Environmental Factors assessment for the project, a noise assessment of the operation of the layover will be undertaken. The results of the noise assessment will inform the height of the noise wall panels.
		Transport seeks to minimise noise impacts from the layover operation and along with the noise wall, will consider other safeguards and management measures identified in the assessment. Results of the noise

		assessment and associated measures will be included in the Review of Environmental Factors report which will be published on the project website.
Construction	Noise impact on local residents during construction	Transport understands residents' concerns regarding any noise produced during the construction of the proposed bus layover construction. As part of the Review of Environmental Factors assessment for the project, a noise assessment of the construction of the layover will be undertaken. This will include an assessment of construction hours, construction activities and predicted noise impacts. Safeguards and management measures will be identified to minimise noise impacts. Transport will update the community on the measures to be implemented in the Review of Environmental Factors report which will be published on the project website.
Consultation	Two weeks of consultation is not sufficient	A two-week period is the standard timeframe to get feedback on projects of this scale. To ensure that residents and other stakeholders on Railway Road were reached, doorknocks were carried out on 23 and 24 November, resulting in direct face to face engagement with 15 residents and two businesses. Additionally, the project team accepted all feedback received after the closing date for submissions. We received feedback from 18 individuals in total.
	Why doesn't Transport post directly to local groups, such as Tempe 2020, on social media?	Transport is unable to post directly to community groups on social media as most group pages (like Tempe 2020) are set to private and not accessible by non-members.
Environment	Alternatives to tree removal should be considered	During the concept development phase, Transport sought to avoid or minimise tree removal by investigating alternative designs. Unfortunately, as the project site is constrained due to the limited available space, two mature trees located at the proposed layover entry point need to be removed. The two trees proposed to be removed as part of the project will be replaced with four trees, to be planted within the Inner West local government area (subject to Council approval). Additionally, the project has allocated space within the northern section of the site for a turfed area.
	Why was the DA for removal of two Melaleucas (paper barks) not advertised?	The approval process for removal of the paperbark trees did not involve a development application (DA). Transport has consulted with Inner West Council and our environmental team, and the trees will be removed in accordance with Transport guidelines, which include offsetting the removal on a two for one basis.
	Native Vegetation should be used for this project	Transport prefers to use native vegetation for landscaping on projects, particularly when it is endemic to the area. More details on the species of trees to be planted as part of the proposed bus layover will be released in the Review of Environmental Factors report.

TRANSPORT

	More trees should be planted as part of the proposal	Transport will be offsetting the removal of trees on a two for one basis. The two trees proposed to be removed as part of the project will be replaced with four trees, to be planted within the Inner West Council local government area (subject to Council approval.) The Inner West Council will manage the tree planting locations.
Noise wall	How high would the proposed noise wall be?	The results of the noise assessment for the proposed bus layover facility will inform the height of the noise wall along with the visual impact assessment. The results will be included in the Review of Environmental Factors report which will be published on the project website.
	What would be the impact on light to adjoining properties from the noise wall?	To address residents' concerns regarding the impact on natural lighting, Transport will perform a lighting assessment of the bus layover. This will be completed once the proposed design for the noise wall has been developed and will form part of Inner West Council's lighting review to assess the impact to natural lighting from the bus layover project. The results will be included in the Review of Environmental Factors report which will be published on the project website.
	The noise wall will not do enough to mitigate noise from the layover	As part of the Review of Environmental Factors assessment for the project, a noise assessment of the operation of the bus layover will be undertaken. The results of the noise assessment will inform the noise wall panel height. Transport seeks to minimise noise impacts from the layover operation and along with the noise wall, will consider other safeguards and management measures identified in the assessment. Results of the noise assessment and associated measures will be included in the Review of Environmental Factors report which will be published on the project website.
Parking	Railway Road is used for parking buses for rail replacement services, would a permanent layover replace this practice?	The proposed bus layover is a permanent facility and will be used by regular bus services as well as by rail replacement services. The layover is expected to improve local traffic flows, road safety, and on-time running by reducing congestion, delays, and instances of buses 'double parking' on Railway Road and Burrows Avenue. We do not expect to exceed six buses at the layover at any given time.
	There is not enough parking in the street and angled parking does not provide enough spaces to offset the loss of spaces, negatively impacting residents and businesses	Transport has undertaken a parking assessment and has worked to optimise the parking spaces in Railway Road and Burrows Avenue. The introduction of angled parking provides an additional five spaces to the existing eight spaces in the section along Railway Road between 105 and 117 Railway Road. Transport has also carried out a review of the Sydenham residential parking permit scheme and available parking spaces post-project delivery. There are sufficient available parking spaces within the project scope area (including Wright Street) to accommodate the permit allocation available for properties along Railway Road.

	Angled parking looks the wrong way	The proposed angled parking is in accordance with Australian Standard 2890 Parking Facilities.
	Angled parking would narrow the road and increase the risk of crashes	The introduction of angled parking has historically been shown to reduce vehicle speeds which creates a safer road environment. Angled parking will also not adversely affect traffic flows along Railway Road.
Will parking on the southern side of Railway Road be modified or removed?	Parking spaces on the southern side of Railway Road will not be modified or removed as part of this project scope. The parking changes are on the northern side of Railway Road and on Burrows Avenue.	
	Why is angled parking on the right side of Railway Road and not the left?	The angled parking is proposed for the northern side of Railway Road to accommodate bus turning manoeuvres into the layover.
		The parking changes to accommodate the bus layover will result in a net reduction of 12 parking spaces.
	parking spaces?	For Railway Road on the southern side, there is no change to the existing 23 parking spaces. On the northern side there are currently eight parking spaces which will increase to 13 parking spaces with the introduction of angled parking.
		On the western side of Burrows Avenue, 12 parking spaces will be reduced to six. The 11 informal parking opportunities in the right turn pocket on the eastern side of Burrows Avenue will be removed as that area forms the layover exit for the buses.
		Transport has undertaken a parking assessment to optimise parking spaces. Transport has also carried out an assessment of the Sydenham residential parking permit scheme and available parking spaces post- project delivery. The results of the assessments indicate that there are sufficient available parking spaces within the project scope area (including Wright Street) to accommodate the permit allocation available for properties along Railway Road.
Pedestrian access	Will the pedestrian walkway next to the layover integrate with small Wright Street?	The proposed footpath will be located between the noise wall and the proposed bus layover facility, noting the walkway will be separated from the layover with a pedestrian fence. This means that Wright Street will not be accessible from the footpath due to the proposed noise wall. This is to ensure privacy and effective noise mitigation for adjacent properties on the eastern boundary.
	The intersection of Gleeson and Burrows	The current traffic signal phasing of Gleeson Avenue and Burrows Avenue has been reviewed as part of project development and Transport has determined that no changes are required.

	Avenue should have pedestrian priority	
	Footpath on Burrows Avenue should be widened	Transport has assessed the existing pedestrian infrastructure and determined there is sufficient existing pedestrian infrastructure on the western side of Burrows Avenue (including footpath width) to enable safe pedestrian movements to the Burrows Avenue bus stop (Stop ID: 204421) and Sydenham Station.
		The footpath on the eastern side of Burrows Avenue on the boundary of the bus layover will be permanently removed to enable safe and efficient bus exit from the layover. The new walkway will provide pedestrian a safe route between Gleeson Avenue and Railway Road.
	The proposed walkway will create noise next to properties	Transport has updated the design, the proposed walkway will now be located between the noise wall and the proposed bus layover, noting the walkway will be separated from the layover with a pedestrian fence. The noise wall will provide noise shielding to adjacent properties from pedestrian traffic.
	Commuters should not need to cross Gleeson Avenue to get to the Burrows Avenue bus stop	There is sufficient existing pedestrian infrastructure to facilitate safe pedestrian movements between Sydenham Station and Burrows Avenue bus stop (Stop ID: 204421). There are existing signalised pedestrian crossings across Burrows Avenue and Gleeson Avenue. Transport does not have any plan to move bus stops within and outside the proposal area.
	The proposed walkway will make travel to the bus stop on Burrows Avenue from Railway Road longer	The footpath on the eastern side of Burrows Avenue on the boundary of the bus layover will be permanently removed to enable safe and efficient bus exit from the layover. Pedestrians would be able to use a new walkway between Gleeson Avenue and Railway Road. Along with the existing footpath to Burrows Avenue along Railway Road, the new walkway will provide an alternative safe option for pedestrians.
Proposed layover	This area was previously proposed as part of the Metro but did not go ahead, what changed?	The 2018 Planning Approval Consistency Assessment Form relates to traffic changes as part of Sydney Metro's proposed projects. The proposed bus layover facility is associated with the Transport's Bus Priority Infrastructure Program which supports the overall Future Transport Strategy.
	Why build the layover now when the area is expected to be rezoned and redeveloped after the Bankstown Line Closure?	The proposed bus layover will provide a valuable operational asset to increase efficiency of existing and future bus services at this intermodal node between the Sydney Trains, Metro, Inner-West and Inner-East bus networks in alignment with Future Transport, the Greater Sydney Integrated Network Plan and the Greater Sydney Bus Network Strategy.
	The cost outweighs the benefits	Transport has performed a benefits assessment as part of the proposal. The bus layover will provide bus drivers a place to park safely between services, improve operating efficiencies and increase reliability for

		passengers, leading to reduced operating costs. The assessment concluded over the lifetime of the project, the benefits provided by the layover are expected to exceed the project capital cost.
	Existing stormwater pipe at the location of the proposed layover has caused flooding to adjacent properties	Transport will liaise with Sydney Water and Inner West Council to manage storm water drainage at the proposed site.
	Why not build a toilet inside the station instead of at the layover	Sydenham Station already has toilet facilities with wheelchair accessibility and baby change tables. The purpose of the amenity block at the layover is to enable bus drivers to access amenities between shifts as efficiently as possible without the need to walk to Sydenham Station.
Safety	Will drivers reverse into and out of the facility?	The bus layover has been designed to allow buses to enter and exit the facility in forward motion. Buses will enter the layover from Railway Road and exit onto Burrows Avenue.
	Bus drivers would need to cross the road from the bus stop to use the amenity block	Bus operators laying over in Burrows Avenue will need to cross Burrows Avenue to access toilet and meal room facilities at the bus layover.
	How will buses enter and exit the layover facility safely?	The bus layover has been designed with the safety of pedestrians, road users and passengers as the priority. All buses will enter and exit the layover in a forward motion. A new pedestrian walkway between Gleeson Avenue and Railway Road and the existing walkway on the north side of Burrows Avenue will separate pedestrians from bus movements.
Traffic	The layover will create more traffic on Railway Road and Burrows Avenue, creating congestion and noise	Transport expects the project to benefit the community and wider bus network. The proposed bus layover facility is expected to improve local traffic flows, road safety, and bus timetable reliability by reducing congestion, delays, and reducing instances of buses 'double parking' on Railway Road and Burrows Avenue. To manage noise to adjacent properties, the proposal includes the construction of a noise wall. The noise wall will run along the eastern boundary of the bus layover and will provide significant noise shielding.
	Will the configuration of lanes at the Intersection of Gleeson Avenue and Burrows Avenue change as part of this proposal?	The configuration of lanes at the Gleeson Avenue and Burrows Avenue intersection will not change as part of this project.

OFFICIAL

Not included as part of this project	Introduce a right hand turn signal phase from Gleeson Avenue into Unwins Bridge Road	The Gleeson Avenue and Unwins Bridge Road intersection is outside the scope of the proposed bus layover facility. Transport has shared this feedback with the relevant team for investigation.
	The pedestrian zebra crossing on Burrows Avenue, adjacent to the train station, needs to be raised into a wombat crossing	The Burrows Avenue zebra crossing to Sydenham Station is outside the scope of this proposal. Transport has shared feedback with the relevant team for investigation.
	Transport should build a commuter carpark next to Sydenham Station	Commuter car parks are delivered under Transport's Commuter Car Park Program. At present there are no plans to build parking facilities near Sydenham Station. Due to the location of the station, particularly its proximity to the Sydney CBD, commuters are not expected to drive to the station by car.

5.2 Engagement outcomes

Transport would like to thank everyone who took the time to consider the proposal and provide feedback. Transport received feedback from 18 residents and local businesses as well as other stakeholders regarding the proposed bus layover facility at the corner of Railway Road and Burrows Avenue.

Key areas of concern were parking and the proposed location.

Transport has considered all feedback received from the local community and has decided to progress development of the proposal with the following amendment:

 Relocating the pedestrian walkway between the noise wall and the bus layover, providing residential properties with more privacy. The noise wall will be set back half a metre from residential property boundaries to access for maintenance purposes.

Transport notes the impact on parking in the area. We encourage parking on properties where possible, parking on Unwins Bridge Road, Wright Street and surrounding local streets.

Feedback received on the noise wall and bus driver amenities will be considered as the design process progresses.

5.3 Next steps

- Inform the community of progress on the proposed bus layover facility
- Publish the Review of Environmental Factors report on the project web page
- Endorsement of the proposed bus layover and parking changes by Inner West Council
- Notify community members and start construction work on the bus layover.



OFFICIAL

HR HR

- Appendix 6.
- 6.1 **Community Update**

Transport for NSW

Sydenham Bus Layover **Have Your Say**



November 2023

The NSW Government is proposing a new bus layover facility as part of the Bus Priority Infrastructure Program to improve the reliability and efficiency of bus services, while easing congestion for all road users.

Sydenham requires a bus layover area to cater to the growing number of buses services in this area. Prior to picking up passengers, buses currently park along Burrows Avenue creating congestion and safety issues for pedestrians and drivers.

Transport is proposing a bus layover area at the corner of Railway Road and Burrows Avenue. This would give drivers a place to park safely between services and improve bus travel times and service frequencies, increasing reliability for passengers.

Key features

The buses would enter from Railway Road and exit into Burrows Avenue at the proposed bus layover which would have:

- six bus parking spaces
- a dedicated drivers' amenity block with a lunch room and toilets
- a noise wall between residential properties and the lavover facility
- landscaping.

Pedestrian walkway

Transport would also create a separate pedestrian walkway to provide the public with a direct pathway to Sydenham Station.

Benefits

- Bus layover with space for six buses and an amenities block for drivers, freeing up the streets and improving traffic flow
- Improved bus on time running and reliability



Transport for NSW acknowledges the Gadigal people of the Eora Nation as the Traditional Custodians of the lands on which we work and pays respect to Elders past and present.

OFFICIAL

- New, separated and safer walkway for pedestrians and residents to get to Sydenham Station
- Improved safety and connectivity for pedestrians, commuters and drivers
- Reduced emissions from buses idling and circling between services.

Expected impacts

- Some loss of parking will occur as part of this project; existing street parking on Railway Road will be converted to angled parking to provide additional parking spaces
- Two trees in the nature strip on Railway Road would need to be removed to create the entry into the layover.

If approved construction is expected to take up to five months to complete, weather permitting.

We have included a map on the reverse side of this notification.

FAQs

Will any car spaces be lost?

Parking loss would be limited with the creation of angled parking on Railway Road, replacing some of the spaces required for the layover space.

Will access change for residents?

Yes-during pavement and footpath work on Burrows Avenue and when the proposed entry and exit points are being established, but these changes would be temporary.

ltem




Have your say

Transport invites your feedback on the proposed bus layover at the corner of Railway Road and Burrows Avenue in Sydenham

Have your say by Friday 8 December 2023 at yoursay.transport.nsw.gov.au/sydenham-bus-layover You can also email projects@transport.nsw.gov.au or call us on 1800 684 490.

Contact us

projects@transport.nsw.gov.au







Have your say at yoursay.transport.nsw.gov.au/ sydenham-bus-layover



For the latest traffic updates: Call 132 701, visit livetraffic.com or download the app Live Traffic NSW

G=O=O Interpreter service

For languages other than English call 131 450 Arabic · Greek · Hindi · Mandarin · Vietnamese

طلب خدمة الترجمة الشفهية للغات غير الإنجليزية اتصل بالرقم 131 450

Για υπηρεσίες διερμηνείας σε άλλες γλώσσες εκτός από τα Αγγλικά καλέστε το 131 450

अंग्रेज़ी के अतिरिक्त अन्य भाषाओं के लिए दुभाषिया सेवा 131 450 पर कॉल करें

获取英语以外的其他语言口译协助服务可以致电131 450

Để có dịch vụ thông ngôn cho các ngôn ngữ khác tiếng Anh, gọi số 131 450

www.transport.nsw.gov.au/privacy-statement#Your_Privacy

Page 2 of 2

Have Your Say: Sydenham Bus Layover - November 2023



OFFICIAL

田叉

6.2 Transport website

Home / Projects / Current Projects / Sydenham Bus Layover

Sydenham Bus Layover

Reviewed 28 Nov 2023

The NSW Government is funding a new bus layover facility as part of the Bus Priority Infrastructure Program to improve the reliability and efficiency of bus services, while easing congestion for all road users.



Sydenham bus layover

Latest news

November 2023 - Have Your Say


Transport invites your feedback on the proposed bus layover at the corner of Railway Road and Burrows Avenue in Sydenham.

Have your say by Friday 8 December 2023 at the consultation website.


Please view or download the **November 2023 Have Your Say (PDF, 1.19 MB)** for more information.

https://www.transport.nsw.gov.au/projects/current-projects/sydenham-bus-layover


OFFICIAL




https://yoursay.transport.nsw.gov.au/sydenham-bus-layover







https://caportal.com.au/tfnsw/inner-west



Extraordinary Local Traffic Committee Meeting 3 June 2024

12

А

В

С

D

Е

₫G

н

FOR REVIEW

PART: SHEET: 1 OF 41 A

12

BRIDGE N

REV VER EDMS No C01.01



Attachment

က

103

6

CONNECT SYDNEY

DESIGN CHECK P. MCLEAN

PROJ/DES MNGR J.STEWARI

APPROVED _____V_TIET____

9

13.02.2024

13.02.2024

13.02.2024

DRAWING SET

10

STATUS: DETAILED DESIGN - 1009

rg No. 520212-AURC-038-RW-DRG-000001

11

A ISSUED FOR 20% DETAILED DESIGN

2

1

COORDINATE SYSTEM: MGA ZONE 56/GDA20

3

DESCRIPTION

.C 21.09.2023 A.J 21.09.2023

DESIGNER VERIFIED INITIAL/DATE INITIAL/DATE

HEIGHT DATUM

4

T 21.09.21

5

DESIGN LOT CODE

APPROVE INITIAL/DA

က

Attachment



А

В

С

D

Е

F

G

1 2	3		4	5		6	\cap	7	8		9	10		11		12	
THE INFORMATION CONTAINED IN IS SOLELY FOR THE USE OF TRAIN WHICH IT HAS BEEN PREPARED. A NO DUTY TO OR ACCEPTS NO RES RELY UPON THIS DOCUMENT, . ALL WORKS SHALL BE PERFORME DRAWINGS AND SPECIFICATIONS I REFERRED TO AURECON FOR CLA . ALL DMENSIONS ARE IN MILLIMET CHAINAGES AND EVECIS ARE IN M . ALL DMENSIONS RELEVANT TO SE VERIFIED BY THE CONTRACTOR B HAS COMMENCED. DO NOT SCALE FROM DRAWINGS.	SPORT FOR NSW FOR THE PURP URECON AUSTRALIA PTY LTD U PONSBULITY TO ANY THIRD PAF D IN ACCORDANCE WITH TINSW NULESS OTHERWISE SHOWN. NS FROM THESE DOCUMENTS S RIFICATION AND APPROVED BY ERS UNLESS NOTED OTHERW ETRES UNLESS NOTED OTHERW	OSE FOR NDERTAKES TY WHO MAY STANDARD HALL BE TFNSW. E. ALL NISE. SHALL BE BRICATION		2. THE CON A STABLE CONSTRI BATTERI ENVIRON 3. THE CON VEHICUL INTRUDEI 4. ALL PITS, FITTED W OTHER ENV	ITRACTOR IS E CONDITION UCTION ACTI NG IS BY THE MENT. ITRACTOR M AR TRAFFIC RS. MANHOLES WITH A CONFI	SRESPONSIBLE FOR RESPONSIBLE FOR ADD ENSURING NO MTIES, PROVISION C E CONTRACTOR AS R UIST MAKE PROVISIO AND PEDESTRIANS, A INED SPACE WARNIN ITAL NOTES TORS WILL BE PROVI	MAINTAINI OPATT SHA DF TEMPOP REQUIRED ON FOR THE AND OTHE ND OTHER IG SIGN.	NG ALL EXCAVATION ALL BE OVERSTRESS RARY BRACING, SHOI TO PROVIDE A SAFE E SAFETY OF NORMA RS INCLUDING UNAU CONFINED SPACES S	ED DURING NING AND WORKING L THORISED HOULD BE	4 4 4 4 4	MODEL DRAWING N 3. ALL SUBSURFACE I	INAGE CONNECTION H TRISW STANDARE - SUPPLEMENTARY FOR SUBSURFACE H PROJECT TRISW ' A, GEOTEXTILE LAP MD.R33,A06, DRAINAGE TRENCH ADIENT OF NOT LES ACCORDANCE WITH FORATED AND NON YED SEALS ARE NO	Y MODEL DRA' TRENCH AND SPECIFICATIC PS SHALL BE II I DRAINS SHAI SS THAN 0.5%, H R33 AND ST/ N-PERFORATE	WINGS, DEGE DRAINS SHAI DN R63: APPLICATIOI N ACCORDANCE WI LL BE INSTALLED WI TRENCH DRAIN TO ANDARD DRAWING M ED PLASTIC PIPE TO	LL BE IN N G3 TH TINSW TH A BE MD.R33.406. CONFORM		A
ORIGN OF LEVELS - AHD COORDIN 2020. WHERE A PROPRIETARY ITEM (OR COUVALENT ITEM IS PROPOSED.) MANUFACTURERS SPECIFICATION APPROVAL AND DEMONSTRATE TI EQUIVALENT OR BETTER, PRIOR TI EQUIVALENT OR BETTER, PRIOR TI EQUIVALENT OR BETTER, PRIOR TI EDUIVALENT OR BETTER, PRIOR DUIVALENT OR BETTER, PRIOR DUIVALENT DUIVALENT OR BETTER, PRIOR DUIVALENT DUIVALENT DUIVALENT OR BETTER, PRIOR DUIVALENT DUIVALEN	EQUIVALENT) IS SPECIFIED, AN ITHE CONTRACTOR SHALL PROV S FOR BOTH PRODUCTS TO TIN HAT THE PRODUCT DERFORMAN E TO BE INSTALLED FIXED AND E RES INSTRUCTIONS. RESPONSIBILITY OF THE CONT RESPONSIBILITY OF THE CONT ALL TIME AND NO PART IS TO BE DR SHALL DEVELOP WORK METL OF STRUCTURAL STEEL/FORM NELS ETC, AND PROVDE TEMPO NG AND SHORING ETC, TO KEI E AND FREE FROM WATER AT A A STRUCTURAL ENGINEET TO D	D AN DE SW FOR CE IS TESTED IN RACTOR TO NED IN A IOD ORK/ IORK/ IP THE LI TIMES,		SLURRIE: SURVEY NC 1. THE SUR NAME: G 2. SURVEY 3. THE AERI GUARANT DISCREP, MAGE AN 4. CONTRAC CONTRAC CONTRAL	IS, PAINTS, A DTES AVEY DATA U TO427 GLEE: DATA WAS P LAL MAP PRC TEE ITS SUIT ANCIES BE E ND ACTUAL S CTOR TO VEI UCTION.	IGNS WILL BE FROM SED FOR THE PROJE SON AVE SYDENHAM ROWDED IN AUTOCA WIDED IS USED AS A ROWDED IN AUTOCA WIDED IS USED AS A ROWDEY DATE DONT RIFY SURVEY AND SI IGNAGE NOTES FERENCES HAVE BEE	ECT WAS SI 1 GDA2020 (AD 3D DWG THE BASIS F FOR CONST FOR CONST TACT THE P ETOUT INFO	MATERIALS AND LITTE UPPLIED BY CONNEC 220727. 5 (2DA, PDF AND MOS FOR DESIGN, AURECT TRUCTION DERWAING RUCTION BERVEEN RUICHALS REPRESS ORMATION PRIOR TC	R. T SYDNEY FILE B FORMATS. ON DOES NOT S. SHOULD THE AERIAL INTATIVE.	1. 2.	THESE DRAWINGS SHA SERVICE PROVIDER DR JEMENA DRAWINGS - AUSGRID DRAWINGS - SYDNEY WATER DRAV - TRNSW SIGNAL PLAN - TENSW SIGNAL PLAN - TELSTRA, OPTUS, AND - SYDNEY TRAINS DRAV - SYDNEY TRAINS DRAV - INNER WEST COUNCI EXISTING UTILITIES SHA LLI SERVICES PRESEN INFORMATION AS SHOO PROVIDER ON SITE, TO ALL UTILITY SERVICES	AMMNGS, INCLUDIN MINGS DRAWINGS D TPG DRAWINGS MINGS IL OWN ON DRAWINGS IT, AURECON TAKES WN ON THESE DRAV S RESPONSIBILITY L DCATE AND IDEN I D BOTH PUBLIC AN	NG BUT NOT LI S ARE INDICA S NO RESPON WINGS. Y TO LIAISE WI ITIFY THE SIZE UN PRIVATE LI	IMITED TO: TIVE ONLY AND MAY SUBILITY FOR THE U ITH EACH UTILITY SI F. POSITION, LINE AI	' NOT INCLUD TILITY ERVICE BO LEVEL OF	Έ	C
TEWORKS THE CONTRACTOR TO MAKE SMOK COMPLETION OF THE WORKS DEMANGED OF DIRTED DURING TH COMPLETION AREA COMPLETED NARCH AND THE SAME DENSITY AS THE ADJAC THE SAME DENSITY AS THE ADJAC ALL SERVICE TRENCHES UNDER V BACKFILLED IN ACCORDANCE WITH ASPHALTIC CONCRETE SHALL CON	DTH CONNECTION TO ANY EXIST THE CONTRACTOR MUST REST RES. PAVENESS ON UTILTY SI E CONSTRUCTION. TO THE SAT KELL MATERIAL. SHALL BE COM HAT MATERIAL. ENCLUAR PAVEMENTS SHALL E HICULAR PAVEMENTS SHALL E HCOULS TANDARD DRAMINGS.	NRE OR IRVICES SFACTION OF PACTED TO E TION R116.		1.1. AS 17 INTRO 1.2. AS 17 CONT 1.2. AS 17 SIGNS 1.3. AUST 1.4. TS 06	742.1 MANUA ODUCTION A 742.2 MANUA TROL DEVICE 742.15 MANU IS, INFORMAT IROADS GUIE 3307 INSTALL 5462.8 DELINI	L-PERCICES HAVE BEE LFOR UNFORM TRA ND INDEX OF SIGNS LFOR UNFORM TRA ES FOR GENERAL US AL FOR UNFORM TR TON SIGNS AND ROU DE TO ROAD DESIGN ATION AND MAINTEN EATION PART & DIAGO	AFFIC CONT E. AFFIC CON JTE NUMBE PART 3: GI VANCE OF 5	FROL DEVICES PART FROL DEVICES PART FRING EOMETRIC DESIGN SIGNS.	1: GENERAL 2: TRAFFIC 15: DIRECTION	5.	COMMENCEMENT OF A THE CONTRACTOR MUS UTILITY SERVICES THR ALL WORKS INVOLVING THE UTILITY SERVICE F ENGAGING WITH THE U THEIR REQUIREMENTS ALL WORKS INVOLVING APPROVED BY THE UTI ALL SERVICE PIT COVE INCATIONS AS SHOWN THE DRAWINGS AND SI ALL SERVICE PIT COVE PROPOSED LONGITUDI	ST TAKE EVERY PRI OUGH THE COURSE OUTILITY SERVICES PROVIDER. THE COI TITLITY SERVICE PR AND PROCUREME OUTILITY SERVICE PRO IST SAND MARKERS. I ON THE PUBLIC DO PECIFICATION.	ECAUTION TO E OF THE CON S TO BE UNDE NTRACTOR W ROVIDER, THE NT OF APPRO' S MUST ONLY VIDER. ARE TO BE PL OMAIN DRAWI AT FINISHED S	NTRACT. IRTAKEN TO THE SA' ILL BE RESPONSIBL EXECUTION OF THE VALS FOR WORKS L BE UNDERTAKEN U' LACED IN ACCORDAI INGS, AND IN ACCOF SURFACE LEVELS T	TISFACTION C E FOR WORK TO INDERTAKEN. SING PLANS NCE WITH THI RDANCE WITH D MATCH THE	E	D
ALL BASECOURSE MATERIAL SHAL TO COMEV WITH TIRSWO AS SPEC SUBBASE MATERIALS FOR SUBFAX MODIFIED DENSITY IN ACCORDAN COMPACITON TESTING TO BE NO I BASECOURSE MATERIAL PLACED. ALL SUBBASE MATERIAL PLACED. AND SUBBASE MATERIAL PLACED. TO 95% MODIFIED DENSITY IN ACC OF COMPACTION TESTING TO BE M BASECOURSE MATERIAL PLACED. THE USE OF RECYCLED MATERIAL	IFICATION 3051 - GRANULAR BAS- ED ROAD PAVEMENTS, COMPA- ED ROAD PAVEMENTS, COMPA- ES STHAN 1 TEST PER 50m2 OF SHALL BE IGNEOUS ROCK QUAR V QA SPECIFICATION 3051 - GRA RFACED ROAD PAVEMENTS, CC ORDANCE WITH AS1289 5.21. FI O LESS THAN 1 TEST PER 50m ³ S IS ENCOURAGED BY COS AND	EE AND CTED TO 98% CY OF RIED VULAR BASE MPACTED EEQUENCY OF TINSW. IF		APPLIC/ AT VER ABOVE ABOVE HGH FRI (PAFV) 01 <u>CONCRE 3.1 ALL V 3.2 THE 0 90/40 RATE 3.3 THE 0 </u>	ATION RATE TICAL FACES POINT. ICTION ASPH IF 56. TE BASE WORKS MUS CONCRETE B AT A MINIMU CONCRETE E	BASES SHALL BE CON	M ² AND 0.30 PLICATION MUM POLIS E WITH TIN RCED WITH 3/ /OR SIKA NSTRUCTEI	RATES MUST BE DOU SHED AGGREGATE FF ISW QA R83. SYNTHETIC MACRO AFIBRE FORCE 48 PP D AND TESTED IN AC	JBLED THE NICTION VALUE FIBRE STRUX AT A MINIMUM CORDANCE	10 11 12	IS CONTAINED WITHIN, NO PIPE OR TRENCH SI FOOTING. "WORKS AS CONSTRUC TO ANY BACKFILLING. AUSGRID TRANSMISSIC EXCAVATION IS WITHIN TRANSGRID TRANSMIS WHEN EXCAVATION IS JEMENA GAS - JEMENA UNDERTAKEN AS REQU	HALL BE LOCATED \ CTED" SURVEY ON A DN CABLES - AUSGF I 2m OF TRANSMISS SION CABLES - TRA WITHIN 2m OF TRAN SUPERVISOR SHAI	WITHIN THE Z ALL UTILITY W RID SUPERVIS SION CABLES, ANSGRID REP NSMISSION CA LL BE ON SITE	ONE OF INFLUENCE WORK SHALL BE REC SOR SHALL BE ON SI RESENTATIVE SHAL ABLES. E WHEN EXCAVATIO	(1V:2H) OF A ORDED PRIOF TE WHEN L BE ON SITE		E-20000_dwg
THE CONTRACTOR INTENDS TO US MATERIAL COMPLYING WITH TINSWAND SUBBASE MATERIALS FOR SUC CONSIDERED. SUBJECT TO MATER CERTIFICATIONS BEING PROVIDES THE CONTRACTOR IS TO COMPLU RECYCLED MATERIALS DURING TH MATERIAL THAT DOES NOT COMPL FOR REMOVAL AND REPLACEMENT THEIR OWN COST. SHOULD THE CONTRACTOR MISH- BHALL BE CLEARLY INDICATED IN BENKEEN AN IGNOUS PRODUCT. CLEARLY NOTED. 4 APY EXCAVATION OR SAW CUTTIN REINSTATED WITH APPROPRIATE IN	SE RECYCLED MATERIALS, A FE VG AS SPECIFICATION 3051 - GRA RFACED ROAD PAVEMENTS WIL ALL SAMPLES AND APPROPRIAT TO THE SATISFACTION OF COS E TO PROVIDE CERTIFICATION F E COURSE OF CONSTRUCTION, Y THE CONTRACTOR MILL BEF WITH A SUITABLY COMPLIANT V THE CONTRACTOR MILL BEF WITH A SUITABLY COMPLIANT TO USE A RECYCLED PRODUCT THEIR TENDER AND THE PRIOE G OF THE ROAD SURFACE SHAL	YYCLED NULAR BASE L BE E OR ALL AND WHERE ESPONSIBLE WATERIAL AT THE INTENT JIFFERENCE ALL BE		STRE SYNT 4. <u>LEAN MIX</u> 4.1. ALL V 4.2. THE L THNSV STRE 4.3. WAX	ENGTH OF 45 FHETIC MACF K CONCRETE WORKS MUS LMC SUBBAS W QA R82 SP ENGTH AT 28 EMULSION T	883 SPECIFICATION, I MPa IS REQUIRED F(30 FIBRES, 5 E ENALL BE CONSTR 52 SHALL BE CONSTR 52 SHALL BE CONSTR 54 STR 2014 ECONSTR 54 STR 2014 ECONSTR 50 BE ADOPTED FOR BASE SURFACE.	OR THE CC E WITH TfN RUCTED AN IOTED THA'	DNCRETE BASE REINF ISW QA R82. ID TESTED IN ACCOR T A MINIMUM 15 MPa	ORCED WITH DANCE WITH COMPRESSIVE								E 180420241-42:00 PM FILE MANE 522212-AURC-038-FM-DR
ING COLOUR CODED - PRINT AL	L COPIES IN COLOUR														FO	R REVIEW	LOT DATE & TIME
ICES:	THIS DRAWING MAY BE PREPARED IN	COLOUR AND MAY BE I	NCOMPLETE IF CO	OPIED.	SCALE: NOT	TO SCALE	CLIENT:	1	This attaining and the related information have been pro purpose other than the purpose infended by Transport Transport for NSW does not provide any exemption and numous other than the infended number.	repared by, or all the requ r for NSW, rd accepts no liability aris r is notestached by converse	est of, Transport for NSW for a specific purpose and may re- ing cut of the use of this drawing or any of the related inform it and no part of this drawing may be reproduced in any fam	readion for any readion for any relation for any relation for any relation for any	WEST COUNCIL	ASSET PERFORM	ANCE CON	TRACTS	

DRAWING COLOUF

																			, a		
	REFERENCES:		THIS DRA	AWING MAY BE PREPARED IN COLOU	R AND MAY BE INCO	OMPLETE IF C	OPIED.	SCALE: NOT	TO SCALE	CLIENT:		purpose other than the purpose intended by Transport i	br NSW.	request of, Transport for NSW for a specific purpose and way r		INNER WEST COU					
								-				Transport for NSW does not provide any warranties and purpose other than the intended purpose. This drawing writen avernission of Transport for NSW.	accepts no liability is protected by cep	arising out of the use of this drawing or any of the related infor yright and no part of this drawing may be reproduced in any for	rmation for any rm without the express		ADS ASSET PERFOR		ONTRACTS		1
										NSW	Transport						STATION BUS LAYO				1
										N-11	for NSW	aurecon	DRAWN	R_MARTINEZ			VENUE AND RAILWA	AY ROAD			
H			C01.01SSU	UED FOR 100% DETAILED DESIGN		LC 18.04.2024 A	J 18.04.2024 V.T 18.04.20	24				www.aurecongroup.com	DESIGN		13.02.2024	GENERAL NOTES					, н
			B ISSU	UED FOR 80% DETAILED DESIGN		L.C 13.02.2024 A	J 13.02.2024 V.T 13.02.20	24		PREPARED	D FOR:		DRG CH	IECK L.CENETA							
			A ISSU	UED FOR 20% DETAILED DESIGN			J 21.09.2023 V.T 21.09.20	13					DESIGN	CHECK _ P. MCLEAN		DRAWING SET No		PART: SH	ET: 2 OF 4	A1	1
			REV	DESCRIPTION		DESIGNER	ERIFIED APPROVED TIAUDATE INITIAUDATE			CON	NECT		PROJ/D	ES MNGR _J.STEWART	13.02.2024	STATUS: DETAILE	D DESIGN - 100%	BRIDGE No:		C	
			COORDIN	NATE SYSTEM: MGA_ZONE_56/GDA20		HEIGHT DAT	JM:	DESIGN LOT	CODE:		C		APPRO ¹	VEDV.TUET	13.02.2024	DRG No. 520212-AURC-0	38-RW-DRG-000002	REV VER EDN C01.01	S No.	AMD No.	1
	1	2		3	4		5		6		7	8		9		10	11		12		
		-		-	-		-		-	U		-		-							

Attachment 3

А

В

С

D

Н

		WEST
--	--	------

Contract proving constraints steeves are decaded by a number of store is a more store is more store is a more store is more store is more store is a more store is more																		
<form></form>		1	2	3	4	5	6	7	8	9	10	10 11 12						
		STRUCTURAL G	ENERAL NOTES	1			1	1 1	1	EARTHWORKS, F	OUNDATIONS AND	FOOTINGS]				
	A	DRAWINGS AND SP REFER TO ARCHITE DISCREPANCY, PRE 2. CARRY OUT WORK STATUTORY REGUL OCCUPATIONAL HE ACCORDANCE WITH REOUREMENTS. AS	ECIFICATIONS, AND WITH S CTURAL DRAWINGS FOR SI CEDENCE IS GIVEN TO DRA CEDENCE IS GIVEN TO DRA NATIONS, BY-LAWS OR RULE ALTH AND SAFETY OF SITE I ALL CURRENT WORK HEA SOCIATED REGULATIONS A	SUCH OTHER WRITTEN INS: ETTING OUT AND DETAIL D AWINGS, THEN NOTES, THE ORDANCE WITH APPLICABI ES, CONTRACTOR IS RESP PERSONNEL AND GENERA AND CODES OF PRACTICE.	TRUCTIONS ISSUED, IMENSIONS, IN CASE OF IN SPECIFICATION, DNSIBLE FOR AL PUBLIC IN GISLATTVE INDUSTRIAL	29. THESE DRAWINGS E TEMPORARY WORK 30. PROVIDE SCAFFOLE WORK AT HEIGHT. E HAZARDS AND FACI AND EI EVATED EDG	S ARE RESPONSIBILITY OF DING, BARRIERS, FALL RES RECT ACCESS STAIRS AT LITATE ACCESS. MAINTAIN DES	THE CONTRACTOR TRAINT, HAND MID RAILS AN EARLIEST OPPORTUNITY TO SAFETY MESH AND BARRIE	ND TOE BOARDS FOR D REDUCE OPEN SHAFT RS TO ALL OPENINGS	EARTHWORKS TO BE <u>FOUNDATIONS</u> FOUNDATION LEVELS SUPERINTENDENT	S SHOWN ARE CONTRACT L	EVELS. FINAL LEVELS TO E	E AS DIRECTED BY	A				
	В	SUBMIT DETAILS OF APPROVAL BEFORE CONTRACT. CHECK STRUCTURA AND OTHER DRAWI NOMINATION OF PR INDICATES REQUIRI PROPERTIES MAY B TO THE CONTRACT. REQUIREMENTS AN OBTAIN NECESSAR	PROPOSED CHANGES TO PROCEEDING. APPROVAL L DRAWINGS AGAINST AR NGS FOR REQUIREMENTS I OPRIFETARY ITEMS DOES N ED PROPERTIES OF ITEM. S E OFFERED FOR APPROVA INSTALL PROPRIETARY ITE D RECOMMENDATIONS. Y PERMITS AND APPROVAL	SCOPE, WORK METHODS () DOES NOT AUTHORISE A () CHITECTURAL, MECHANICA FOR PENETRATIONS, CONI OT INDICATE EXCLUSIVE P SIMLAR ALTERNATIVES HA L, APPROVAL DOES NOT A EMS IN ACCORDANCE WITH S FROM RELEVANT AUTHO	DR MATERIALS etc FOR (ARIATION TO THE UL, ELECTRICAL SERVICES DUITS, DUCTS, PIPES, etc. REFERENCE BUT WING REQUIRED UTHORISE A VARATION H MANUFACTURER'S WRITES BEFORE	DRAWINGS, PROVID ENSURE NO PART IS SUPPORT FORMVOI APPROVAL, PROVID ADEQUACY OF STRI INCLUDING PROPPIN 32, PROVIDE TEMPORAL STABILIZED BY MASS ERECTION OF THE S DESIGN ASSUMPTIONS	VE SPREADERS AT LOADS / S OVERSTRESSED, DO NOT RK OR PROP FROM STRUC E CALCULATIONS BY SUIT JCTURE FOR PROPOSED C NG, CRANE LIFTS etc. RY BRACING WHERE REQU ONRY, PRECAST CONCRET STRUCTURAL ELEMENT OR	ND/OR LIFTING POINTS WH FLACE OR STORE BUILDIN TURAL MEMBERS WITHOUT BLY QUALIFIED STRUCTUR CONSTRUCTION SEQUENCE, JIRED FOR STRUCTURAL EL E OR OTHER ELEMENTS CC FRAME, AND SHOW ON SHO	IERE REQUIRED. G MATERALS ON, SUPERINTENDENT'S AL ENGINEER TO PROVE METHODS AND LOADS EMENTS OR FRAMES DNSTRUCTED AFTER OP DRAWINGS.	TEST AS-1289-E2.1 O - "CONTROLLED FILL" THICK BY UBRATING WELL COMPACTED II DURING COMPACTO SPECIFICATION - "ROLLED FILL" IS: SA NON-SAND FILL UP T MOIST DURING COM - AVOID OVER EXCAV/ - KEEP EXCAVATIONS NOT AFFECTED BY M	R 80% MINIMUM DENSITY IN S SAND FILL UP TO 800 mm PLATE OR VIBRATING ROLL N LAYERS < 550 mm THICK B' N), OR OTHER MATERIAL PL ND FILL UP TO 600 mm DEEF O 300 mm DEEP COMPACTE PACTION), ATION, BACKFILL OVER EXC, FREE OF WATER, PROVIDE OISSTURE, PREVENT FOUND	IDEX FOR COHESIONLESS DEEP, WELL COMPACTED LER, OR NON-SAND FILL UF Y MECHANIGAL ROLLER (C .ACED AND COMPACTED IN COMPACTED IN LAYERS - D IN LAYERS - 150 mm TH D IN LAYERS - 150 mm TH AVATION WITH GRADE N7 ADEQUATE DRAINAGE TO JATION DRYING QUT DUE T	SOLS. IN LAYERS < 300 mm TO 400 mm DEEP. AY FILL TO BE MOIST ACCORDANCE WITH 300 mm THICK, OR XK (CLAY FILL TO BE SULIDDING CONCRETE, ENSURE FORMATION IS D FXPOSURE FOR FL	В				
	С	WORK ON SITE. 8. GIVE TWO WORKIN STAGES OF WORK. 9. INSPECTIONS AND I CONTRACTOR OF R 10. DO NOT OBTAIN DIN 11. DIMENSIONS ARE IN UNO. 12. HAVE SURVEY AND 13. VEREY ON SITE SE	G DAYS' (48 HOURS) NOTICI REVIEWS UNDERTAKEN BY ESPONSIBILITY FOR COMPI MENSIONS BY SCALING FRC I MILLIMETRES, LEVELS AR SETTING OUT DIMENSIONS AN	E SO THAT INSPECTION MA SUPERINTENDENT OR OTI LIANCE WITH DRAWINGS A MORAWINGS. E IN METRES UNO, CHAINA EN BY A REGISTERED SURV DO EXISTING MEMBER SIZE	AY BE MADE OF CRITICAL HERS DO NOT RELIEVE IND SPECIFICATIONS. IGES ARE IN METRES FEVOR. S SHOWN ON DRAWINGS	TO HAVE A DESIGN' 34. STRUCTURAL WORK PERMANENT DEK LIVE LOADS TO A NON-TRAF CELLING AND SEF IMPOSED 'SURC' COMPACTION LO SOLL DENSITY: ANGLE OF INTER ACTIVE LATERAL	WORKING LIFE OF 100 YEA (HAS BEEN DESIGNED FOI AD LOAD OF STRUCTURE A SINZS1170,1: FICABLE ROOF: RVICES LOAD: HARGE' LOAD ON GROUND JADS: INAL FRICTION: EARTH PRESSURE COEFF	RS, R FOLLOWING LOADS: S SHOWN ON DRAWINGS 0,25 0,5 10 10 12 18 30 10 12 18 30 30 10 10 18 30 30 10 10 10 10 10 10 10 10 10 1	kPa kPa kPa kN/m3 DEGREES FOR ENGINEERED FILL	FROM ADVERSE EFF PROVIDE SHORING EXCAVATIONS WHEF DO NOT UNDERMINE TRENCHES (EVEN IF HORIZONTAL) FROM 11. PROVIDE SAFETY ME EXCAVATIONS DURIN	ECTS OF GROUND WORKS, CERTIFIED BY SUITABLY QU/ RE REQURED, EXISTING FOOTINGS. BY THICKENING BLINDING C BACKFILLED), EXCAVATION FOOTING IS BELOW ADJACI SH AND OTHER PROTECTIO GEOLINDATION CONSTRUCT	PROVIDE TEMPORARY WC ALIFIED STRUCTURAL ENG ONCRETE AS REQUIRED N S, BATTERS etc, SO INFLUE ENT EXCAVATION. IN TO PREVENT EXPOSUR TION	RKS AS REQUIRED, NEER TO ALL DEEP EAR EXISTING SERVICE NCE LINE (AT 30° TO E OF PERSONNEL TO	c				
	D	14. USE STANDARD BO AMBIGUITY. 15. TAKE CARE OF HAZ TAKE PRECAUTION: AND PROTECT EXIS APPROXIMATE LOC. MARK LOCATIONS OF EXCAVATE WITHIN 16. DISPOSE OF SURPH- REGULATIONS. 17. IMPLEMENT SOLLAM AND SEDIMENTATIC	LT PATTERNS etc. THROUGI ARDS ASSOCIATED WITH B S AND WORKMANSHIP UND TING SERVICES AT SITE. SS ATIONS ONLY. SERVICES O DF SERVICES CLEARLY ON J DIS MATERIAL OFF SITE IN J NO WATER MANAGEMENT P NO F SITE. SURROUNDING	HOUT THE WORKS TO AVC JURIED, CONCEALED OR O' LERTAKE EXPLORATION TO ERVICES SHOWN ON DRAV THER THAN THOSE SHOWN SITE, AND ON AS-BUILT DR SERVICES. ACCORDANCE WITH LOCAL PROCEDURES TO AVOID EF AREAS. AND DRAINAGE SY	JID CONFUSION OR VERHEAD SERVICES, ESTABLISH LOCATION OF VINGS ARE IN N MAY EXIST ON SITE. AWINGS, HAND L AUTHORITY WASTE ROSION, CONTAMINATION (STEMS.	BUILDING IMPOR WIND LOADS TO REGION AVERAGE ULTIMATE SERVICEA DIRECTION TERRAIN(DESIGN B, TERRAIN(SHIELDIN(TOPOGRA)	TANCE LEVEL: AS/NZS1170.2: RECURRENCE INTERVAL, REGIONAL WIND SPEED V BILITY REGIONAL WIND SP NAL MULTIPLIER ATEGORY UILDING HEIGHT AS PER BI HEIGHT MULTIPLIER (MS) PHC MIL ITPLIER (MS)	2 R 42 State 500 R (3 sec GUST) 45 FEED V25 (3 sec) 37 10 JIL DING ELEVATION 5 1,0 1,0 1,0 1,0	YEARS M/s m/s	IF CONSTRUCTION M DESIGN LOADS IN GE PRESSURES ON STR CONCRETE STRENG 13. BACKFILL FOR RETA DRAINAGE BEHIND R GRANULAR SURROU DRAINAGE SYSTEM OF WALL. 4. SLOPE SERVICES TR COMPATIBLE WITH N COMPACTED CLAY W	IETHODS IMPOSE COMPACT SIERAL NOTES), BACKFILL E UCTURES, BACKFILL GAIN INING WALLS TO BE FREE D ETAINING WALLS COMPRISI ND, OR NYLEX "COREDRAIN PROVIDE SO MM DIAMETER" RENCHES AWAY FROM BUILL IATURAL MATERIAL ON SITE (THIN 1500 mM OF BUILDING)	ION LOADS GREATER THA EVENLY TO AVOID DIFFERE IST RETAINING WALLS ONL MAIENT SUPPORT INSTALLI RAINING GRANULAR MATE ING CONTINUOUS SLOTTEI I' CONNECTED TO RETICUL WEEPHOLES AT 1500 MAXI DING. BED SERVICES ON C . BACKFILL TOP 300 mm OF G. WHERE SERVICES PASS G. WHERE SERVICES PASS	I ALLOWED (SEE NTAL SOIL CAFTER SPECIFIED D WHERE APPLICABLE. RIAL, PROVIDE D DRAIN WITH ATED STORMWATER WUM CENTRES AT BASE DMPACTED MATERIAL TRENCHES WITH HAND TRENCHES WITH HAND	D				
Construction by the second procession of	E	AUTHORITES ALLS COMMENCEMENT O 19. OBTAIN REQUIREM OR SUPPORT OF ADJOI OF ALL FIXTURES. II 20. HAVE TESTING PER AUTHORITIES JACCI 21. SEPARATE METALS UNCAL VANIZED ST	STANDARDS REFERRED TO F CONTRACT, ENTS FOR SERVICES, ADJO WORK AND PROVIDE FOR NING ELEMENTS DURING C VSERTS, SLEEVES, RECESS FORMED BY AN INDEPENDI REDITED AUTHORITY AND P FROM INCOMPATIBLE MAT FEI AND TREATED TIMBER.	ARE THOSE CURRENT (AS DINING ELEMENTS etc TO BI REQUIRED FIXINGS, PROV JONSTRUCTION, DRAWING; SES OR OPENINGS etc REG ENT NATA (NATIONAL ASSO FROVIDE TEST REPORTS TI TERIALS (eg STAINLESS STI TERIALS (eg STAINLESS STI etc) BY CONCFALED I AYFE	; AMENDED) AT E EMBEDDED IN, FIXED TO IDE FOR TEMPORARY S DO NOT SHOW DETAILS IUIRED. DCIATION OF TESTING O SUPERINTENDENT. ELL, GALVANIZED STEEL, SO CS UITABLE INFRT	EARTHQUAKE LC ANNUAL P ANNUAL P PROBABL HAZARD D SITE SUB- EARTHOW STRUCTUF NUMBERC STRUCTUF 35. LATERAL DEFLECTIC OF POST.	SADS TO AS1170.4; ROBABILITY OF EXCEEDAN ITY FACTOR, (kp) ESIGN FACTOR (2) SOIL CLASS AKE DESIGN CATEGORY (E RE HEIGHT, (hn) DF STOREYS RE DUCTILITY FACTOR (u) ON OF POST UNDER SLS W	1.0 0.08 Ce (T 15 3 2 IND LOAD SHALL BE LIMITED	BC) m D TO 1:125 OF HEIGHT	LAGGING. 15. FOR SITES CLASSIFI BACKFILL TRENCHES SIDE OF FOOTING AG WITH HAND COMPAG STORMWATER AND J 16. FOLLOWING CONST BUILDING TECHNOLC HOMEOWNER'S GUID SLABS AND FOOTINGS	ED M OR GREATER REACTN S WITH HAND COMPACTED O SAINST CLEAN, DRY, UNDIST TED CLAY WITHIN 1500 mm WASTEWATER SERVICES AT RUCTION, FOUNDATION MA GOY FILE 18 "FOUNDATION N DE", INCLUDING CONSTRAIN	VITY; WHERE SERVICES PA CLAY OR BLINDING CONCR UNBED NATURAL MATERU OF BUILDING, PROVIDE FL TEXTERIOR OF BUILDING, NTENANCE TO BE IN ACCO AINTENANCE AND FOOTIN TS ON TREE LOCATIONS.	SS UNDER FOOTINGS ETE FOR 1500 mm EACH IL, BACKFILL TRENCHES EXIBLE JOINTS IN RDANCE WITH CSIRO G PERFORMANCE: A	URC-038-RW-M3D-00001.nt T				
Image: http://www.specifications.edu Example of the system of the sy	F	22. EXTERNAL ELEMEN FINAL WORKS. 23. SUPPLY RELEVANT 24. UNO-UNLESS NOTE STATE. NSL=NATUR 25. SUPERINTENDENT= 26. BUILD, FABRICATE / 27. KEEP ON SITE A CO SPECIFICATIONS) A 28. REFER TO CIVIL AN	TS ARE THOSE EXPOSED T NOTES, DRAWINGS AND SI ED OTHERWISE, SLS=SERVI AL SURFACE LEVEL, FSL=F SUPERINTENDENT NOMINA AND PROCURE ONLY FROM MPLETE SET OF CONTRAC DL SITE INSTRUCTIONS.	TO WEATHER, RAIN AND W PECIFICATIONS etc TO SUB ICEABILITY LIMIT STATE, UI INISHED SURFACE LEVEL. ATED IN CONTRACT. I DRAWINGS 'ISSUED FOR (T DOCUMENTS (INCLUDING	ATER PENETRATION IN -CONTRACTORS. LS=ULTIMATE LIMIT CONSTRUCTION'.	TO BE CONFIRMED O <u>PILES</u> 1. BORED PILES TO BE 2. PILES HAVE BEEN D FRICTION AND 8.4x11 <u>PILING DELIVERABLE</u> 3. SURVEY AS CONSTF OFF LEVELS. AND SI	DNCE THE SOIL PROPERTI IN ACCORDANCE WITH TH ESIGNED ASSUMING 700 kI 0 ⁴ kPa/m MODULUS OF SUE RUCTED PILE POSITIONS, G	ES OF THE BACKFILL IS CON NSW QA SPECIFICATION B55 Pa ALLOWABLE END BEARIN GRADE REACTION OF ROCI SROUND LEVEL AT TIME OF I	IFIRMED. 9. IG AND 70 kPa SKIN K LAYERS. INSTALLATION AND CUT-	CONTROLLED FILL 18. CONSTRUCT FOOTIN REPORT). REMOVE S THESE PRESSURES. SIDES OF EXCAVATIK 19. PROOF ROLL FORMA 20. OBTAIN APPROVAL C QUALIFIED GEOTECH REINFORCEMENT OF 21. SLAB PANEL S TO RE	IGS FOUNDED IN SPECIFIED IOFTENED OR LOOSE MATE ENSURE FORMATION IS CLE DNS NOT STABLE UNO. VITON WITH HEAVY DUTY RC DF FOUNDATION MATERIAL INCAL ENGINEER/SUPERIN RELACING CONCRETE. FOUNDED ON UNDISTURBE	MATERIALS (AS ABOVE, A RIAL AND MATERIAL THAT EAN AND LEVEL. PROVIDE DULER. FOR THE DESIGN PRESSUR TENDENT/BUILDING AUTHO	ND IN GEOTECHNICAL DOES NOT ACHIEVE ORMWORK WHERE ES FROM SUITABLY RITY BEFORE FIXING OWARI E REARING	willodesk Docs//520212 - SRAPC/520212-A				
H C SIDE FRI WAS REFLED COSTON C SIDE FRI WAS REFLED COSTON A SIDE FRI WAS REFLED A SIDE FRI WAS A SID WAS	G	TÍNSW SPECIFICATI TÍNSW SPECIFICATI TÍNSW SPECIFICATI TÍNSW SPECIFICATI	ON B59 BORED CAST- (WITHOUT PEI ON B80 CONCRETE W ON B349 PRECAST CON ON B220 PROTECTIVE	IN-PLACE REINFORCED CC RMANENT CASING) JORKS FOR BRIDGES (FOR NCRETE NOISE WALLS (NO TREATMENT OF BRIDGE ST	BORED PILES) T PRETENSIONED)	FILING.				CONTROLLED FILL, C 22, LOCATE FOOTINGS (23, PROVIDE 0.2 mm HIG TO AS2870 ON 50 mm DAMP PROOF MEMBI BARRIER IN ACCORD PUNCTURING OR DAI 24, TOP OF CONCRETE 3 25, SLOPE GROUND SUIF	20NTROLLED FILL MUST CO CENTRALLY UNDER WALLS / I MARCT RESISTANT VIRG RANES, TAPE AT PENETRAT NANCE WITH MANUFACTURE MAGE BY PLACING A PLAST SLAB TO BE AT LEAST 150 m RROUNDING SUIL DING SO V	NTINUE AT LEAST ONE ME AND COLUMNS UNO. IN POLYETHYLENE FILM DA HOWN ON DRAWINGS, LAP IONS, et: TO ENSURE A CO RS'S RECOMMENDATIONS A IC PLATE UNDER REINFOR IM ABOVE ADJACENT GROI MATER WILL DRAIN AWAY F	RE PAST BUILDING. MP PROOF MEMBRANE 200 mm AND SEAL WPLETE VAPOUR ND AS2870, PREVENT 2EMENT SUPPORTS. IND LEVELS. ROM BUILDING TO 11 UNG ELL TO BF	PLOT DATE & TIME7/04/2024 6:20:17 PM				
1 2 3 4 5 6 7 8 9 10 11 12	н	REFERENCES:	C ISSUE 8 ISSUE A ISSUE REV	D FOR 100% DETAILED DESISN D FOR 80% DETAILED DESISN D FOR 20% DETAILED DESISN D ESCRIPTION	JOH1.04.24 1 JOH3.02.24 [JOQ1.09.23 DESIGNER INTRUGNE	APT1.04.24 VT/11.04.24 OC13.02.24 VT/11.04.24 OPT1.02.23 VT/21.05.23 VERIFED APPROVED INLUANTE INITUALDATE	PREF C	Fared For:	CUITECON DRAV DESI DRG DESI DESI PROJ	MM.COMEDES SNEDJ.OBLEA CHECKS.TYLEB N CHECK_B.REMEDIOS JDES MNGR.J.STEWART	SYDENHAM 	ADS ASSET PERFORM STATION BUS LAYOVE AVENUE AND RAILWAY S- SHEET 1 400 1000 1000 1000	ANCE CONTRACTS R ROAD RT SHEET: 3 OF 41 A1	н				
		1	2	3	4	5	6	7	8	9	10	11	12					

1	2	3	4	5	6	7	8	9	10	11	12
STEEL											<u> </u>
WORKMANSHIP AND N CONSTRUCTION CATE SERVICE CATEGO FABRICATION CAT ASIN337 GRADE G4 ASIN3367 GRAD ASIN3367	EGORY: ECI ATEGORY: CC3 CORDANCE WITH: SOF OR PURLINS AND GRTS SHED BARS. E 250 HOT-ROLLED STEEL F 250 HOT-ROLLED STEEL F 250 HOT-ROLED STEEL F 20 RADE 300 FOR WELDED OR BHP GRADE 300 PLUS F : CHANNELS ANGLES, FLAT DIPOCESSORS OF STRUC- D FROCESSORS OF STRUC- D EYACRS (AUSTRALASIAN EELS), PROVIDE ACRS CERT 21 TAGS AND SUPPORTING I	ACCORDANCE WITH AS ACCORDANCE WITH AS BEAMS AND WELDED CI OR UNIVERSAL BEAMS, S. BARS AND RODS. S. BARS AND RODS. S. BARS AND RODS. EXPIRISION AND AND AND EXPIRISION AND AND AND EXPIRISION AND AND AND EXPIRISION AND AND AND EXPIRISION AND	INZS5131 AS FOLLOWS: OLUMINS, ASINZS3879 UNIVERSAL COLUMINS, D A VALID CERTIFICATE D A VALID CERTIFICATE TO FOR REINFORCING VCE UNFOLLORAL	COMMERCIAL GRADE I STRENGTH STRUCTUR OF BOLTS, NUTS, SCRI WITH AST23, TIGHTE SANUGTIGT, SANUGTIGT, SANUGTIGT, TF FREITON MODE CONNECTIONS TO 24, BOLT TYPE AND TIGHT GRADE/TIGHTENING PI STRENGTH STRUCTUR 25, USE BOLT LENGTHS SX MORE THAN 10 mm. 26, PROVIDE A COLOURE MORE THEO TOROUE HARDENED WASHER U.	BOLTS TO AS1111 AND 1112 ALA BOLTS, NUTS AND WAS EWS AND STUDS TO COMP MING PROCEDURES TO COM JOINT, BOLTS FULL TENS JOINT, BOLTS FULL TENS JOINT, BOLTS FULL TENS ENNO PROCEDURES, REG. ENNOS PROCEDURES, REG. ENNOS PROCEDURES, REG. ENNOS PROCEDURES, REG. ALA BOLTS FULLY TENSION O THAT PROJECTION BEYO LASH AT LOCATIONS OF THE STALL AND AND AND AND AND AND AND AND O ADI INDICATING WASHERS WIRENCHES, PROVIDE WIT INDER BOLT HEAD ON NUT:	ONED, DNED, (CONTACT SURFACE)	ADE 8.8 TO BE HIGH HAINCAL PROPERTIES HERS TO COMPLY S OF FRICTION STRENGTH TINCHIGH HREADS, AND NOT HREADS, AND NOT ART-TURN METHOD DO NOT USE NUT, PROVIDE A				_
MARKS COMPATIBLE U 6. PROVIDE 3 mm CAP PI 7. CARRY OUT ERECTION ERECTION OF BUILDIN 8. PROTECT STEELWOR ERECTION. SUBMIT PF STEELWORK STORES 9. PL UMB COLUMNS WIT	K FROM DAMAGE DURING H ROPOSED METHOD TO REPA ON SITE FROM CORROSION TH METAL PACKERS OR SHIN	H PAINT SYSTEM, ILLOW SECTIONS UNO. IDANCE WITH AS3828 GI ANDLING, TRANSPORT, S IR DAMAGE FOR APPRO I OR DETERIORATION OF IS.	UIDELINES FOR THE STORAGE AND WAL. PROTECT F COATINGS.	BRUSHING OR LIGHT B TO ACHIEVE ASSUMED 28. USE BOLTS, SCREWS, TAP GALVANIZED NUTS PROTECTION. INSTALL USE HARDENED OR PL	D FOR FRICTION TYPE BOL SLASTING TO CLASS 3 (SUR S ULP FACTOR, NUTS AND WASHERS HOT S 0.4 mm OVERSIZE TO SUI WASHERS UNDER BOTH ATE WASHERS UNDER BOT	TS = 0.35, TREAT CONTACT FACE PROFILE 35 TO 65 MIC DIP GALVANIZED BY MANUF I GALVANIZED THREADS TO EAD OR NUT, WHICHEVER F TH HEAD AND NUT FOR OVE HERS AS REQUIRED UNDER	CRONS) AS REQUIRED FACTURER TO AS1214 O AS1214 AND OIL FOR PART IS ROTATED RSIZED AND				-
APPROVAL TO MAKE L STRENGTH BUTT WEL ON SHOP DRAWINGS, GAUGE-LINES TO INTE RESTRAINT DURING J 12. DRILL HOLES FULL SI DRILLED OR SUB-PUN OF HOLES IS NOT PER	I WORKS TO AVOID PINCH E BERS MADE FROM WHOLE L LENGTHS UP OF SECTIONS. DS GROUND FLUSH WHERE ENSURE MEMBERS ARE CC RRSECT) UNO. ACCURATELY OINING. ZE OR REAM TO FULL SIZE A CHED HOLES TO BE AT LEA MITTED. BOLT HOLE SIZE IT O ST LUS 2 mm FOR STEEL TO ST	IOINED BY COMPLETE PI REQUIRED, WHERE PR INCENTRIC AT CONNECT PRE-FORM PARTS TO A FTER SUB-DRILLING OR ST 3 mm UNDERSIZE. "O/ D BE:	ENETRATION FULL OPOSED, SHOW JOINTS IONS (GRAVITY- OR VOID FORCE AND/OR SUB-PLINCHING, SUB	29. SLOTTED HOLES TO BI UNO. USE 8 mm PLATE CONNECTIONS 30. STEEL CONNECTION D INSTITUTE (ASI) STRUC 31. MAKE BOLTED STRUCT BOLTS UNO. USE M12- GIRT CLEATS AND FLY	WASHERS UNDER BOLT HI DETAILS TO BE IN ACCORDA TURAL STEEL CONNECTION TURAL CONNECTIONS WITH 4.6/S BOLTS FOR PURLINS I BRACE CLEATS TO BE 8 mi	IG UNO. BOLTS TO BE SET (FAD AND NUT TO COMPLETI NCE WITH AS4100 AND AUS N SERIES OF MANUALS AND 140 mm THICK CLEAT PLATT JP TO 250 DEEP UNO. STIFF 7 TH/CK UNO, ROD BRACING	ELY COVER HOLE STRALIAN STEEL D GUIDES UNO. ES AND 2 M16 8.8/S ENERS PURI IN AND				-
BOLT DIAMETER PI BOLT DIAMETER PI	LUS 4 mm FOR STEEL TO CC LUS 4 mm FOR HOLDING DO LUS 6 mm FOR HOLDING DO	NCRETE CONNECTIONS		TURNBUCKLES WITH F 32. PROVIDE CLEATS AND SHOW ON SHOP DRAW 33. PROVIDE RADIUSED CI LACERATIONS	ULL CAPACITY OF ROD UN DRILL HOLES NECESSARY VINGS. ORNERS ON EXPOSED CLE	D. FOR FIXING OTHER ELEMEI ATS TO REDUCE RISK OF IN	NTS TO STEELWORK. IPALEMENT AND				
PREQUALIFIED WELD DEVELOP QUALIFICAT AS/NZS1554.1 CLAUSE QUALIFICATION RECO 14. WELDING TO BE UNDI	CEDURES TO SUIT JOINT DE PROCEDURES AND CONSUI TON OF WELD PROCEDURE 4.2. LIST APPLICABLE PARA RD AND MAKE RECORD AV ERTAKEN BY SUITABLY QUA LIFIED WELDING SUPERVIS	MABLES TO AS/NZS1554 AND CONSUMABLES BY METERS ON WELDING F ILABLE FOR INSPECTION LIFIED EXPERIENCED W	1 CLAUSE 4.3 OR TESTING TO PROCEDURE N	35. CROP INTERNAL CORN DRAINAGE HOLES TO F CONSTRUCTION, SHOW	NERS OF CLEATS AND STIF PREVENT WATER PONDING W PROPOSED HOLES ON SI	WELDED CONNECTIONS CA VELDED TOGETHER. "ENERS, etc TO FACILITATE ON STRUCTURAL ELEMENT 40P DRAWINGS. ATION, USE LOCK NUTS FO	DRAINAGE. PROVIDE IS DURING				=
15. CARRY OUT WELDING CONNECTED WITH 6 n • WELDS TO BE SHC • WELDS TO BE CAT • BUTT WELDS TO B • ELECTRODES TO B • TO ASINZS1554, eg	5 TO AS/NZS1554: ALL INTER nm CONTINUOUS FILLET WE P WELDED UNO, EGORY SP, E FULL (COMPLETE) PENETI SE LOW CARBON WITH TENS (CLASSIFICATION B-E49XX	FACES BETWEEN STEEL	THICK WELD LEG UNO.	2. FOR STEEL PROTECTIV <u>DELIVERABLES</u> 3. SUBMIT NAMES AND CO	/ORK TO BE HOT DIPPE GAI VE TREATMENT REFER TO "	VANISED. IMSW SPECIFICATION B220 OSED FABRICATION AND IN:					re fullulu derring vo
 VISUAL EXAMINATI WELDS, RablogRaPHIC of OTHER WELDS SMOOT GRIND ONLID SMOOT GRIND ONLID SMOOT GRIND ONLY IN LONGI 18, REPAR FAULTY WELT THE EXAMINATION. WELDS TO BE INSPEC TO AS2214, PROVIDE 20 WEL DING SYMBOL SA 	ION: 100% OF BUTT WELDS I R ULTRASONIC: 10% OF BUT TH AND FLUSH WITH PAREN ITUDINAL DIRECTION OF ME SAND DEFECTS REVEALED SAND DEFECTS REVEALED TED BY INDEPENDENT NAT. WELDING INSPECTOR'S REF RE TO AS1101.3. "CFW' INDI NGTH BUTT WELD WHICH IS	T WELDS IN TENSION ME T METAL WHERE NOMIN MBER, D BY WELD INSPECTION/ A ACCREDITED QUALIFIE ORT TO SUPERINTENDE CATES CONTINUIOUS FIL	EMBERS AND 5% OF ATED ON DRAWINGS, TESTING AND REPEAT ED WELDING INSPECTOR INT. LET WELD "ESRW"	SUBCONTRACTORS. 4. SUBMT SHOP DRAWIN 5. PROVIDE DOCUMENTA RELEVANT AUSTRALIA EACH BATCH OF FASTI PRODUCT MEETS RELI ALPHANUMERIC CHAR. MANUFACTURER. SUPI WITH PAGE NUMBER C PRODUCT DESIGNATIC LENGTH, BUNDLE, PAG (FROM CASTING), MCC STANDARD): WHETHEF STANDARD: CHEMCAL	IGS AND DESIGN CALCULA' IRY EVIDENCE (INCLUDING IN STANDARDS ISSUED BY ENERS USED, EVIDENCE M EVIDAT AUSTRALIAN STANDA ACTERS, EVIDENCE TO INC ALTER AND TESTING AUTHC ULER AND TESTING AUTHC ING AND RELEXANT DIMENSI IN AND RELEXANT DIMENSI IX OR UNIQUE IDENTIFIER FRO FACH MEASURED MECHA ANALYSIS RESULTS AND 1 MATCH BATCH NUMBER. A	TIONS: REFER GENERAL-DE TEST RESULTS) OF COMPLI MANUFACTURER FOR ALLS JST PROVIDE CLEAR VERHE ARDS AND BE WRITTEN IN LUDE: NAMES AND ADDRES WRITY. TEST CETTIFICATE NE NGS: PRODUCT STEEL MAK O WHICH CERTIFICATE APF M TENSILE TEST (ALL VALU NICAL PROPERTY COMPLIE YPE OF ANALYSIS UNDERT. NY OTHER SYSTEM REFERE	ELIVERABLES NOTES, IANCE WITH TEELWORK AND ICATION THAT ENGLISH UMBER AND DATE ID GRADE OF STELL; ING PROCESS; PLIES; HEAT NUMBER IES CITED IN AS/NZS AKEN; CUSTOMER				1111 - 111
21. M16 AND LARGER BOI M12 SIZE BOLTS SHAL 22. FOR BOLTS MANUFAC ACCREDITED LABORA VERIFICATION.	LTS TO BE HIGH STRENGTH L BE COMMERCIAL BOLTS, - TURED OUTSIDE AUSTRALL TORY COMPLIANCE CERTIF	4.6/S PROCEDURE UNO A, PROVIDE LOCAL INDE ICATE BASED ON APPRO	PENDENT NATA								
DRAWING COLOUR CC	C ISSUED		LOUR AND MAY BE INCOMPLETE JOINTA424	F COPIED. SCALE: NC	GOVI	SW Transport for NSW	aurecon	DESIGNEDJ_QBLEA	SYDENH 13.02.24 BURROV 13.02.24 STRUCTUR	Y ROADS ASSET PERFORM HAM STATION BUS LAYOVE WS AVENUE AND RAILWAY	R
		FOR 80% DETAILED DESIGN FOR 20% DETAILED DESIGN DESCRIPTION		DC/13.02.24 VT/13.02.24 MP/21.09.23 VT/21.09.23 VERIFIED APPROVED		PARED FOR:		DRG CHECKS.TYLER DESIGN CHECK _ B.REMEDIOS	13.02.24 GENERAL N 13.02.24 DRAWING S	NOTES - SHEET 2	RT SHEET: 4 OF 41 A1

ER WEST

Attachment 3

	1	2		3		4	5	6		7	8	9	10	11	12			
	CONCRETE CONCRETE MIX			1	I		CONCRETE TESTING				1	REINFORCEME	WINGS FOR GRADE AND T	PE OF REINFORCEMENT AF	E AS FOLLOWS:			
A	1. WORKMANSHIP AND AS3582, AS3799, AS SPECIFICATIONS B8 3. WET CONCRETE TO CORNERS AND ARO SEGREGATION, EXC	2758.1, AS5100 FOR BORED PI 0. BE UNIFORM, I UND REINFORM ESS FREE WA	5 AND AS39 ILES SPECIF HOMOGENE CEMENT CO TER ON SUF	FICATION SHALL COM OUS, COHESIVE AND MPLETELY FILLING FI RFACE, LOSS OF MATI	PLY WITH THNSW ABLE TO WORK ORMWORK WITH ERIAL OR CONTA	READILY INTO DUT MINATION.	21. TEST SLUMP OF EA THAT DELIVERY. SL TOLERANCES GIVEI LIABLE TO REJECTI 22. REGISTER PROJEC INFORMATION. MAN COMPLIANCE WITH	FFOR DISSEMINATION OF UFACTURER TO CARRY OF REQUIREMENTS OF AS137	GREATER THA CONCRETE OL CONCRETE PR JT PRODUCTIO 9.	AN TARGET S UTSIDE SLUMI RODUCTION A DN ASSESSME	LUMP WITHIN P TOLERANCE LIMITS IS SSESSMENT ENT OF CONCRETE FOR	 R: STRUCTURAL GRADE 250 PLAIN ROUND BAR TO ASINZ54671 N: HOT ROLLED GRADE 500 DEFORMED (RBBED) BAR DUCTLITY CLASS N TO ASINZ54671 L: HOT ROLLED GRADE 500 DEFORMED BAR DUCTLITY CLASS L TO ASINZ54671 SL: HARD DRAWN WIRE GRADE 500 SQUARE MESH DUCTLITY CLASS L TO ASINZ54671 RL: HARD DRAWN WIRE GRADE 500 RECTANGULAR MESH DUCTLITY CLASS L TO ASINZ54671 RL: HARD DRAWN WIRE GRADE 500 TECHNCH MESH DUCTLITY CLASS L TO ASINZ54671 TM: HARD DRAWN STEEL GRADE 500 TENCH MESH DUCTLITY CLASS L TO ASINZ54671 TM: HARD DRAWN STEEL GRADE 500 TENCH MESH DUCTLITY CLASS L TO ASINZ54671 						
в	 CRACKING, THERM FINISHED CONCRET FORMWORK, EMBEL HONEYCOMBS, OF L BUT NOT EXCESSIV CONCRETE BLEED 1 WALLS. AIR ENTRAINMENT I REVIEW LOCATION. THAT MAY COMPRO 	L CRACKING A TO BE A DUR DDING REINFOI JNIFORM COLC E STRENGTH F TO BE LESS TH OF EMBEDDED MISE STRUCTL SED CONCRETT	IND SHRINK REABLE, DENS RCEMENT AI OUR AND TE: OUR AND TE: OUR AND TE: AN 3% FOR TED UNLESS ITEMS TO N ITAL INTEGI E TO BE CLA	SE, HOMOGENEOUS N ND TENDONS, AND FI XTURE, WITH LOW PE FLOOR AND ROOF SL S APPROVED IN WRIT MINIMIZE POSSIBLE 20 RITY SSIFICATION B1 UNC	MASS COMPLETE REE OF STONE P RMEABILITY AND ABS, LESS THAN ING BY SUPERIN DNES OF POOR C	Y FILLING OCKETS OR ADEQUATE 2% FOR TENDENT	EVENLY THROUGH I EACH SAMPLE TAKE DESIGN MIX TARE O DAY, NOT LESS THA FOUR CYLINDERS: 2 WORKING DAYS IF TO BE BELOW SPEC 24, FOR TYPE LH CEME TWO AT 28 DAS ANI 25, CARRY OUT DRYING ONE SAMPLE EVER	NT EACH SAMPLE TO COM O ONE AT 56 DAYS. SHRINKAGE TESTING TO Y THREE MONTHS, OR FOR	EFOR PROJEC: ESSMENT AT PI 5 CUBIC METRI DR EACH MIX D TWO AT 28 DA' ESULTS INDIC, IPRISE FOUR C AS1012.13, FOI E EVERY 1000 m	T ASSESSMEI ROJECT SITE LES OF CONCF DESIGN. EACH YS. NOTIFY SI CATE 28 DAY SI CYLINDERS: TH OR EACH CONC m3 OF CONCR	NT CONCURRENTLY WITH FOR EACH CONCRETE RETE DELIVERED PER ISAMPLE TO COMPRISE UPERINTENDENT WITHIN TRENGTHS ARE LIKELY EST ONE AT 7 DAYS AND CRETE DESIGN MIX TAKE ETE PLACED, A MINIMUM	CERTIFICATION OF DOCUMENTATION AS/NZS4672.1 FOR WITH AS/NZS4671. 4. REINFORCEMENT 5. DO NOT USE LOW 6. USE MESH SUPPLI 7. REINFORCEMENT MATERIAL THAT M	F COMPLIANCE WITH ASINZ FOR ALL REINFORCEMENT ALL PRESTRESSING TEND INTATION TO SHOW THAT F MUST HAVE UNIQUE MARK. DUCTILITY REINFORCEMEN ED IN FLAT SHEETS UNLES TO BE CLEAN, FREE OF LO GHT REPLUCE ROND BETW	EINFORCEMENT SUPPLIER S TO IDENTIFY SUPPLIER IT (GRADE L) UNO. S APPROVED OTHERWISE. DSE MILL SCALE, RUST, OIL, FEN REINFORCEMENT AND	SUPPORTING F COMPLIANCE WITH AND MILL COMPLIES B GREASE, MUD OR OTHER CONCRETE	В		
	STRUCTURAL E	LEMENT E		MENITIES BULDING RAFT SLAB	NOISE BORE WALL PILE	P	OF ONE SAMPLE, E/ PROJECT SITE, DIRI	ACH SAMPLE TO COMPRIS				 SUBMIT PROPOSA EXPOSED CUT ENI 	L FOR CUTTING OR DISPLA DS OF REINFORCEMENT US	CING REINFORCEMENT. CLE ING 6 mm APPROVED EPOX AS SHOWN: eg. 17 N20 - 350	AN AND PROTECT	_		
	EXPOSURE CLASS	FICATION -	P		B1 B1	<u>}</u>	26. CONCRETE SAMPLI	NG AND TESTING TO BE B				 17⁺ DENOTE 	S NO OF BARS AND TYPE IN	GROUP	F			
	STRENGTH GRADE		-	32	S32 S32	-	LABORATORY.					 N: DENOTE 20: DENOTE 350: DENOTE 	S BAR GRADE AND DUCTIL S NOMINAL BAR DIAMETER	TY CLASS IN mm		_		
С	MINIMUM DENSITY	(350	2350	-	REINFORCEMENT COV					 350: DENOTE EF: DENOTE 	S SPACING IN mm S LOCATION		C	3		
	MAX AGGREGATE		2	0	20 8		etc) AND OUTS DE S	STANCE BETWEEN ANY RI URFACE OF STRUCTURAL	CONCRETE.			10. TO MINIMIZE TRIP TRAFFICABLE ARE	HAZARDS CONSIDER MAXI AS PRIOR TO CASTING CO	MUM REINFORCEMENT BAR NCRETE OF 200 mm. ALTERN NG IS GREATER THAN 200 m	SPACING FOR ATIVELY PROVIDE SL82			
	MAXIMUM / PEAK IN	ISITU	. 6	:5°C	65°C		28. COVER MUST NOT E REINFORCEMENT A	BE LESS THAN SPECIFIED. S SHOWN BELOW, EXCEP	PROVIDE MINI WHERE SPEC	MUM CLEAR C	OVER TO WISE.	ADDITIONAL IF MA 11. FOLLOWING ABBR	EVIATIONS APPLY TO LOC/	TION OF REINFORCEMENT:				
	CONCRETE TEMPE			€P	65°C OLLAND			LOCATION		COVE	R (mm)	EW: EACH W. EF: EACH FA	CE B: BOTT	DM TT: TOP TO	I BOTTOM (LAID FIRST)			
	MINIMUM CEMENTI	TIQUE		70	270		BORED PILES			8	30	NF: NEAR FA 12. PROVIDE STANDA		SOR CP: CENTRA S3600. TERMINATE ENDS OF REES. PROVIDE FIRST LIGAT	LLY PLACED COLUMN AND BEAM			
D	CONTENT (kg/m ^a)			.5	0.5 IS MSNJ		FOOTINGS, UNDER AGAINSTGROUND	SIDE SLABS ON GROUND, ON MEMBRANE	etc CAST	:	30	FACE OF SUPPOR 13 COG HALE OF SLA	T. B BOTTOM REINFORCEMEN	IT AT EDGES TO ACHIEVE A		п		
	WATER/CEMENTIT						TOP OF SLAB - INT	ERIOR		:	20	14. PROVIDE ONE COI CONSTRUCTION J	NTINUOUS BAR PARALLEL " DINTS UNO.	O (WITHIN 75 mm OF) CONC	RETE EDGES, INCLUDING	-		
	SHRINKAGE (MICR	OSTRAIN)	6	50	650		NOISE WALL		520		ER TO 88-ST-DRG-008002	AT RE-ENTRANT C	ORNERS OPENINGS SERV	000 mm LONG AT EACH LAY				
\square	9. SUPPLEMENTARY C GROUND GRANULA 10. RHEOLOGY, WORK/ CHUITE atta), COMPA	EMENTITIOUS I FED BLAST FUF ABILITY AND SL	MATERIALS RNACE SLAG	INCLUDE AMORPHOU GGBFS OR SLAG) C AS REQUIRED FOR P SUPERPLASTICISEF	IS SILICA FUME, I OMPLYING WITH LACEMENT (eg PI	LY ASH, AND AS3582 JMPING,	ELSEWHERE 29. PROVIDE 50 mm BLI GROUND UNO.	NDING CONCRETE UNDER	STRUCTURAL		50 D CONCRETE CAST ON	PROJECTION, SET	REINFORCEMENT OUT AT	D 500 WHERE NONE SHOW IMATICALLY AND IS NOT NE EQUAL CENTRES IF SPACING MENT TO REDUCE RISK OF	IS NOT NOMINATED.	\supset		
E	CHOLE BLO, COMPAN REDUCERS TO AS14 11. MAXIMUM SULPHAT SO3 AS A PERCENT, 12. TOTAL REACTIVE AI (EQUIVALENT), 13. USE CEMENTITIOUS OF RECEIPT. 14. FOR GENERAL BLEN LEAST 5% SUPPLEN	178 TO ACHIEVE E CONTENT OF AGE OF CEMEN KALI CONTENT MATERIALS LE	E ADEQUATI CONCRETE ITITIOUS MA I IN CONCRI ESS THAN SI (GB) CONTA	E WORKABILITY E TO BE LESS THAN 5 ITERIAL ETE TO BE LESS THAI IX MONTHS OLD. USE INING ORDINARY PO	% BY MASS OF A N 2.8 kg/m3 Na2O BAGGED CEMEN	TID SOLUBLE	30. TOLERANCE ON CO DURABILITY AND PROT 31. APPLY ANTI-GRAFFI MANUFACTURER'S I PRIMER CONFORM	VER IS +10mm, -5 mm UNO ECTIVE COATINGS TI COATING TO ALL EXPO: REQUIREMENTS, SYSTEM NG WITH AS/NZS3750.9 AN MANUFACTURER. COLOUF	SED CONCRET PSL1 OF AS/NZ D RECOMMENT	2S2312 TABLE DED FOR APP	6.3 USING AN EPOXY LICATION OVER	19. ENSURE ALL LAID BARS ROLLING UN 20. REINFORCEMENT CAGES TO BE PRE 21. SECURE REINFOR CLEAR CONCRETE SPACERS, LIGATU ADEQUATE SUPPC	IDERFOOT TO BE SUPPLIED TO SITE F -FABRICATED OFF-SITE AS CEMENT IN POSITION AGAI : COVER TO REINFORCEME RES OR TIES AT 800 mm M2	NST DISPLACEMENT AND M/ NT (INCLUDING FITMENTS) E XIMUM CENTRES EACH WA' MENT OF REINFORCEMENT	PES. REINFORCEMENT	E		
	SILICA FUME TO FLYASH TO BE LI GROUND GRANU CEMENT TOTAL 5	BE LESS THAN ESS THAN 25% ILATED BLAST I SUPPLEMENTA	10%, OR , OR FURNACE S RY CEMENT	LAG TO BE LESS THA TTIOUS MATERIAL MU TUENTS INCLUDED, F	ST BE LESS THA	N SMALLER OF						22. SECURELY THE RE CLEAR OF COVER 23. THE BUNDLED BAR	NFORCEMENT WITH WIRE ZONE. S TOGETHER SO THEY ARE	TIES. TURN ENDS OF TIE WI IN CLOSEST POSSIBLE CON TIMES DIAMETER OF SMALLI CORNER OF EACH STIRRUF IAXIMUM CENTRES.	TACT WITH 2.5 mm			
F	TOTAL SUPPLEM 15. TEST FINE AND COA USING CSIRO ACCE ALTERNATIVELY US PROVIDE ADDITION TYPE AS PROPOSEI 16. ADMIXTURES TO CC	IENTARY CEME IRSE AGGREGA LERATED MOR E ASTM C1293 AL AGGREGATE D IN THE WORK DMPLY WITH AS	NTITIOUS M ATES FOR P TAR BAR TE CONCRETE E AAR RISK I S 1478, ADMI)	IATERIAL MUST BE LE OTENTIAL AGGREGA ST (REFER SAA HANI PRISM TEST, PETROO INFORMATION, TESTS	SS THAN 40%. FE ALKALI REACT DBOOK HB-69 APF GRAPHIC TESTING MUST USE SAM EDUCE STRENGT	IVITY (AAR) ENDIX B3.2). G CAN E CEMENT H OF						LONGTUDINAL BA	RS TO STIRRUPS AT 1000 N	AXIMUM CENTRES.	ARE - 12 CAREFORM	F		
G	ADMIXTURES IN ACC ADMIXTURES SHALL CONCRETE OR STEL ADMIXTURES OR OT 17. MAXIMUM ACID SOL STRONGLY IONIZED 18. DO NOT ADD WATE 19. MIX CONCRETE TO I	CORDANCE WIT NOT ENHANCI EL DURING EXF HER MATERIAL UBLE CHLORID SALTS R TO CONCRET ENSURE UNIFC	TH MANUFAU E CORROSIO PECTED LIFE S WITHOUT DE ION CONT E AFTER TR DRM DISTRIE	CTURER'S RECOMME DN OF REINFORCEME OF STRUCTURE, DC I SUPERINTENDENT'S FENT IS 0.4 kg/m3 OF 4 RUCK HAS LEFT BATC 3UTION OF CONSTITU	NDATIONS, CONC NT, NOR BE DET NOT USE CHEMI WRITTEN APPR CONCRETE, DO N HING PLANT ENTS	RETE RIMENTAL TO CAL OVAL OT USE									NEO42254 620-17 FM	 G		
	20. SPRAYED CONCRET SPECIFICATION (RE	FER APPENDIX	A OF "RECO	DMMENDED PRACTIC	SPRAYED CON	EKENGE RETE").									FOR REVIEW			
								T TO SCALE CLI	-NT.	17	his drawing and the related information have been presared	by, or at the measest of. Transport for NSW for a specific purpose	and may not be used for INNER WEST CC	- NOL				
н	REFERENCES:		C ISSUE B ISSUE	WING MAY BE PREPARED		J0/11.04.24 1 J0/13.02.24 1 J0/21.09.23 1	NP/11.04.24 VT/11.04.24 VT/13.02.24 VT/13.02.24 VP/21.09.23 VT/21.09.23	N COVI	🥼 Tra	nsport NSW	Targaset for XBW does not provide any semantials and across pages either than the intended puppers. The datasety is prof arrange within permission of Transport for XBW.	by or at the mapsed of. Transport for ADSI for a guide purpose services and submitted of the said of the said of the same of a way of the m she that by subspirit of the said state guide and the off the subspirit of the said state guide and the same of the s	SYDNEY RO SYDNEY RO SYDENHAN	DADS ASSET PERFORMA I STATION BUS LAYOVER AVENUE AND RAILWAY I S- SHEET 3	2	Н		
				DESCRIF			VERIFIED APPROVED VITIALDATE INITIALDATE UM: AHD DESIGN LOT		ONNECT	SYDNEY	PRC	J/DES MNGR. J. STEWART	13.02.24 STATUS: DETAIL	ED DESIGN - 100% BRI	GE NO: © VER EDMS No. AMD No.			
	1	2		ATE SYSTEM: MGA_ZONE	.00 💋 GD	42020 HEIGHT DAT	UM: AHD DESIGN LOT	6		7	8	9		138-ST-DRG-000005 C	12			
	1	2				-	5		U	1	U U	, in the second s	10	"	12			

10

3 June 2024

А

В

С

D

8 F

≣F

ş 0:20:18 104/2024 TE & TIME7

12

	2
=	ltem

1 2 3 4 CONTINUATION FOR EIENFORCEMENT 34, 000, 000, 000, 000, 000, 000, 000, 0										
A 52. FOR EXTERNAL DR CORRECANE, APPLICATIONS USE HOT DP CALLWARED TE MHES A 25. FOR EXTERNAL DR CORRECTION TO AND TRAFFIC LOADS AND MAINTAIN DURABILITY OF ADEQUATE TO WITHSTAND CONSTRUCTION AND TRAFFIC LOADS AND MAINTAIN DURABILITY OF FINASED CONCRETE STRUCTURE, FOR CONCRETE SURFACES WITH BE EXPOSURE CLASSIFICATION OR GREATER, ONLY USE PROPRIETARY HIGH STRENCTH FIBRE REINFORCED 20. OWNED PLACE DURING TO REPORT OF CONCRETE SURFACES WITH STRENCTH FIBRE REINFORCED 20. OWNED PLACE DURING INSERTS, THEADED SOCKETS, FERRULES, BOLTS, DISSIMLAR METALS, AND DEVICE DURING INSERTS, THEADED SOCKETS, FERRULES, BOLTS, DISSIMLAR METALS, AND DEVICE DURING INSERTS, THEADED SOCKETS, FERRULES, BOLTS, DISSIMLAR METALS, AND DEVICE DURING INSERTS, THEADED SOCKETS, FERRULES, BOLTS, DISSIMLAR METALS, AND DEVICE DURING INSERTS, THEADED SOCKETS, FERRULES, BOLTS, DISSIMLAR METALS, AND DEVICE DERING INSERTS, THEADED SOCKETS, FERRULES, BOLTS, DISSIMLAR METALS, AND DEVICE DERING INSERTS, THEADED SOCKETS, THE TEMS EMBEDDED IN COVER CONCRETE. B 30. DO NOT WELD REINFORCEMENT, CASTIN ITEMS EN UNITS APPROVED UNO. 31. SPLEE REINFORCEMENT, CASTIN ITEMS EN UNITS APPROVED UNO. 32. LAPED SPLICE LEART SPACING DETAIL STARK WITH MORE THAN SOME THE SAR DUMMETER, WHERE BAR SIZES VARY USE LAPPED BARETO DE LISS THAN THE DEST APPROVED UNIT AND THE THEME EXAMINES DURING THE CONCRETE AND SPACED LAT 2150 mm CENTRES TO COMPLY WITH THE FOLLOWING UNO. 20. LAPPED SPLICE LEART SPACING DETAIL STARK WITH MORE THAN SOME THE SAR DUMMETER, WHERE BAR SIZES VARY USE LAPPED SPLICE LEARTHS. 20. LAPPED SPLICE LEART SPLICE LEARTHS. 20. LAPPED SPLICE LEART SPLICE LEARTHS. 20. LAPPED SPLICE LEART SIZES OF SPLICE LEARTHS.		1			2		3			4
28. SUPPORT REINFORCEMENT ON PROPRIETARY CONCRETE. MITAL OR PLASTIC SUPPORTS A ADJUATE TO WITATAND CONSTRUCTION AND TRAFTIC LOADS AND MARTAN DUBRALITY OF PINISHED CONCRETE STRUCTURE, FOR CONCRETE SUFFACES WITH B2 EXPOSUME CONCRET SPACER BUNCHEDRES (INCERTS, THERADED SOCKETS, FERRULES, BOLTS, DISSIMILAR METAL TENS, BIO, NO CONCRETE OR EXPOSED TO AR ARE NOT IN CONTACT WITH METAL TENS, BIO, NO CONCRETE OR EXPOSED TO AR ARE NOT IN CONTACT WITH METAL TENS, BIO, NO CONCRETE OR EXPOSED TO AR ARE NOT IN CONTACT WITH METAL TENS, BIO, NO CONCRETE OR EXPOSED TO AR ARE NOT IN CONTACT WITH METAL TENS, BIO, NO CONCRETE OR EXPOSED TO AR ARE NOT IN CONTACT WITH METAL TENS, BIO, NO CONCRETE OR EXPOSED TO AR ARE NOT IN CONTACT WITH METAL TENS, BIO, NO CONCRETE OR EXPOSED TO AR ARE NOT IN CONTACT WITH METAL TENS, BIO, NO CONCRETE OR EXPOSED TO AND EXPOSED THEMS. 30. DD NOT WELD REINFORCEMENT, CASTIN TESMA SENDAL RAME RATION CONTACT WITH METAL TENS, BIO, NO CONCRETE OR EXPOSED TO AND EXPOSED THEMS. 31. DD NOT WELD REINFORCEMENT, CASTIN TESMA SENDATION DAVING SO RA APPROVED BW 33. DD NOT WELD REINFRIT ONLY AT LOCATIONS SHOWN ON DRAWINGS OR AS APPROVED BW 34. DEPENDENT CONCRETE STRUCTURE, LAPPED DEPLOTE LENGTH FOR CONCRETE CAST DEMETER, WHERE BAR RIZES XARY WHERE POSSIBLE, LAPPED DEPLOTE LENGTH SO CONCRETE CAST BELODY THE BWARAND SPACED AT 2150 mm CENTRES TO CONCRETE CAST BELODY THE BWARAND SPACED AT 2150 mm CENTRES TO CONCRETE WILL BEOLOW THE BWARAND SPACED AT 2150 mm CENTRES TO ASSUME ON SUPERINTENDENT. LAPPED SPLICE LENGTHS ROR BRAIN NO COUNTS. DD NOT INTERPOLATE INTERMEDIATE VALUES OF SPLICE LENGTRS TO CONCRETE WILL BEOLOW THE BWARAND SPACED AT 2150 mm CENTRES TO COMPLY WITH THE FOLLOWING UNCO. DD NOT TITERPOLATE INTERMEDIATE VALUES OF SPLICE LENGTRS. LAPPED SPLICE LENGTHS ROR BRAIN NO COUNTS IN THE ON CONCRETE W			ON FOR RE	INFORCEN	<u>IENT</u>					
REINFORCEMENT AND EXPOSED ITEMS. 20. DETAM SUPERINTENDENTS APPROVAL OF INSERTS, FMANGS AND OTHER ITEMS EMBEDDED IN COVER CONCRETE. 31. SPUICE REINFORCEMENT CONTINUESS AS UNDERS AND AVAINASS OR AS APPROVED BY SUPERINTENDENT. STAGGER LAPS WHERE POSSIBLE. LAPPED SPUICE LENGTHS TO COMPLY SUPERINTENDENT. STAGGER LAPS WHERE POSSIBLE. LAPPED SPUICE LENGTHS TO COMPLY SUPERINTENDENT. STAGGER LAPS WHERE POSSIBLE. LAPPED SPUICE LENGTH FOR SMALLER BAR DUMMETER. 32. LAPPED SPUICE LENGTHS FOR ANDR/2004 LENGTHS TO COMPLY WITH THE FOLLOWING UND. Image: Stage Stag	A	26. SUPPORT ADEQUAT FINISHED CLASSIFIC CEMENT S 27. DO NOT P 28. ENSURE E METAL ITE	REINFORG E TO WITH CONCRET CATION OR PACER BL LACE OR M MBEDDEE	CEMENT OF STAND CO E STRUCTI GREATER OCKS OR MOVE REIN TEMS (IN COVER C	N PROPRI INSTRUCT URE, FOR , ONLY US SUPPORT IFORCEME SERTS, TH ONCRETE	ETARY CON ION AND TH CONCRETE SE PROPRIE S. ENT DURING HREADED S OR EXPOS	NCRETE, M RAFFIC LO E SURFACE ETARY HIG G OR AFTE GOCKETS, I GED TO AIR	ETAL OR F ADS AND I ES WITH B H STRENG R CONCRE FERRULES	PLASTIC S WAINTAIN 2 EXPOSU TH FIBRE ETE PLACI 3, BOLTS, I IN CONTA	UPPORTS DURABILITY OF RE REINFORCED EMENT. DISSIMILAR CT WITH
C ²²⁵ 220 770 1150 1570 ¹⁵⁰ 150 C ²⁴⁰ 225 630 980 1380 1740 ¹⁵⁰ 150 150 150 150 DO NOTINTERPOLATE INTERMEDIATE VALUES OF SPLICE LENGTHS. ²⁴⁰ 232 510 770 1100 1440 1810 2220 250 240 460 633 980 1200 1530 1890 ²⁵⁰ 150 150 ²⁵⁰ 150 DO NOTINTERPOLATE INTERMEDIATE VALUES OF SPLICE LENGTHS. ²⁵⁰ 150 150 ²⁵⁰ 150 32. LAPPED SPLICE LENGTHS FOR BARS IN COLUMNS REFER TO DETAILS OR SUPERINTENDENT. ²⁵⁰ 150 ²⁵⁰ 150 33. LAPPED SPLICE LENGTHS FOR VERTICAL BARS (AND HORIZONTAL BARS WITH LESS THAN 300 mm ²⁵⁰ COMPLY WITH THE ²⁵⁰ 150 ¹⁵⁰ 150 200 225 420 590 ¹⁵⁰ 150 240 225 490 750 ¹⁵⁰ 140 ¹⁵¹ 140 250 240 350 ¹⁵⁰ 1100 260 232 400 150 ¹⁵⁰ 1100 270	В	REINFORC 29. OBTAIN SI COVER CC 30. DO NOT W 31. SPLICE RI SUPERINT WITH AS3 DIAMETER 32. LAPPED S	CEMENT AI UPERINTE DNCRETE VELD REIN EINFORCE ENDENT 600. CLEAI WHERE PLICE LEN	ND EXPOSE NDENT'S A FORCEMEN MENT ONL' STAGGER I R SPACING BAR SIZES IGTHS FOR	ED ITEMS. PPROVAL NT, CAST-I Y AT LOCA LAPS WHE BETWEEI VARY USI HORIZON	OF INSERT IN ITEMS et ATIONS SHO RE POSSIE N LAPPED I E LAPPED S ITAL BARS	S, FIXINGS CUNLESS OWN ON D BLE, LAPPE BARS TO B SPLICE LEE WITH MOF	S AND OTH APPROVE RAWINGS ED SPLICE E LESS TH NGTH FOR RE THAN 30	IER ITEMS D UNO. OR AS AP LENGTHS IAN THREI SMALLER 20 mm COI	EMBEDDED IN PROVED BY TO COMPLY E TIMES BAR BAR DIAMETER. NCRETE CAST
C ²⁴⁰ ²²⁵ ⁶³⁰ ⁹⁸⁰ ¹³⁵⁰ ¹⁷⁴⁰ ¹⁷⁴⁰ ¹ ¹⁴⁰ ¹³⁵⁰ ¹⁷⁴⁰ ¹⁴⁰ ¹³⁵⁰ ¹³⁶⁰ ¹³⁴⁰ ¹⁵¹ ¹⁵¹ ¹³⁵⁰ ¹¹¹⁰ ¹⁴¹⁰ ¹¹¹⁰ ¹¹¹⁰⁰ ¹¹¹⁰⁰ ¹¹¹⁰⁰ ¹		1					N24	N28	N32	_
C 240 232 510 770 1100 1440 1810 2220 250 240 460 630 890 1200 1530 1890 Do NOT INTERPOLATE INTERMEDIATE VALUES OF SPLICE LENGTHS. LAPPED SPLICE LENGTHS FOR BARS IN COLUMNS REFERT NO DETAILS OR SUPERINTENDENT. 33. LAPPED SPLICE LENGTHS FOR VERTICAL BARS (AND HORIZONTAL BARS WITH LESS THAN 300 mm CONCRETE CAST BELOW THE BAR) AND SPACED AT ≥150 mm CENTRES TO COMPLY WITH THE FOLLOWING UNO D COVER fc N12 N16 N22 N32 225 220 590 890 1210 - - 240 225 490 750 1040 1340 - 240 232 390 600 840 1110 1400 1710 250 240 350 480 690 920 1180 1450 NOT APPLICABLE FOR BARS IN COLUMNS. DO NOT INTERPOLATE INTERNEDIATE VALUES OF SPLICE LENGTHS. LAPPED SPLICE LENGTHS FOR BARS IN COLUMNS. SUPERINTENDENT. 35. ENSURE REINFORCEMENT SOLDEL SOLUMASS. SUPERINTENDENT. 40 232 350 480 6			-			-				-
ES0 240 460 630 990 1200 1530 1990 DO NOT INTERPOLATE INTERPOLATE VALUES OF SPLICE LENGTHS, LAPPED SPLICE LENGTHS FOR PARSI IN COLUMNS REFER TO DETAILS OR SUPERINTENDENT. EPOXY COATED BARSS BARS IN LICHTWEIGHT CONCRETE AND SUP FORMED CONCRETE WILL REQUIRE LONGER SPLICE LENGTHS, REFER TO ASSA00 OR SUPERINTENDENT. 33. LAPPED SPLICE LENGTHS FOR VERTICAL BARS (AND HORZONTAL BARS WITH LESS THAN 300 mm CONCRETE CAST BELOW THE BAR) AND SPACED AT 2150 mm CENTRES TO COMPLY WITH THE FOLLOWING UNO. D 225 220 590 890 1210 - - 240 225 490 750 1040 1340 - - 250 240 350 480 980 920 1180 1450 NOT APPLICABLE FOR BARS IN COLUMNS. DO NOT INTERPOLATE INTERPOLATE WITERPOLATE WITERPOLET AND SUP FORMED CONCRETE WILL REQUIRE LONGER SPLICE LENGTHS, REFER TO DESIDE OR MECHANICAL SPLICES, 35. ENSURE REINFORCEMENT COUPLERS BROUDE FULL TENSION CAPACITY OF REMORCEMENT, 35. LAPPED SPLICE LENGTHS FOR BARS IN COLUMNS. 0 30. CHINOROCEMENT SPLICE SUP THAN ONT MIMIL COVER IN EAUS ON SUPERINTENDENT. 33. ENENFORCEMENT SPLICE SUP TO THAS TOMAINM COVER IN CHAILS ON SUPERINTENDENT. 34. REINFORCEMENT SPLICE BARS TO HAR MIMIL COVER INT ENDELLS ON WOUTERMOST WIREDOCHARCELS SUPEROVERAPROVIDE FULL TENSION CAPACITY O	~							1810	2220	-
LAPPED SPLICE LENGTHS FOR BARS IN COLUMNS REFER TO DETAILS OR SUPERINTENDENT. 33. LAPPED SPLICE LENGTHS FOR WERTCAL BARS (AND FONZONTAL BARS WITH LESS THAN 300 mm CONCRETE VALLE LENGTHS FOR VERTICAL BARS (AND FONZONTAL BARS WITH LESS THAN 300 mm CONCRETE CAST BELOW THE BAR) AND SPACED AT 2150 mm CENTRES TO COMPLY WITH THE FOLLOWING UNO. D	C	≥50	≥40	460	630	890	1200	1530	1890]
D 225 220 590 890 1210 . . 240 225 490 750 1040 1340 . . 240 225 490 750 1040 1340 . . 240 232 390 600 840 1110 1400 1710 250 240 350 480 960 920 1180 1450 NOT APPLICABLE FOR BARS IN COLUMNS. DO NOT INTERPOLATE INTERPOLATE INTERDENT. 230 ENFORCEMENT SPLICES IN MIGHTWEICHONGERT CONCRETE AND SLIP FORMED CONCRETE WILL 340 FRIPORCEMENT SPLICES IN MIGHTWEICHONGERS MURES WEEVEDED ON MECHANICAL SPLICES. 350 PONTDE IMMUNMESSI LARS TO CARGE WIRES OF ENFORMENTION CONCRETION OUTERMOST 360 PONTDE IMMUNMESSI LARS TO CARGE WIRES OF ADJACENT SHEETS OT MENORCOMON CARACENT SHEET SO TATION OUTERMOST 		EPOXY CO REQUIRE 33. LAPPED S CONCRET FOLLOWIN	DATED BAF LONGER S PLICE LEN E CAST BE NG UNO:	RS, BARS IN PLICE LEN IGTHS FOR LOW THE	N LIGHTWE GTHS. RE VERTICA BAR) AND	EIGHT CON FER TO AS L BARS (AN SPACED A	CRETE AN 3600 OR S ID HORIZO T ≥150 mm	D SLIP FO UPERINTE NTAL BAR CENTRES	RMED COI NDENT. S WITH LE TO COMP	NCRETE WILL
E25 220 540 840 1210 - - 240 225 490 750 1040 1340 - - 240 225 490 750 1040 1340 - - 240 232 390 600 840 1110 1400 1711 250 240 350 480 690 920 1180 1450 NOT APPLICABLE FOR BARS IN COLUMNS, DO NOT INTERFOLATE INTERNETONET CONCRETE AND SUP FORMED CONCRETE WILL REQUIRE LONGER SPLICE LENGTHS, REFER TO AS300 OR SUPERINTENDENT, APPLY COATED BARS, BARS IN LIGHTWEIGHT CONCRETE AND SUP FORMED CONCRETEWILL REQUIRE LONGER SPLICE LENGTHS, REFER TO AS300 OR SUPERINTENDENT, 35, ENSURE REINFORCEMENT TOJUPLERS PROVIDE FULL TENSION CAPACITY OF REINFORCEMENT, 36, ENSURE REINFORCEMENT SO THAT MINIMUM COVER IS TO MAIN WIRES UNO. 37, PROVIDE MINIMUM MESH LAPS TO CROSS WIRES OF REINFORCING MESH, SO TWO COLTERMOST WIRES OF ONE SHEET OVERLAP TWO OUTERMOST WIRES OF ADJACENT SHEET SUND. 37, PROVIDE MINIMUM MESH LAPS TO SITE 25 END LAP 225 END LAP	CONTINUATION FOR REINFORCEMENT 25. FOR EXTERNAL OR CORRONNE APPLICATIONS USE HOT DIP GALVANZED 26. SUPPORT REINFORCEMENT ON PROPHETARY CONCRETE. METAL OR PLA ADEQUATE TO WITHISTAND CONSTRUCTION AND TRAFFIC LOADS AND MUMIP HINSHED CONCRETE STRUCTURE, FOR CONCRETE OR PROPHETARY HGH STRENGTH CEMENT SPACER BLOCKS OR SUPPORTS. 27. OD NOT PLACE OR MOVE REINFORCEMENT DURING OR AFTER CONCRETE BLASHIGATION OR GRAFT, NILL SPACE REINFORCEMENT AND EXPOSED TEMS, 100 NOT PLACE OR MOVE REINFORCEMENT DURING OR AFTER CONCRETE 28. ENSURE EMEEDDED TEMS (INSERTS, THREADED SOCKETS, FERRULES, BU METAL TEMS (a) IN COVER CONCRETE OR EXPOSED TO ATA RAEE NOT IN REINFORCEMENT AND EXPOSED TEMS. 29. DO TAT WILD REINFORCEMENT, CASTIN TEMS etc. UNLESS APPROVED U 31. SPLICE REINFORCEMENT CASTIN TEMS etc. UNLESS AND OTHER COVER CONCRETE. 30. DO NOT WELD REINFORCEMENT CASTIN TEMS etc. UNLESS APPROVED U 31. SPLICE REINFORCEMENT CASTIN TEMS etc. UNLESS APPROVED U 32. LAPPED SPLICE LENGTHS FOR HORIZONTAL BARS WITH MORE THAN 300 32. LAPPED SPLICE LENGTHS FOR HORIZONTAL BARS WITH MORE THAN 300 33. LAPPED SPLICE LENGTHS FOR BARS IN CLOUMNS REFERE TO COMPLY WITH TH COVER TO NILL ENGTHS FOR BARS IN CLOUMNS REFERE TO DETAILS OR SUPERINTENDENT DO NOT INTERPOLATE INTERMEDIATE VALUES OF SPLICE LENGTHS, 1240 225 230 400 430 1350 1740 - 1440 1350 1470 1150 1570 - 240 225 1220 590 980 1210 - 240 1225 1220 1590 1440 1340 - 1250 240 450 1350 1770 1140 1440 1510 250 240 350 440 750 1404 1340 - 1240 225 120 150 120 5121 5150 PPC REINFS OR CONCRETE AND SUPERINTENDENT FOLLOWING UND. DO NOT INTERPOLATE INTERMEDIATE VALUES OF SPLICE LENGTHS, REPORT CONCRET SPLICE LENGTHS FOR BARS IN COLUMNS REFERE TO DETAILS OR SUPERINTEND EDUDIE LONGTHS FOR BARS IN COLUMNS REFERE TO DETAILS OR SUPERINTEND EDUDIE CONCRET SPLICE LENGTHS FOR BAR				N32	-				
Early and a sign of the second seco	-							-	-	-
 NOT APPLICABLE FOR BARS IN COLUMNS. DO NOT INTERPOLATE INTERMEDIATE VALUES OF SPLICE LENGTHS. DO NOT INTERPOLATE INTERMEDIATE VALUES OF SPLICE LENGTHS. DO NOT INTERPOLATE INTERMEDIATE VALUES OF SPLICE LENGTHS. DO NOT INTERPOLATE INTERMEDIATE VALUES OF SPLICE LENGTHS. DEPENDENCE LENGTHS FOR BARS IN COLUMNS REFER TO DETAILS OR SUPERINTENDENT. EXEMPTION CONTRACTION DEPENDENT COLUMNS REFER TO DETAILS OR SUPERINTENDENT. ENSURE REINFORCEMENT SPLICES IN TENSION MEMBERS MUST DE WELDED OR MECHANICAL SPLICES. ENSURE REINFORCEMENT SPLICES IN TENSION MEMBERS MUST DE WELDED OR MECHANICAL SPLICES. ENSURE REINFORCEMENT SOLUTERNOST WIRES OF ADJACENT SPLORE SUPERIOR MESH SUNO. PROVIDE MIMIUM MESH LAPS TO CROSS WIRES OF REINFORCIMES UNO. PROVIDE MIMIUM MESH LAPS TO CROSS WIRES OF REINFORCIME SUNO. PROVIDE MIMIUM MESH LAPS TO CROSS WIRES OF REINFORCIME SUNO. RECTANOLUAR MESHES 225 END LAP 125 SIDE LAP SOLARE MESHES SIL02 TO SL42 225 END LAP 125 SIDE LAP SOLARE MESHES SIL02 TO SL42 225 END LAP 125 SIDE LAP SOLARE MESHES SIL02 TO SL42 225 END LAP 125 SIDE LAP SOLARE MESHES SIL02 TO SL42 225 END LAP 125 SIDE LAP SOLARE MESHES SIL02 TO SL42 225 END LAP 125 SIDE LAP SOLARE MESHES SIL02 TO SL42 225 END LAP MAR USE LAP LENGTHS BASED ON LARGEST WIRE SPACING. ON ON TLAP MORE THAN THREE SHEETS AT ANY ONE POINT. SALTERNATIVELY USE MIZ SPLICE BARS TO OVERLAP MESH. SPLICEND OF SPLICE BARS TO MATCH SPRACING OF BARS IN MESH. SPLICE BARS TO OVERLAP MESH BY 750 mm MIMIUMU MUNO. SUFICE TRENCH MESH FULL WIDTH OF INTERSECTION. AT L-INTERSECTIONS, CONTINUE TRENCH MESH FULL WIDTH OF INTERSECTION. AT LAND HITERSECTIONS, CONTINUE TRENCH MESH FULL WIDTH OF INTERSECTION AT LAND HAVES BAR TO AVERADE MAY AND SUFFRIKTENDER. WHER ALLOWED. WELDING OF REINFORCEMENT (INCOMING FACK-WELDING FOR FINNCE PURPOSES) TO COMPLY WITH ASSED MON DAVINGS OR OTHERWISE APPROVED BY SUPERINTENDER. TO HERE SHE OLLOWED WITH MES						-		1400	1710	1
DO NOT INTERPOLATE INTERMEDIATE VALUES OF SPLICE LENGTHS. LAPPED SPLICE LENGTHS FOR BARS IN COLUMNS REFERT NO DETAILS OR SUPERINTENDENT. EPOXY COATED BARS, BARS IN LIGHTWEIGHT CONCRETE AND SLIP FORMED CONCRETE WILL PROURE LONGER SPLICE LENGTHS, REFERT TO ASS800 OR SUPERINTENDENT. 34, REINFORCEMENT SPLICES IN TENSION MEMBERS MUST BE WELDED OR MECHANICAL SPLICES. 35, ENURE REINFORCEMENT SOUTHERS FORVIDEF FULL TENSION CAPACITY OF REINFORCEMENT. 36, LAY MESH REINFORCEMENT SOUTHERS FORVIDEF ULL TENSION CAPACITY OF REINFORCEMENT. 37, PROVIDE MINIMUM MESH LAPS TO CROSS WIRES OF REINFORCENCING MESH. SO TWO OUTERMOST WIRES OF ONE SHEET OVERLAP TWO OUTERMOST WIRES OF ONE SHEET OVERLAP TWO OUTERMOST WIRES OF ONE SHEET OVERLAP TWO OUTERMOST SUBAR MESHES SLID TO SL42 225 END LAP 225 BIDE LAP SUBAR MESHES SLID TO SL42 225 END LAP 125 BIDE LAP SUBAR MESHES SLID TO SL42 SUBAR MESHES SLID TO SL42 225 END LAP 125 BIDE LAP SUBAR MESHES SLID TO SL42 125 END LAP 125 END LAP SUBAR MESHES SLID TO SL42 126 END LAP 125 END LAP 125 END LAP 125 END LAP SUBAR MESHES SLID TO SL42 126 END LAP 125 END LAP 125 END LAP 125 END LAP SUBAR MESHES SLID TO SL42		- L					920	1180	1450]
SQUARE MESHES SL102 TO SL42 225 END LAP 225 SIDE LAP SL81 125 SIDE LAP 125 SIDE LAP TRENCH MESH 500 END LAP NA USE LAP LENGTHS BASED ON LARGEST WIRE SPACING, DO NOT LAP MORE THAN THREE SHEETS AT ANY ONE POINT. 7 38, ATTERNATIVELY USE N12 SPLICE BARS TO LAP ADJACENT SHEETS OF MESH, SPACING OF SPLICE 80, DATCH SPACING OF BARS IN MESH, SPLICE BARS TO OVERLAP MESH BY 750 mm MINNUM UNO, AT T-AND LANTERSECTIONS, CONTINUE TRENCH MESH BY A LAP OF 750 mm MINNUM UNO, AT T-AND LANTERSECTIONS, CONTINUE TRENCH MESH BY A LAP OF 750 mm MINNUM UNO, AT T-AND LANTERSECTIONS, CONTINUE TRENCH MESH BY A LAP OF 750 mm MINNUM UNO, AT T-AND LANTERSECTIONS, CONTINUE TRENCH MESH BY A LAP OF 750 mm MINNUM UNO, AT T-AND LANTERSECTIONS, CONTINUE TRENCH MESH BY A LAP OF 750 mm MINNUM UNO, AT T-AND LANTERSECTIONS, CONTINUE TRENCH MESH MENT UNLESS SHOWN ON DRAWINGS OR OTHERWISE APPROVED BY SUPERITYENDENT, WHERE ALLOWED, WELDING OF REINFORCEMENT (INCLUDING TACK-WELDING FOR FIXING PURPOSES) TO COMPLY WITH ASSOU AND ASIX251543. 3D NOT WELD REINFORCEMENT WITHIN 75 mm OF A SECTION THAT HAS BEEN BENT (100 mm FOR N28 AND N32 BARS, 125 mm FOR N88 BRS). EXTENT OF WELD INSPECTION/TESTING TO BE: VISUAL EXAMINATION, 50% OF WELDS VISUAL EXAMINATION, 50% OF WELDS VISUAL EXAMINATION, 50% OF WEL	E	DO NOT IN LAPPED S EPOXY CC REQUIRE 34. REINFORG 35. ENSURE F 36. LAY MESH 37. PROVIDE WIRES OF mm, THUS	ITERPOLA PLICE LEN DATED BAF LONGER S CEMENT SI REINFORCI I REINFOR MINIMUM I ONE SHE	TE INTERM IGTHS FOR S, BARS IN PLICE LEN PLICES IN T EMENT CO CEMENT S MESH LAPS ET OVERLA	EDIATE V BARS IN IGHTWE GTHS, RE TENSION M UPLERS P O THAT MI TO CROS	ALUES OF S COLUMNS I EIGHT CON FER TO AS MEMBERS I ROVIDE FL INIMUM CO SS WIRES C UTERMOST	REFER TO CRETE AN 3600 OR SI MUST BE W JLL TENSIC VER IS TO OF REINFO WIRES OF	DETAILS O D SLIP FO UPERINTE /ELDED OF DN CAPACI MAIN WIR RCING ME = ADJACE	RMED COI NDENT. R MECHAN TY OF REI ES UNO. SH, SO TV NT SHEET	NCRETE WILL NCAL SPLICES NFORCEMENT
40. DO NOT WELD REINFORCEMENT UNLESS SHOWN ON DRAWINGS OR OTHERWISE APPROVED BY SUPERINTENDENT. WHERE ALLOWED, WELDING OF REINFORCEMENT (INCULDING TACK-WELDING FOR FIXING PURPOSES) TO COMPLY WITH ASS800 AND ASNZS1554.3. DO NOT WELD REINFORCEMENT WITHIN 75 mm OF A SECTION THAT HAS BEEN BENT (100 mm FOR N28 AND N32 BARS, 125 mm FOR N36 BARS). EXTENT OF WELD INSPECTION/TESTING TO BE: • VISUAL SCANNING 100% OF WELDS • VISUAL SCANNING 100% OF WELDS • RADIOGRAPHIC OR ULTRASONIC 5% OF FILLET WELDS AND 100% OF BUTT WELDS. DRAWING COLOUR CODED - PRINT ALL COPIES IN COLOUR	F	SQUAF SL81 TRENC USE LAP L AT ANY OI 38. ALTERNA BARS TO I MINIMUM 39. SPLICE TF CONTINUE	RE MESHES ENGTHS E NE POINT TIVELY US MATCH SP UNO RENCH ME TRENCH	S SL102 TO BASED ON I ACING OF I SH BY A LA MESH FULI	LARGEST CE BARS ⁻ BARS IN M NP OF 750 L WIDTH C	225 END 125 END 500 END WIRE SPAC TO LAP AD, IESH, SPLIC mm MINIMU DF INTERSE	LAP 22 LAP 12 LAP N// CING. DO N JACENT SH CE BARS TO	5 SIDE LAF 5 SIDE LAF A IOT LAP M IEETS OF I O OVERLA F T- AND L-	ORE THAN MESH, SP/ P MESH B	ACING OF SPLICE Y 750 mm CTIONS.
	G	40, DO NOT W SUPERINT FOR FIXIN REINFORC BARS, 125 EXTENT O VISUAL VISUAL	ELD REIN G PURPOS EMENT W MM FOR I F WELD IN SCANNIN EXAMINA	FORCEMEN WHERE ALL SES) TO CC ITHIN 75 m N36 BARS). ISPECTION IG 100% OF TION 50% (NT UNLES: LOWED, W MPLY W M OF A SE //TESTING WELDS OF WELDS	S SHOWN (VELDING O FH AS3600, ECTION TH/ TO BE:	F REINFOF AND AS/NZ AT HAS BE	CEMENT (S1554.3. E EN BENT (INCLUDIN OO NOT WI 100 mm FC	G TACK-WELDING ELD)R N28 AND N32
REFERENCES: THIS DRAWING MAY BE PREPARED IN COLOUR AND MAY BE INCOMPLETE		DRAWING CC		DDED - PF	RINT ALL	COPIES	N COLOL	IR		
			-		TH	IS DRAWING	MAY BE PRE	PARED IN CO	LOUR AND	WAY BE INCOMPLETE
		REFERENCES:								
	Н	REFERENCES:			c					J0/11.04.24 J0/13.02.24

DO NOT BEND OR STRAIN REINFORCEMENT IN A WAY THAT MAY CAUSE DAMAGE. BEND
DIAMETERS TO BE TO AS3600. BARS TO BE BENT COLD UNO. GRADE 250 BARS MAY BE BENT AT
TEMPERATURES UP TO 850°C. DO NOT COOL HEATED BARS BY QUENCHING.

7

8

9

6

5

- JSE ONLY N12 QUENCHED AND SELF TEMPERED REINFORCEMENT FOR PULLOUT BARS OR BARS USE ONLY M12 QUENCHED AND SELF-TEMPERED REINFORCEMENT FOR PULLOUT BARS OR BARS TO BE BENT ON SITE (eg TEMPCORE BY ONESTELL). DO NOT USE MICROALLOY REINFORCEMENT FOR PULLOUT BARS AND BARS TO BE BENT ON SITE. CAST IN PULLOUT BARS WITH BEND CLEAR OF CONCRETE. USE PROPRIETARY POWERD BENDING TO OLS WITH PIN DAMETERS TO A S3800 AT AMBIENT TEMPERATURE FOR SITE BENDING OF PULLOUT BARS, USING A SINGLE SMOOTH BENDING ACTION, DO NOT USE IMPACT BLOWS OR HAMMER BARS, OR BEND BARS USING A PIPE. TAKE CARE TO MINIMUSE SURFACE BOAMAGE, AND INSPECT REBENT BARS FOR CRACKS, REPORT CRACKS TO SUPERINTENDENT. DO NOT CUT, BEND NOR HEAT REINFORCEMENT ON SITE WITHOUT SUPERINTENDENTS PRIOR MIDITICA MEDIZIONAL
- DUNDI CUT, BENDING REAL REINFORCEMENT ON STE WITHOUT SUPERINTENDENTS FRÜR WITTEN APPROVAL. ENSURE HOT BENDING OF REINFORCEMENT COMPLIES WITH AS3600 CLAUSE 17.2.3.1. DO NOT HEAT DISON REINFORCEMENT. USE TEMPERATURE INDICATOR PAINTS AND/OR CRAYONS TO ENSURE REINFORCEMENT TEMPERATURE DOES NOT EXCEED MANUFACTURENS RECOMMENDED LIMITS, 450 DEGRESS MAXIMUM, REINFORCEMENT THAT CHANGED COLOUR DURING HEATING JUST BE DISCARDED
- MUST BE DISCARDED. DO NOT EBND REINFORCEMENT AFTER GALVANISING OR APPLICATION OF OTHER COATINGS. USE 10 mm HOT DIPPED GALVANIZED DANLEY DIAMOND DOWELS (TEL: 07 3899 3486). INSTALL DOWELS PARALLE ITO SURFACE OF SLAB. MINITIAN DOWEL ALIGNMENT TO VLSE OF A SUITABLE SUPPORT ASSEMBLY TO ENSURE HORIZONTAL AND VERTICAL ALIGNMENT TOLERANCE OF 2 IN 300. DO NOT INSERT DOWELS DURING PLACEMENT OF CORCRETE. PERCUSSION ROTARY DRILL HOLES FOR GROUTED BARS AND THREADED RODS (NOTE: CORED HOLES MUST BE ROUGHENDED, HOLE DUMETER AND INSTALLATION TO BE IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS. EMBEDMENT ELENGTHS AS PER DRAWINGS.
- MANUFACTURER'S RECOMMENDATIONS, EMBEDMENT LENGTHS AS PER DRAWINGS. ENSIRE HOLES FOR GROUTED BARS AND THREADER DORS ARE DRY AND CLEANED THOROUGHLY BEFORE INSTALLING ANCHORS, WIRE BRUSH HOLES AND BLOW OUT WITH COMPRESSED ANT O REMOVE DUST, FILL HOLE WITH ADHESIVE USING A CAULKING GUN FROM BOTTOM OF HOLE OUTWARDS, DISCARD ADHESIVE FROM FIRST TRIGGER PULL, PROVIDE BARSTIRHEADED RODS WITH CHAMFERED (CHISELLED) ENDS, BARS TO BE DEGREASED, AND FLAXY RUST REMOVED, ROTATE WHILE INSERTING TO ENSURE FULLY COATED AND PUSH FULLY INTO HOLE. PROTECT FROM INSTURBANCE DURING CURING, FOLLOW MANUFACTURER'S RECOMMENDATIONS, USE HILT-HYDROR OR HILT HIT-RE500x3 ADHESIVE IN ACCORDANCE MANUFACTURER'S RECOMMENDATIONS UNO.

DRAWING COLOUR CO	RAWING COLOUR CODED - PRINT ALL COPIES IN COLOUR																	FOR RE	/IEW	PLOT DAT
REFERENCES:		THIS DRAW	VING MAY BE PREPARED IN COLO	UR AND MAY BE INC	OMPLETE IF	COPIED.	SCALE: NO	IOT TO SCALE	CLIENT			drawing and the related information have been prepared surpose other than the purpose intended by Transport for	ry, or at the request of, Transport for NSW for a specific purpose NSW.	and may not be used for	INNER WEST COU	JNCIL				
							_		184		ραφο	sport for NSW does not provide any warranties and acce, ose other than the intended purpose. This drawing is pro- rus written permission of Transport for NSW	ts no liability arising out of the use of this drawing or any of the n sted by copyright and no part of this drawing may be reproduce	in any form without the		ADS ASSET PERFO		CE CONTRACT	S	
	ŀ						-		NSV	Transpor	π					STATION BUS LAYO				
									GOVERNME	for NSW		aurecon 🔤	WN M. COMEDES			VENUE AND RAILW	/AY RC	AD		
	ŀ		D FOR 100% DETAILED DESIGN D FOR 80% DETAILED DESIGN		J0/11.04.24 J0/13.02.24	MP/11.04.24 VT/11. DC/13.02.24 VT/13.			PREPAR	ID EOP		ww.aurecongroup.com DES	GNEDLUBLEA		STRUCTURAL	OUEET I				н
	t	A ISSUED	FOR 20% DETAILED DESIGN		J0/21.09.23	MP/21.09.23 VT/21.			FINE PAP				CHECKS_TYLER GN CHECK _ B. REMEDIOS		GENERAL NOTES DRAWING SET N		PART	SHEET: 6 OF	11 11	
		REV	DESCRIPTION		DESIGNER INITIAL/DATE	VERIFIED APPRO	DATE		COI	NECT SYDNEY			J/DES MNGR J. STEWART			D DESIGN - 100%	BRIDGE		©	
		COORDINA	TE SYSTEM: MGA_ZONE_56	ØGDA2020			DESIGN LC	OT CODE:		0			ROVEDV.TIET	13.02.24	DRG No.	18-ST-DRG-000006	REV VEI B	R EDMS No.	AMD No.	
1	2		3	4			5	6		7		8	9		10	11		12		

DRAINAGE - GENERAL

2

3

4

5

11

12

А

В

С

D

Е

₿F

[§]G

WE.

က Attachment

1. ALL COORDINATES ARE REFERENCED TO GEODETIC DATUM OF AUSTRALIA (GDA94-) ZONE 56 AND ALL LEVELS ARE TO AUSTRALIAN HEIGHT DATUM. 2. ALL DIMENSIONS ARE IN MILLIMETRES UNLESS NOTED OTHERWISE ALL EXCAVATOR CAT 325B - 25.9 T ROLLER CPAAVR - 10 T GRADER CAT140H - 17 Α LEVELS. STATIONS AND COORDINATES ARE EXPRESSED IN METRES REFER TO TINSW STANDARD DRAWING INDEX TABLE 3 FOR DRAWINGS TO BE TRUCK CATD300E - 49 T COMPACTOR CAT815F - 20 9 T DOZER CATD9R - 48.3 T USED FOR THIS PROJECT ALL GRADING POINTS ARE RELATED TO FINISHED ROAD LEVEL ALL LOCATIONS, ORIENTATION AND LEVELS MUST BE VERIFIED ON SITE SCRAPER CAT623F - 60.2 T EXCAVATOR • COMPACTION WHEEL CAPAACWH1 - 20 T EXCAVATOR • COMPACTION WHEEL DEFORE COMMENCING ANY WORK, REFER DISCREPANCIES TO THE PRINCIPAL, DO NOT OBTAIN DIMENSIONS FROM SCALING, EXISTING SURFACE LEVELS ON THE DRAWINGS ARE INDICATIVE ONLY. 6 THE DOCUMENTED DRAINAGE SYSTEM IS DETAILED ONLY FOR THE PERMANENT ROAD CONFIGURATION UNLESS NOTED OTHERWISE. 7. EXISTING STORMWATER DRAINAGE PIPES AND MANHOLES WITHIN THE LIMITS DRAINAGE DURABILITY OF WORK MUST BE RETAINED, DECOMMISSIONED OR MODIFIED AS SPECIFIED. 8. CONTRACTOR TO UNDERTAKE PRE AND POST CONSTRUCTION CCTV В INSPECTIONS FOR ALL PIPE LINES IMPACTED BY THE WORKS AND TO BE PROVIDED TO TINSW FOR ACCEPTANCE PRIOR TO HAND-OVER. 9. CONTRACTOR TO MANAGE AND STAGE CONSTRUCTION WORKS. INCLUDING PROVIDING TEMPORARY DIVERSION WORKS, IF NECESSARY, TO ENABLE EXISTING DRAINAGE SYSTEM TO PERFORM TO ITS CURRENT STANDARD. SAFETY - IN - DESIGN INFORMATION IN THE PIT AND PIPE SCHEDULE 1 THESE DRAWINGS ARE TO BE READ IN CONJUNCTION WITH TINSW QA SPECIFICATION G22 AND THE PROJECT SAFETY IN DESIGN REGISTER. OTHER HAZARDS AND RISKS IDENTIFIED IN THESE DOCUMENTS TO BE ADDRESSED BY CONTRACTOR N AND SUB-CONTRACTORS ON SITE DURING MEETINGS. С AT ALL TIMES DURING CONSTRUCTION, ADEQUATE SAFETY PROCEDURE SHALL BE TAKEN TO PREVENT PERSONNEL FROM FALLING INTO PITS AND OPEN TRENCHES. EXISTING STORMWATER 1. LAYOUT OF EXISTING STORMWATER DRAINAGE HAVE BEEN PREPARED BASED ON A COMBINATION OF DRAINAGE UTILITIES SURVEY, DETAILED GROUND FEATURE SURVEY PROVIDED BY TINSW OBTAINED DURING CURRENT DESIGN AND BYDA INFORMATION. 2. WHERE AN EXISTING PIT HAS ONLY ONE PIPE OUTLET, THE SETOUT / REFERENCE POINT OF THE EXISTING PIT IS BASED ON THE SURVEYED PIPE D OA R11 STORMWATER DRAINAGE INVERT LEVEL 3 WHERE AN EXISTING PIT HAS TWO OR MORE CONNECTION PIPES. THE SETOUT QA R44 EARTHWORKS TREFERENCE OF THE EXISTING PIT IS BASED ON THE INTERSECTION POINT OF THE CENTERLINE OF EACH PIPE. ANY EXISTING RETAINED PIPES ARE TO BE TREATED IN ACCORDANCE WITH TINSW QA SPECIFICATION R11. DRAINAGE STRUCTURES 5. EXISTING STORMWATER PIPES OR CULVERTS THAT ARE IDENTIFIED TO BE DECOMMISSIONED OR ABANDONED SHALL BE ASSESSED FOR THE APPROPRIATE TREATMENT WHICH INCLUDES: REMOVE AND BACKFILL EXISTING PIPES / PITS TO BE REMOVED WITH TRENCH BACKFILLED AND COMPACTED. Е - SEAL AND GROUT - PIPE ENDS TO BE CAPPED AND PIPES INFILLED WITH GROUT. 6. ALL EXISTING STORMWATER DRAINAGE LINES AND PITS THAT ARE TO REMAIN, AND ANY PART OF THE SYSTEM DENTIFIED AS WARRANTING REPAIR SHALL BE REPORTED TO PRINCIPAL FOR FURTHER DIRECTION. LONGITUDINAL PAVEMENT DRAINAGE AND FRAMES WITHIN THE PAVEMENT SURFACE ARE TO BE BICYCLE SAFE IN ACCORDANCE WITH A 3599 GUILESS NOTED OTHERWISE. 6. ALL WELDS TO COMPLY WITH AUSTRALIAN STANDARD AS 1554, FILLET WELDS TO BE NOT LESS THAN 6mm UNLESS NOTED OTHERWISE. 7. ALL GALVANISING TO BE IN ACCORDANCE WITH ASINZS 2312 AND ASINZS 4880, GALVANISING TO THER DED FASTENERS TO BE IN ACCORDANCE WITH AS 1214, MINIMUM GALVANISING TO THER THAN ON FASTENERS. 1. ALL PIPES ARE TO BE CLASS 4 STEEL REINFORCED CONCRETE PIPE AS PER AS/NZS 4058:2007 UNLESS NOTED OTHERWISE. CONCRETE PIPES ARE TO BE RUBBER RING JOINTED SPIGOT AND SOCKET TYPE. ALL PIPEWORK IS TO LAID F WITH SOCKET FACING UPSTREAM 2. CONCRETE PIPE INSTALLATION SUPPORT TYPE TO BE MINIMUM 'HS2' IN ACCORDANCE WITH AS/NZS 3725-2007 3 CONCRETE PIPE CLASSES HAVE BEEN DETERMINED, BASED ON TYPE HS3 SUPPORT AND TRENCH OR EMBANKMENT CONDITION INSTALLATION TO AS3725 AND TINSW QA SPECIFICATION R11 UNLESS OTHERWISE NOTED. 4. ALL PITS AND PIPES ARE TO BE IN ACCORDANCE WITH TINSW STANDARD 520212-AURC-038-DR-DRG-006001 DRAWINGS. 5. CONNECTION BETWEEN PIPES AND STRUCTURES TO BE UNDERTAKEN IN ACCORDANCE WITH TINSW QA SPECIFICATION R11 AND TINSW STANDARD DRAWINGS. 6. PIPE CLASSES HAVE BEEN CHECKED FOR OPERATIONAL TRAFFIC LOADING AND THE FOLLOWING CONSTRUCTION MINIMUM COVER REQUIRED ABOVE EXISTING AND NEW PIPES BEFORE USING THE PLANT SHOWN IN TABLE 1. PIPES ARE TO BE G PROTECTED IN ACCORDANCE WITH TINSW QA SPECIFICATION R11.

TABLE 1 - MINIMUM COVER FOR CONSTRUCTION LOADS NUM COVER FOR CONSTRUCTION LOAD RCP CLASS 4 (nm) EXISTING PIPE (nm) 400

6

7

8

9

- 1 THE EXPOSURE CLASSIFICATION FOR BOX CULVERTS SHALL BE 'B1' IN ACCORDANCE WITH AS 1597.2:2013 AND DRAINAGE PITS SHALL BE 'B1' IN ACCORDANCE WITH AS5100.5:2017 UNLESS NOTED OTHERWISE IN THE PIT AND PIPE SCHEDULE.
- PRECAST PIPES SHALL BE IN ACCORDANCE WITH AS/NZS 4058/2007 ALL PIPES PRECEST PIPES SHALL BE IN ACCORDANCE WITH ASINZS 4088/2007. ALL PIPES SHALL BE BACKFILLED WITH NON-AGGRESSIVE SOLL (pH >5.5, SO4 < 1000 mg/Kg (ppm) AND CHLORIDE < 1000 mg/Kg (ppm)). THE EXPOSURE CLASSIFICATION FOR PRECAST PIPES HAS BEEN CLASSIFIED AS 'NORMAL' UNLESS NOTED OTHERWISE

CONSTRUCTION LOAD	COVER (MM)
PEDESTRIAN VIBRATING PLATE	200
VIBRATORY RAMMER (UP TO 75kg)	250
VIBRATORY TRENCH ROLLER (UP TO 21)	250
VIBRATORY SMOOTH DRUM ROLLER (71)	500
TRUCK AND DOG TRAILER	500
25 TONNE EXCAVATOR AND 580mm COMPACTION WHEEL ACTING SEPARATELY	1000

TRANSPORT FOR NSW SPECIFICATIONS

- OA R53 CONCRETE FOR GENERAL WORKS
- 1. STRUCTURES HAVE BEEN DESIGNED FOR FINAL LOADS (UNLESS STATED OTHERWISE) ACTING ON COMPLETED STRUCTURES. THE CONTRACTOR IS RESPONSIBLE FOR THE DESIGN AND PROVISION OF ANY TEMPORARY BRACING, PROPPING, ETC. REQUIRED DURING CONSTRUCTION, STRUCTURES MUST BE MAINTAINED IN A STABLE CONDITION
- AND NO PART MUST BE OVERSTRESSED. 2. FOUNDATION SUPPORT FOR DRAINAGE STRUCTURES TO BE PROVIDED IN ACCORDANCE
- TO TINSV GA SPECIFICATION R11. INADEQUATE FOUNDING MATERIAL FOR PIPES AND STRUCTURES MUST BE REMOVED OR IMPROVED IN ACCORDANCE WITH TINSW QA SPECIFICATION R11. TINSW STANDARD DETAILS TO BE ADOPTED UNLESS NOTED OTHERWISE.
- TINESIN GTANDARD DE FAUST IS EN ADD'T ELD DIRESSIN FED TROM MED STEEL GART ES AND FRAMES ARE TO BE FABRICATED FROM MILD STEEL AND HOT DIP GALVANISED ALL GRATES ARE TO BE CLASS (UNLESS NOTED OTHERWISE), GRATES AND FRAMES WITHIN THE PAVEMENT SURFACE ARE TO BE BICYCLE SAFE IN


- 8 GRATE SUPPORT TO BE CONSTRUCTED LEVEL TO ENSURE THAT THE GRATE DOES NOT
- 9 FOR LOCATION AND LEVEL OF PITS, REFER TO PIT SCHEDULE ON DRAWING

							This sharehow and the article of information beam from a		est of. Transport for NSW for a speallic purpose and may	and by courd for one			FUR	REVIEW							
REFERENCES: THIS DRAWING MAY BE PREPARED IN COLOUR AND MAY BE IN					COMPLETE	- COPIED.	SCALE: NOT	TO SCALE	CLIENT:		custops other than the purpose intended by Treaspo	ort for NSW	and of the use of this drawing or any of the related inf		INNER WEST COUNCIL						
		_									purpose other then the intended purpose. This drawing	and accepts no liability are ing is protected by copyrig	any out of the use of this drawing or any of the related int At and no part of this drawing may be reproduced in any f	annalism for any ann without the express	SYDNEY RO	ADS ASSET PERF	ORMANCE CONTI	RACTS			
		-					-				NSW Transport		written permission of Transport for NSW.				SYDENHAM	STATION BUS LAY	OVER		
	-						í.		NSW for NSW				NSW for NSW	NSW for NSW		w aurecon	DRAWN R. MARTINEZ		11.04.2024 BUR	024 BURROWS AVENUE AND RAILWAY ROAD 024 DRAINAGE GENERAL NOTES	
	-	+					-														
		-							PREPARE) FOR:	www.aurecongroup.com		CK M. RICHARDS			INTENOTES					
	A010 ISSUED FOR 100% DETAILED DESIGN MR 11/04/2024 AJ 11/04/2024 V.T 11/04			AJ 11/04/2024 V.T 11/04/2024					DESIGN CHECK _ P.MCLEAN												
F		(DESCRIPTION		DESIGNER INITIAL/DATE	VERIFIED APPROVED INITIAL/DATE NITIAL/DATE	1		CON	NECT DSYDNEY					STATUS: DETAILE		BRIDGE No:	C			
		ORDINA	ATE SYSTEM: MGA_ZONE_56/GDA20				DESIGN LOT	CODE:		0		APPROVE	DV.TIET	11.04.2024	0RG No 520212-AURC-0	038-RW-DRG-000007	REV VER EDMS No. A01.01	AND No.			

TABLE 3 - THISM STANDARD DRAMINGS

TABLE 3 - TfNSW STANDARD DRAWINGS											
MODEL DRAWING NUMBER	NUMBER										
R0220-01	GULLY PIT TYPE SA FOR PIPE DIA. UP TO 450mm	Jun-17									
R0220-03	PRECAST CONCRETE LINTELS FOR TYPE SA GULLY PITS	Jun-17									
R0220-21	GULLY PIT TYPE SO1	Jun-17									
R0220-28	GULLY PIT WIDENING FOR PIPES GREATER THAN 450mm DIA	Jun-17									
R0220-35	INSPECTION PIT WITH SINGLE OR DOUBLE CAST IRON FRAME AND COVER	Jun-17									
R0240-01	INSTALLATION OF BURIED CONCRETE PIPES TYPE HS3 SUPPORT										

3 June 2024





1

R

А

В

С

D

Е

F

G

н

REFERENCES:

1

MK01-

Item 2

3 June 2024

А

В

С


D

Е

G

н


Item 2



Attachment


က






Item 2









В

С


D

Е

F

G

Н



က

11


10


9

8



12






Attachment

က






FR WF


Attachment

Item 2



Extraordinary Local Traffic Committee Meeting 3 June 2024

Item 2




S

Item 2

က


Attachment



IER WEST

Extraordinary Local Traffic Committee Meeting 3 June 2024

Item 2




Attachment

က









А

В

С

D


Е

F

8

[≊]G

н




HR.

Item 2

S


Attachment

3 June 2024




Item 2

Attachment








FR WÞ






3 June 2024



Item 2

3 June 2024




ST

R

က

3 June 2024



Item 2

S

3 June 2024

А

В

С


D

Е

۶F

[≊]G

н



ER WEST

Attachment 3

12

11

9

8

10

	1	2	3	4	5	6	7	8	9	10	11	12	
A	R	PT CHAINAGE EASTING S 0.000 330442.782 10.000 330447.4673 20.000 330465.963 330465.965	SNMENT->MC01 HORIZONTAL SEGM NORTHING HEIGHT BEARING 6246600,785 5.361 307/4330.97 6246610,916 5.225 30774330.97 6246610,312 5.227 30774330.97	ENTS DEP.3EQ DEP.RAD DEP.LEN LINE 103.475	PT CHAINAGE S 0.000 10.000 TC 16.813 20.000	ALIGNMENT KERB->MK03 H EASTING NORTHING HEIGHT 3304/21/76 6245637.167 4.992 330412.267 6245632.285 4.974 330408.788 6245637.454 4.952	BEARING DEP.SEG 307°43'30.64" LINE 307°43'30.64"	DEP.RAD DEP.LEN 16.813 17.500 34.089 17.500	PT CHAINAGE EASTING NC S 0.000 330420.392 624 10.000 330426.341 624 DIS 18.115 330431.169 624	->NW01 HORIZONTAL SEGMENT RTHNG HEXHT BEARNO 665.736 5.234 36*30/22.51* 680.298 6.191 35*22/02.17* 680.298 6.191 35*22/02.17*	Image: Second state DEP.LEN LINE 18.115 LINE 14.075		A
В		40,000 330461,44 50,000 330443,234 60,000 330445,225 77,0000 330427,415 70,000 330427,415 70,000 330417,956 90,000 330417,956 100,000 330403,587 TC 103,475 330400,383 110,000 330385,793 112,000 330385,793 122,000 330385,584	62463.1270 6.195 307*430.597 624637.389 6160 307*430.597 6246467.389 5.125 307*430.597 624564.4507 5.125 307*430.597 624564.8507 5.125 307*430.597 624564.8507 5.125 307*430.597 624566.864 4.972 307*430.597 6245667.862 4.562 307*430.597 6245667.108 4.962 307*430.597 624567.108 4.960 307*430.597 624565.3616 5.464 307*430.597 624565.3616 5.464 307*430.597 624565.3616 5.465 307*430.597 624565.3616 5.465 307*430.597 624565.3616 5.485 10*50*46.337	ARC 15,000 29,219 15,000 15,000	30,000 40,000 50,000 CT 50,901 60,000 70,000 80,000 E 85,606	330400,306 6245678,528 5,131 330401,555 6245698,313 5,733 330407,897 6245698,313 6,185 330408,660 6245696,348 6,233 330416,867 6245696,348 6,233 330408,680 624500,588 6,719 33046,847 6245700,589 6,719 33042,688 6245710,699 7,287 33043,689 6245711,190 7,787 330438,651 6245714,049 8,086	59°19'57.17" 59°19'57.17" 59°19'57.17" 59°19'57.17"	17,500 17,500 17,500 34,705	30,000 330438,046 624 DIS 32,189 330438,315 624 40,000 330443,934 624 DIS 41,818 330445,657 624 DIS 45,779 330446,657 624 DIS 48,158 330448,654 624 SOL000 330448,654 624 6304 DIS 48,158 330448,654 624 SOL000 330450,648 624 63048 DIS 64,848 330450,648 624 SOL000 330450,648 624 624	669.990 6,933 35°22/02,17° 690.77 7,073 36°1507,69° 690.874 7,572 36°1507,69° 690.874 7,690 36°1507,69° 703.142 7,960 53°1743,34° 704.564 8,123 53°2555,25° 705.652 8,249 53°2555,25° 705.653 8,282 36°0258,33° 715.464 8,933 36°0258,33°	LINE 9.628 LINE 3.961 LINE 2.379 LINE 2.331 LINE 15.902		в
С		130.000 330400.284 CT 132.694 330402.465 140.000 330408.750 330417.351 160.000 330425.953 33043.556 170.000 33043.156 33043.156 180.0000 33043.156 190.000	b24968,479 b.bbb 1015/414,395 c2445693,301 b568 4570228,801 c245694,8475 b.088 5571957,007 c245694,8475 b.080 5571957,007 c245703,803 7,913 5571957,007 c245701,803 7,913 5671957,007 c245713,803 7,913 5671957,007 c245714,004 6,475 5671957,007 c245714,004 6,476 5671957,007 c245712,020 9,518 5671957,077	15.000 LINE 67.306	PT CHAINAGE S 0.000 CT 2.218 10.000 20.000 TC 20.413 E 22.631	ALICINMENT KERBMK04 H EASTING MORTHING HEIGHT 330404_053 6245671,856 4,954 330404_505 6245671,856 4,954 330404_505 6245671,856 5,460 330404_551 6245671,856 5,460 330404_551 6245671,853 5,966 330404_551 6245671,853 5,966 330404_551 6245671,853 5,966 330405,955 6245692,003 5,966 330406,545 6245693,3905 6,098	BEARING DEP.SEG I 7"28'20.77" ARC 7"28'20.77" LINE 7"28'20.77" Y 7"28'20.77" RC 40*50'17.90" ARC	DEP.RAD DEP.LEN 3.000 2.218 18.195 3.000 3.000 2.218	PT CHAINAGE EASTING NC S 0.000 330418.785 624 10.000 330424.734 624 20.000 330430.683 624 DIS 22.888 330432.401 624	Electric Description Th-Net HeE/ehrt Beanso 666.927 5.204 36"30/22.51" 674.965 5.673 36"30/22.51" 685.302 6.477 36"43/22.51" 685.324 6.447 37"43/39.32" 687.336 6.640 35"2/20.17"	NTS DEP.3EG DEP.LEN LINE 22.888 LINE 2.543 LINE 6.736		с
D	_	PT CHAINAGE EASTING S 0.000 330374.542 CT 1.318 330375.567 10.000 330382.404 TC 12.383 330384.280 20.000 330390.493 CT 21.701 330391.936 GT 21.701 330399.022	IENT KERB->MK01 HORIZONTAL SEG NORTHING HEIGHT BEARING 6246883.272 A248 51*5715.61* 6246883.278 A404 51*5715.61* 6246883.278 A404 51*5715.61* 6246883.278 A404 51*5715.61* 6246880.429 A506 51*5715.61* 6246890.497 5.218 51*5715.61* 6246894.490 5.734 88*3740.92* 6246990.400 5.734 88*3740.92* 6245904.200 6.81*8 8*3740.92* 6245904.001 6.330 58*3740.92*		E 1.562	ALIGNMENT KERB->MK05 H0 EASTING NORTHING HEIGHT 330401.986 6245674.540 4.907 330403.131 6245674.540 4.907 330403.131 6245674.540 4.907 ALIGNMENT KERB->MK06 H1 EASTING NORTHING HEIGHT 330405.237 6245691.385 5.912	BEARING DEP.SEG DE 7*28'20.76' ARC C 7*28'20.76' BEARING C NRIZONTAL SEGMENTS BEARING DEP.SEG 218'21'29.35' ARC	1.600 1.562	30,000 304/45,602 624 DIS 32,147 304/45,865 624 40,000 304/42,865 624 DIS 41,638 304/43,454 624 DIS 44,705 3304/43,454 624 DIS 44,563 3304/43,612 624 S0,000 3304/43,630 624 60,000 0304/43,630 624 624,000 3304/43,679 624 OLO 3304/43,679 624 60,000 3304/43,679 624	691.02 6.903 35*2202.17 662.829 7.042 66*1409.25* 669.147 7.56 65*1409.25* 700.468 7.650 24*3445.74* 7070.410 7.922 53*1743.34* 706.009 8.104 53*2555.25* 7070.723 8.236 56*0258.33* 774.703 8.829 36*0258.33* 774.869 9.240 36*0258.33*	LINE 9.471 LINE 4.225 LINE 2.842 LINE 2.058 LINE 15.627		D
E	_	ALIGNN PT CH4INAGE EASTING S 0.000 330424.865 TC 0.449 330424.504 CT 2.014 330423.055 TC 6.461 330424.504 CT 2.014 330424.056 TC 6.861 330421.560 CT 6.661 330421.570 10.000 330417.584 C1 CT 17.662 330417.584	MENT KERB>-MK02 HORIZONTAL SEC NORTHING HEIGHT BEARING 6245653,191 4,743 307*420.077 6245659,465 4,743 307*420.077 6246569,465 4,743 307*420.077 6246569,766 4,993 307*593.087 6246567,166 4,993 307*593.087 6246567,166 4,998 307*593.307 6246567,166 4,998 303*4729.211 6246560,076 4,964 303*4729.211 6246560,076 5,964 353*4729.211		CT 3.028 TC 4.926 CT 5.697 TC 7.571 CT 8.754	ALIGNMENT KERB->MK07 H EASTING NORTHING HEIGHT 330402.273 6245602.396 6.548 330401.253 6245602.396 6.548 330403.034 6245605.276 5.559 330486.170 6245605.475 5.579 330468.170 6245605.072 5.472 330465.171 6245605.475 5.404	BEARING DEP.SEG 324*17'03.56" LINE 324*17'03.56" ARC 303*19'20.32" LINE 303*19'20.32" ARC 259*08'27.04" LINE 219*16'10.21" LINE	DEP.RAD DEPLEN 1.747 3.500 1.280 1.898 -1.000 0.771 1.874 -1.700 1.183 0.396					E [0]
F	_	20,000 330419,829 30,000 330425,578 40,000 330425,578 CT 44,0550 330431,527 CT 44,0550 330431,556 CT 44,614 330433,356 60,000 330434,058 CT 45,734 330436,104 70,000 330438,279 CT 74,642 330442,735	6245692,911 5,160 36*1022.51* 6245672,7249 5,704 36*1022.51* 6245672,7249 5,704 36*1022.51* 6245682,727 6,337 36*1022.51* 6245682,729 6,337 36*1022.51* 6245682,448 6,500 7*220,55* 6245644,708 6,504 7*220,55* 6245712,4391 8,669 7*220,55* 6245714,409 7,4820,55* 6245714,408 8,672 6,773 6245714,408 7,2820,55* 6245714,408 7,2820,55* 6245714,408 7,2820,55* 6245714,408 8,673 6245714,408 8,773 6245714,408 8,773 6245714,408 8,773 6245714,408 8,773 6273 6,973 6,974 8,773 6,773 6,773 7,773 6,774	ARC -5.000 4.064 21,130 ARC 5.000 8.908 5.000 LINE 0.000	E 9.150	330484.923 6245605.172 5.381	219*16'10.21*						FILE NAME: 520212-AURC-038-RM-DR0-004
G		TC 74.642 330442.735 E 79.069 330446.997	6245714.460 8.273 109*3314.39* 6245714.894 8.462 58*4926.41* PIES IN COLOUR	ARC -5.000 4.427								FOR REVIEW	PLOT DATE & TIME 180042024 1:42:30 PM
н	REFERENCES:	801/A65 A 155 FEV	RAMING MAY BE PREPARED IN COLOUR A INED FOR KINN DETAILED DESIGN URED FOR KINN DETAILED DESIGN DESCRIPTION INATE SYSTEM: MGA_ZONE_56/GDA20	LC 18,042284 AJ 18,042284 LC 18,042284 AJ 18,042284 LC 18,042284 AJ 18,042284 LC 18,042284 AJ 18,042284 LC 18,042284 AJ 18,042284 DESIGNER MIRLANT	V.T 18.04.2024	9 5 10m ILE 120 PREPAI	RED FOR:	Is dramp, and for incled afformation laye loo manage of a ADD base regional and a second second provide the ADD base regionals are provide any second and the permission of language for ADD base Contract Contract (Contract) WirkLard Congregation	DRAWN V. Buy M. Charles Care V. Lanke, Joseph J. Charles V. Lanke, Joseph J. Charles V. Charl	SYDENHAM S 13.02.2024 BURROWS AV 13.02.2024 SETOUT TABLES 13.02.2024 DRAWING SET NO: 13.02.2024 DRAWING SET NO: 13.02.2024 STATUS: DETAILED	DS ASSET PERFORMA TATION BUS LAYOVEF /ENUE AND RAILWAY F DESIGN - 100% BR	ROAD	H

Attachment 3

7

6

5




2

1

3

Item 2







А

В

С

D

Е

۶F

[≊]G


н

AMD No.

FOR REVIEW


12

12



Item 2






S

Extraordinary Local Traffic Committee Meeting

3 June 2024






Extraordinary Local Traffic Committee Meeting


3 June 2024
















12.50

6.85

12

 $(\odot)(\odot$

METERS 2.50 2.50 2.50 3.6.0 3.6.6 А

В

С

D

Е

G


10


2.20

BUS

WIDTH TRACK LOCK TO LOCK TIME STEERING ANGLE









METERS

: 1.94 : 1.84 : 6.0 : 33.5

А

В

С

D

Е

G

н

FOR REVIEW


PART: SHEET: 35 OF 41 A

12

BRIDGE No: REV VER EDMS No A01.01

11





Attachment 3

7

8

9

10

6

DESIGN LOT CODE:

5

COORDINATE SYSTEM: MGA_ZONE_56/GDA20


3

2

1

HEIGHT DATUM


Item 2



Attachment

က






Attachment


က



က







RR WÞ

က

Attachment



3 June 2024



Item 2

Attachment 3



Item No: LTC0624(2) Item 3

Subject: RAILWAY ROAD, SYDENHAM - PROPOSED CHANGES TO PARKING AND TRAFFIC ARRANGEMENTS AS A RESULT OF CONSTRUCTION WORKS (MIDJUBURI- MARRICKVILLE WARD / HEFRON ELECTORATE / INNER WEST PAC)

Prepared By: George Tsaprounis - Coordinator Traffic Engineering Services (south)

Authorised By: Manod Wickramasinghe - Traffic and Transport Planning Manager

RECOMMENDATION

That 45-degree rear to kerb angle parking signposted as '2P 8am-10pm Permit Holders Excepted Area M4' be approved for the eastern side of Railway Road from no. 101/103 to 111/113 Railway Road in order to lessen parking impacts from construction activities.

STRATEGIC OBJECTIVE

This report supports the following strategic directions contained within Council's Community Strategic Plan:

2: Liveable, connected neighbourhoods and transport

EXECUTIVE SUMMARY

Transport for New South Wales (TfNSW) has approached Council with regards to a proposal for the construction of a bus layover area in Burrows Avenue, west of Gleeson Avenue, Sydenham. The designated bus layover area is required at Sydenham Station to cater for the growing number of bus services in this area.

It is proposed to increase parking capacity in Railway Road during construction activities to reduce the impact on residents.

BACKGROUND

The proposed bus layover facility at the corner of Railway Road and Burrows Avenue in Sydenham will include the following changes (refer to figure 2):


- Six 16m-long angle bus parking spaces on the southern side of Burrows Avenue with manoeuvring space at the northern end of Railway Parade for egress, replacing a total of 11 parallel parking spaces.
- A dedicated drivers amenity block with a lunchroom and toilets.
- The 8 parallel parking spaces along the eastern side of Railway Road converted into 13x 45 degree angle car parking spaces.
- A reduction in 90 degree angle car parking spaces along the northern side of Burrows Avenue from 12 to 6 spaces.
- Create a path for pedestrians, passengers and the community to safely walk to and from Railway Road to Gleeson Avenue.
- Build a noise wall to separate the nearby homes from the new bus layover facility and minimise noise impacts from the bus layover facility.
- Install driveways for buses to enter from Railway Road and leave through Burrows Avenue.



DISCUSSION

TfNSW are planning to commence construction activities for the new bus layover area on 10 June 2024. This will involve installing a temporary site compound on Burrows Avenue at Railway Road (in the existing 90-degree parking area against the railway fence on Burrows Avenue). This will temporarily remove all 12 spaces in this area (6 spaces will be returned in the final layout).

Upon completion of stormwater drainage and roadworks in bus layover area (on 22 July 2024) the site compound will then be relocated into the bus layover area. The project is expected to be finished by mid September 2024. In order to lessen the burden of loss in parking for residents of Railway Road, it is proposed to install the 45 degree 2P Residential Parking spaces during this phase of the works. This will assist the residents by creating some parking. These spaces will remain in place at the end of the works.



FINANCIAL IMPLICATIONS

There are no financial implications associated with the implementation of the proposed recommendations outlined in the report.

ATTACHMENTS

Nil.



Item No: LTC0624(2) Item 4

Subject: PROPOSED NEW KERB EXTENSION FACILITES AT INTERSECTION OF VICTORIA STREET AND CLISSOLD STREET, ASHFIELD. (DJARRAWAWUNANG- ASHFIELD WARD/SUMMER HILL ELECTRATE/BURWOOD PAC)

Prepared By: Boris Muha - Traffic Engineer

Authorised By: Manod Wickramasinghe - Traffic and Transport Planning Manager

RECOMMENDATION

That the detailed amended design plan (10281-A) to install new landscaped blister islands (kerb extension build-outs) and painted island/line marking to all corners of Victoria Street at Clissold Street, plus realign the 'STOP' lines on both approaches on Clissold Street and remove the raised central median islands to be replaced with road at-grade stenciled marked islands in Clissold Street as shown in *Attachment 1*, be approved.

STRATEGIC OBJECTIVE

This report supports the following strategic directions contained within Council's Community Strategic Plan:

2: Liveable, connected neighbourhoods and transport

EXECUTIVE SUMMARY

Council at its meetings on 18 March 2024 (through its Traffic Committee 11 December 2023) approved in principle, subject to detailed design, a series of proposed pedestrian (zebra) crossings and kerb extension treatments (under concept) for improved pedestrian and road safety around and near to the Cardinal Freeman (Retirement) Village, Ashfield.

This report discusses the prepared design of the proposed treatment, i.e., provide new landscaped blister islands (kerb extension build-outs) and painted island/line marking to all corners of Victoria Street at Clissold Street. In addition, the 'STOP' lines are realigned on both approaches of Clissold Street and the raised central median islands are replaced with at-grade stenciled islands in Clissold Street. This work is programmed to be constructed in the 2024/2025 financial year.

BACKGROUND

The Cardinal Freeman Village (currently known as Levande Cardinal Freeman) is bounded by Clissold Street to the north, Victoria Street to the east, Seaview Street to the south and Queen Street to the west.

The village caters to an independent living lifestyle however as the average age is over 82 years there are a significant number of residents with mobility issues that hinder their ability to move around freely.

Many of the elderly residents are capable, and desire to walk to and from various destinations outside of the village, and/or take other forms of public transportation (e.g., bus and train) to travel to other parts of Sydney.

Extraordinary Local Traffic Committee Meeting 3 June 2024

This has prompted a general request from the elderly residents to improve pedestrian safety around the village to enable them to walk to various desired destinations and take public transport within the area.

Other Aged care facilities such as the Ashfield Baptist Homes, Bethal Nursing Homes, Ashfield Terrace Care Community, and other community facilities are also located adjacent or near to the Cardinal Freeman Village.

The proposed treatment in this report received a high support rate (80%) under a general community engagement consultation conducted through Council's 'Have Your Say' back in October 2023. The facility is viewed in benefit and supported by the community at large, and not only for the elderly of the Cardinal Freeman Village.

DISCUSSION

The following information is provided in discussion.

NHR WISST




Figure 1. Locality Plan

Propose	d intersection treatment of Victoria Street and		
Clissold Street, Ashfield.			
•	New landscaped blister islands (kerb extension		
	build outs and painted island/line marking to all corners of Victoria Street.		
•	Remove narrow concrete median islands in Clissold Street at approaches to Victoria Street- replace with at-grade stenciled concrete central median islands.		
•	Bring out the STOP lines on both sides of Clissold Street.		

Street Name	Victoria Street (at intersection to Clissold Street)
Carriageway width (m) kerb to kerb	Approx. 12.8m
Carriageway type	Two-way, one travel lane each direction.
Classification	Local
Speed Limit km/h	50
85 th percentile speed km/h	
Vehicles per day (vpd)	Approx. 2500
Available TfNSW recorded crash history Last 5 years (2018- 2023)	2 X RUM 10 at intersection 2021 and 2023, cross-traffic, both non-casualty tow-away
	Prior to 2018, 5 incident occasions recorded as far back to 2009, mainly RUM 10, cross traffic, non injury to moderate injury.
Parking arrangements	Unrestricted parking both sides, 'No Stopping' to corners of intersection
Side street (nearest)	-

豆荚杈 金斑斑

Table 1. Road Network detail. Change

The Plan

The following works are proposed and are illustrated on the attached plans:

Clissold Street (at Victoria Street), Ashfield (Amended Plan No. 10281-A):

- Construct three (3) new landscaped kerb blister islands with integrated footpaths and kerb ramps to improve pedestrian points & safety whilst slowing traffic approaching the intersection;
- Provide painted island/line marking treatment to the north-eastern corner of the intersection to maintain the existing Bus Stop at the corner;
- Construct four (4) new kerb ramps to improve pedestrian accessibility;
- Reconstruct sections of damaged concrete footpath with new concrete footpath
- Reconstruct some damaged concrete kerb & gutter with new kerb & gutter;
- Remove the 2 raised concrete median islands in Clissold Street and construct new 'atgrade' (flat) central median islands in their place (with stencilled & coloured finish);
- Provide new line marking at the Clissold Street intersection (extending into Victoria Street) to improve sight lines for motorists (refer to Plans);
- Adjust 1 existing 'No Stopping' sign and zone in Victoria Street to cater for one of the new kerb blister islands (refer to plans);
- Install associated signage associated with the works as required and where shown on Plan;

Parking Changes

The proposal will require an adjustment to some of the existing on-street parking arrangements. It is proposed to adjust the existing 'No Stopping' signage and zone in Victoria Street to accommodate one of the new landscaped kerb blister islands needed to improve pedestrian safety.

This adjustment <u>will not</u> result any loss of existing on-street parking spaces in Victoria Street or Clissold Street.



Streetlighting

The existing lighting is deemed adequate and therefore there will be no changes to the existing street lighting due to the proposed works.

Further information

- The kerb blister islands, or kerb extension build outs with compliant pram ramps assist pedestrians to cross-over Victoria Street over a shorter distance, whilst being refuged by the islands.
- The north-eastern corner of the intersection is treated in painted island/line marking to maintain the function and operation of the existing Bus Stop on the eastern side of Victoria Street, north of Clissold Street. A complaint pram ramp is constructed away of the required front door boarding area of the bus.
- The alignment of the kerb blister islands and painted line marked island assists to bring out the STOP lines in Seaview Street to improve the sight view of traffic.
- The kerb blister islands and line marked island are widened out as far possible to provide a narrowing channel for 2-way traffic in Victoria Street in attempt to control speed through the intersection. Associated and extended edge line marking in Victoria Street assists to guide and control traffic movement though and around the intersection.
- The existing narrow (raised) concrete median islands in Clissold Street, in approach to the Victoria Street are removed and replaced with road at-grade stencil marked islands with associated line marking to maintain the separation in traffic. The physical islands are narrow and are known to be hit with signage on top being continuously damaged, particularly with vehicles turning at the intersection. They are therefore viewed to be hazardous.
- Transit Systems Australia, being the public bus operator for Transport for NSW raises no objection to the proposal.
- Design garbage turn path movements are provided in Attachment 2.
- An original plan (10281) was issued out to consultation as shown in Figure 2 below. Based on certain concerns as raised by residents regarding illegal parking and the need for improved sight view at the corners of the intersection, the kerb blister islands are amended and extended and tailed off in towards Clissold Street. -see amended plan 10281-A Attachment 1. This further signifies the presence and effectiveness of the kerb extensions to assist and guide traffic through and around the intersection and ensures that vehicles do not park at the corners. The extension of the kerb blister islands further improves to assist and bring out the 'STOP' lines in Clissold Street, particularly on the western side of Victoria Street, nearest the Cardinal Freeman Village.

The north-western kerb return corner of the intersection (under amended plan) is extended out to widen the pram ramp at the corner of Clissold Street.




Figure 2. Original plan (10281) issued out to consultation

FINANCIAL IMPLICATIONS

DER WEST

The project is listed on Council's Traffic Facilities Capital Works budget for works to be carried out in 2024/2025, subject to funding. The work is estimated to be around \$95,000. Council has applied for external funding for this project under the Get Active NSW/Road Safety Program.

CONSULTATION

A letter outlining the proposal was mailed out to 18 properties (55 letters) around the intersection of Victoria Street and Clissold Street, Ashfield requesting residents' views regarding the proposal.



HR R

Figure 2. Map on Consultation Area

Council officers also convened a presentation session on the 2 May 2024 at the Cardinal Freeman Village outlining the proposal to the elderly residents of the Village.

One (1) street resident raised concerns as to why a kerb-blister island was not going in one of the corner locations in Victoria Street. 11-12 residents of the village who attended the presentation session and who provided comments on the proposal on the day were wholly in support of the proposal with or without certain concerns. One (1) resident was unsure.

One (1) response was submitted under email by a visually impaired resident of the village raising various concerns to the proposal.

Transit Systems Australia being the public bus operator for TfNSW raised no objection to the proposal.

The main traffic related concerns raised (to date) by the residents are outlined below in the table.

Residents Comments	Officers Response
Street resident concern/comments.	
Request for an additional kerb blister island(s) (Our only query pertains to the south-west junction at Victoria Street on the Clissold St corner).	The concern may well be related to the north-eastern corner and not the south-western corner (side of the Village) where a kerb blister is proposed. It is not possible to provide an additional kerb blister island to the north-eastern corner of Victoria Street due to the existing Bus Zone and the road space needed for buses to access the area. Additional kerb blister islands in Clissold Street are not feasible due to the narrowness of the road and the clearances needed for vehicles to enter & exit Clissold Street safely.
Cardinal Freeman Village- Elderly resident concerns/	
comments (inclusive with those of the visual impaired	
 resident). Concerns with deep grooves around corner of Clissold St- request resurfacing as part of 	 The request for resurfacing of the road under the proposal will be referred to the design team of Council to investigate the matter under detailed

Extraordinary Local Traffic Committee Meeting 3 June 2024

proposal.	planning for construction.
pioposai.	
Bus stop relocation concerns.	 No bus stop will be relocated under this proposal.
 Will sight lines improve at this location? Concerns about existing sight lines at Clissold Street. Why is Council proposing another pedestrian arranging at clean leasting to evidting pedestrian 	 Sight lines between pedestrians and traffic will be improved at the corners with the kerb blister islands
crossing at close location to existing pedestrian crossing?Are pram ramps compliant and will they improve	built out into Victoria Street. The islands will be placed within the existing 'No Stopping' zones at the corners. An amendment to plan is made to extend the physical kerb islands towards Clissold Street, by
Victoria Street is referred to as a 'race track' due	tailing them off into the corners. This would ensure that vehicles do not park at the corners and that the necessary sight view is acquired.
to speed and dangerous driving.	
• Residents hope that changes to grade can be made to assist Giselle.	• The existing at -grade pedestrian (zebra) crossing in Clissold Street (under a separate proposal) will be removed, and a new raised pedestrian (zebra) will be constructed further west near towards the Village's
Drop kerbs on the north side of Clissold Street may be a potential trip hazard?	Gate 11.
 Proposed turning radius is too wide allowing vehicles to turn corners at speed. This is exacerbated by removal of the existing raised median islands and replacement road line markings. 	• Yes, new pram ramps will be made complaint. Any old ramps will be rectified to comply within this proposal.
• Relocation of the crossing on Victoria Street will encourage pedestrians to deviate from their walking route to the new crossing point. This is	• There will be sufficient grade variation to all pram ramps irrespective if constructed alone to the corners or incorporated within the kerb -blister islands.
unsafe as pedestrians may decide to cross directly along the alignment of Clissold Street footpath at the intersection of Victoria Street.	• The intention of building the kerb blister islands out as far possible and/or use associated line marking is to narrow the traffic passageway at the intersection to lend and assist in traffic control through the area.
	• The corners will be rebuilt to provide compliant pram ramps and kerbing. The matter of drop kerbs (within the scope of works) will be referred to the design team to investigate under construction detail.
	• The proposed build outs/painted island markings to the corners with associated edge line marking, narrows and channelises the intersection to control and guide traffic movement in the area. The existing narrow (raised) concrete median islands in Clissold Street, in both approaches to Victoria Street are removed and replaced with at-grade stencil marked islands with associated line marking for appropriate separation in traffic.
Suggested Recommendations:	• The relocation of the crossing points across Victoria Street away from the corners provide an improved pedestrian facility with kerb blister islands and new prome costablished to cross at a shorter
An alternative design as advised by 'Better Streets'	pram ramps established to cross at a shorter distance. Pram ramps are not built right at the

to construct korb build outs at interportion and	Viotoria Streat corpora Dedectriana are discouraged
to construct kerb build outs at intersection and include minor narrowing of Clissold Street. Creating slower, tighter turns for cars and heavy vehicles.	Victoria Street corners. Pedestrians are discouraged from crossing right at the corners.
 Identify trip hazards and remove or repair. This is important for aged individuals and individuals with a disability or mobility issues. 	Response to suggested recommendation by resident(s).
 'Better Streets' suggest that the nearby 'Bus Stop' be situated in-lane with the footpath extending into the parking lane so the bus stops traffic only within that lane. The plan shows the 'Bus Stop' being retained with no change to the kerb location for buses travelling south along Victoria Street The bus would need to move from the travel lane to the parking lane to drop-off/pick-up passengers. A build out on the northeast corner of the intersection would allow for safer crossing for pedestrians. 	 Clissold Steet cannot be further narrowed owing to 2- way traffic movement. The kerb blisters islands (in amendment to plan) will be extended in Victoria Street towards Clissold Steet and tailed off in towards the corners. The kerb blister islands are widened out into Victoria Street as far possible, with edge line marking going around the corners. This will sufficiently tighten, control and guide traffic movement around the intersection.
 Request for an additional pedestrian (zebra) crossing along with kerb ramps at this intersection of Victoria Street at Clissold Street to improve safety for pedestrians and visually impaired individuals crossing with the assistance of their 	 Any trip hazards revolving around the proposed scope of works will be further examined under construction detail.
 The existing lighting at the intersection is deemed inadequate. Concerns raised with the safety at the pedestrian (zebra) crossing at Yeo Park and Harland Street. 	• The Bus stop on the eastern side of Victoria Street, north of Clissold Street is maintained as existing. Bus platforms are only limited to locations where current designed buses cannot pull up safely close to the kerb, e.g., Bus Stops located in a short span distance between trees. An out reached bus platform at the corner would pose danger and hazard with buses pulling up 'in lane' and obstructing the view of cross- traffic. A kerb blister island to the western side but no kerb blister island to the eastern side, north of Clissold Street, with complaint aligned pram ramps to both sides of the road, is still considered as an improved cross-over path for pedestrians at a shorter distance.
	• A pedestrian (zebra) crossing is not proposed in Victoria Steet, to the north side of Clissold. Sufficient pedestrian numbers could not be substantiated to consider a crossing over Victoria Street under appropriate Transport for NSW/Council guidelines/policies.
	It was viewed and approved by Council (in principle) that a crossing further up at Robert Street next to the Sydney Private Hospital, would accommodate path movements across Victoria Street, allowing visitors/outpatients of the Sydney Private Hospital to reach out to bus stops on the eastern side and destined movements towards Summer Hill. A pedestrian (zebra) crossing in Victoria Street, south of Robert Street, is yet to be proposed in detail and will be reported separately. It is viewed that this crossing will cater for improved pedestrian access for other community needs in the area.
	Notwithstanding this, kerb blister island(s) with complaint aligned pram ramps are proposed as an alternative facility for improved pedestrian access

Extraordinary Local Traffic Committee Meeting 3 June 2024


across Victoria Street at Clissold Street.
• Lighting in the area is considered appropriate, however Council's Design Section will be asked to relook at this.
• Concerns raised with the safety at the pedestrian (zebra) crossing at Yeo Park and Harland Street will be investigated separately.

CONCLUSION


It is recommended that the detailed amended design plan (10281-A) to install new landscaped blister islands (kerb extension build-outs) and painted island/line marking to all corners of Victoria Street at Clissold Street, realign the 'STOP' lines on both approaches of Clissold Street and remove the central median islands to be replaced with road at-grade stenciled marked islands in Clissold Street as shown in *Attachment 1*, be approved.

ATTACHMENTS

- **1.** Proposed (amended) kerb extensions at the intersection of Victoria Street and Clissold Street, Ashfield.
- **2.** Design Garbage Truck turning paths.








Attachment


`


Attachment





VEHICLE PROFILE FOR SWEPT PATH ANALYSIS





Attachment 2

2

Attachment



